

Revision Number: 005.1 Issue date: 10/05/2018

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: Loctite Epoxy Quick Set Multi-purpose IDH number: 1427733

5 Minute Resin

Product type: Epoxy resin 1395391 1427733 Item number: Restriction of Use: None identified Region: **United States Contact information:**

Company address:

Henkel Corporation Telephone: +1 (860) 571-5100

One Henkel Way MEDICAL EMERGENCY Phone: Poison Control Center Rocky Hill, Connecticut 06067 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC

1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING: CAUSES SKIN IRRITATION.

> MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES SERIOUS EYE IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1

PICTOGRAM(S)



Precautionary Statements

IDH number: 1427733

Prevention: Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling.

Contaminated work clothing should not be allowed out of the workplace. Wear protective

gloves, eye protection, and face protection.

IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several Response:

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off

contaminated clothing.

Storage: Not prescribed

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Epichlorohydrin-4,4'-isopropylidene diphenol resin	25068-38-6	90 - 100

^{*} Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. If symptoms develop and persist, get medical attention.

Skin contact: Immediately flush skin with plenty of water (using soap, if available). Remove

contaminated clothing and footwear. If symptoms develop and persist, get medical attention. Wash clothing before reuse. Thoroughly clean shoes before

reuse.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Get

medical attention.

Ingestion: DO NOT induce vomiting unless directed to do so by medical personnel.

Never give anything by mouth to an unconscious person. Get medical

attention.

Symptoms: See Section 11.

IDH number: 1427733

Notes to physician: Treat symptomatically and supportively.

5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards: Closed containers may rupture (due to build up of pressure) when exposed to

extreme heat. In case of fire, keep containers cool with water spray.

Hazardous combustion products: Oxides of carbon. Phenolics. Toxic fumes. Irritating vapors.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Wear appropriate protective equipment and clothing during clean-up. Prevent

further leakage or spillage if safe to do so. Do not allow product to enter sewer

or waterways.

Clean-up methods: Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Dispose of according to Federal, State and local

governmental regulations.

7. HANDLING AND STORAGE

Handling: Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist.

Wash thoroughly after handling. Use only with adequate ventilation. Keep

container closed.

Storage: Keep container tightly closed and in a cool, well-ventilated place away from

incompatible materials. Keep away from heat, spark and flame. Protect from

direct sunlight.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Epichlorohydrin-4,4'-isopropylidene diphenol resin	None	None	None	None

Engineering controls: Local exhaust ventilation is recommended when general ventilation is not

sufficient to control airborne contamination.

Use a NIOSH approved respirator if ventilation is inadequate. Respiratory protection:

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists.

Skin protection: Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid

Translucent, Clear Color:

Odor: None

Odor threshold: Not available. pH: Not applicable Vapor pressure: 0.03 mm hg

> 260.2 °C (> 500.4 °F) Boiling point/range:

Melting point/ range: Not available.

1.17

Specific gravity: Vapor density: Not available.

Flash point: > 249 °C (> 480.2 °F) Pensky Martens closed cup

Flammable/Explosive limits - lower: Not available. Flammable/Explosive limits - upper: Not available. Autoignition temperature: Not available. Flammability: Not applicable Not available. **Evaporation rate:** Solubility in water: Slight Partition coefficient (n-octanol/water): Not available.

VOC content: 0.1 % (value for resin and hardener together)

Viscosity: Not available. **Decomposition temperature:** Not available.

IDH number: 1427733

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: None under normal processing.

Hazardous decomposition

products:

Oxides of carbon. Phenolics. Toxic fumes. Irritating vapors.

Incompatible materials: Strong oxidizing agents. Strong bases. Strong acids. Amines.

Reactivity: Not available.

Conditions to avoid: Keep away from heat, ignition sources and incompatible materials. Protect from direct sunlight.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

Inhalation: Inhalation of vapors or mists of the product may be irritating to the respiratory system.

Skin contact: Causes skin irritation. May cause allergic skin reaction.

Eye contact: Causes serious eye irritation.

Ingestion: Not expected under normal conditions of use.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
Epichlorohydrin-4,4'-isopropylidene diphenol resin	None	Allergen, Irritant	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Epichlorohydrin-4,4'-isopropylidene diphenol resin	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

IDH number: 1427733

Proper shipping name:Not regulatedHazard class or division:NoneIdentification number:NonePacking group:None

Product name: Loctite Epoxy Quick Set Multi-purpose 5 Minute Resin Page 4 of 5

International Air Transportation (ICAO/IATA)

Proper shipping name: Environmentally hazardous substance, liquid, n.o.s. (Bisphenol-A Epichlorhydrin

resin)

Hazard class or division: 9
Identification number: UN 3082
Packing group: III

Water Transportation (IMO/IMDG)

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-A

Epichlorhydrin resin)

Hazard class or division: 9
Identification number: UN 3082
Packing group: III

Marine pollutant: Bisphenol-A Epichlorhydrin resin

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis.

CERCLA/SARA Section 311/312: Immediate Health

CERCLA/SARA Section 313: None above reporting de minimis.

California Proposition 65: This product contains a chemical known in the State of California to cause cancer.

Canada Regulatory Information

IDH number: 1427733

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Product Safety and Regulatory Affairs

Issue date: 10/05/2018

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.