

Revision Number: 010.0

PRODUCT AND COMPANY IDENTIFICATION 1.

Product name:

Product type/use: Silicone Restriction of Use: Company address: Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067

Loctite Polyseamseal 100% Silicone Sealant None identified

| IDH number: | 1508974 |
|------------------------|----------------------------------|
| Item number: | 1508974 |
| Region: | United States |
| Contact information: | : |
| Telephone: +1 (860) 5 | 571-5100 |
| MEDICAL EMERGEN | ICY Phone: Poison Control Center |
| 1-877-671-4608 (toll f | ree) or 1-303-592-1711 |
| TRANSPORT EMER | GENCY Phone: CHEMTREC |
| 1-800-424-9300 (toll f | ree) or 1-703-527-3887 |
| Internet: www.henkelr | na.com |

HAZARDS IDENTIFICATION 2.

EMERGENCY OVERVIEW NOT CLASSIFIED. READ ENTIRE SAFETY DATA SHEET.

HAZARD CATEGORY

PICTOGRAM(S) None

None

HAZARD CLASS

Precautionary Statements

None

Prevention: Response: Storage: Disposal:

Not prescribed Not prescribed Not prescribed Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s) | CAS Number | Percentage* |
|------------------------|------------|-------------|
| Silicon dioxide | 7631-86-9 | 5 - 10 |

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

| | 4. FIRST AID MEASURES |
|---------------|---|
| Inhalation: | Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. If symptoms develop and persist, get medical attention. |
| Skin contact: | Wipe off paste with paper towel or cloth. Wash with soap and water. If symptoms develop and persist, get medical attention. |
| Eye contact: | Rinse thoroughly with plenty of water, also under the eyelids. If eye irritation persists, consult a specialist. |

| Ingestion: | Do not induce vomiting. If a person feels unwell or symptoms of skin irritation appear, consult a physician. | |
|------------------------------------|--|--|
| Symptoms: | See Section 11. | |
| 5. FIRI | E FIGHTING MEASURES | |
| Extinguishing media: | Water spray (fog), foam, dry chemical or carbon dioxide. | |
| Special firefighting procedures: | Wear self contained breathing apparatus. | |
| Unusual fire or explosion hazards: | In case of fire, keep containers cool with water spray. | |
| Hazardous combustion products: | Oxides of carbon. Oxides of silicon. Formaldehyde. | |

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:

Clean-up methods:

Do not allow product to enter sewer or waterways.

Scrape up as much material as possible. Spilled material will solidify. Store in a partly filled, closed container until disposal. Maintain good ventilation for large spills.

7. HANDLING AND STORAGE

Handling:

Avoid contact with eyes, skin and clothing. Do not handle contact lenses until all sealant has been removed from hands. Residual sealant may transfer to lenses and cause eye irritation.

Storage:

Store in a dry area below 90° F. Keep container closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s) | ACGIH TLV | OSHA PEL | AIHA WEEL | OTHER |
|------------------------|---|--|-----------|-------------------------------------|
| Silicon dioxide | 6 mg/m3 TWA 3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Inhalable particles. | 15 MPPCF TWA Respirable fraction. 50 MPPCF TWA Total dust. 15 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction. 20 MPPCF TWA 0.8 mg/m3 TWA | None | 3 mg/m3 TWA Respirable fraction. |

| Engineering controls: | Ensure adequate ventilation, especially in confined areas. Use local ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits. |
|-------------------------|--|
| Respiratory protection: | Use NIOSH approved respirator if there is potential to exceed exposure limit(s). |
| Eye/face protection: | Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. |
| Skin protection: | Chemical resistant, impermeable gloves. |
| 9. PH | YSICAL AND CHEMICAL PROPERTIES |

Physical state: Color: Odor: Odor threshold: pH: IDH number: 1508974 Paste Translucent Acetic acid Not available. Not available.

| Vapor pressure: | < 10 mm hg (20 °C (68°F)) |
|--|---------------------------|
| Boiling point/range: | Not available. |
| Melting point/ range: | Not available. |
| Specific gravity: | 1.01 at 20 °C (68°F) |
| Vapor density: | Heavier than air. |
| Flash point: | > 93 °C (> 199.4 °F) |
| Flammable/Explosive limits - lower: | 4 % |
| Flammable/Explosive limits - upper: | 19.9 % |
| Autoignition temperature: | Not available. |
| Flammability: | Not applicable |
| Evaporation rate: | Not available. |
| Solubility in water: | Not determined |
| Partition coefficient (n-octanol/water): | Not available. |
| VOC content: | 3.0 %; 30 g/l |
| Viscosity: | Not available. |
| Decomposition temperature: | Not available. |
| | |

10. STABILITY AND REACTIVITY

| Stability: | Stable under normal conditions of storage and use. |
|--------------------------------------|---|
| Hazardous reactions: | Will not occur. |
| Hazardous decomposition products: | Oxides of carbon. Oxides of silicon. Formaldehyde. |
| Incompatible materials: | Oxidizing agents. |
| Reactivity: | Not available. |
| Conditions to avoid: | Prolonged heating at temperatures above 150 °C. Exposure to moisture. |
| | |

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:

Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation:When heated to temperatures exceeding 300° F (150° C) in the presence of air, silicones may
form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and
respiratory sensitizer. Vapors irritate the eyes, nose and throat. Safe handling conditions may
be maintained by keeping formaldehyde vapor concentrations below the OSHA permissible
limit. May cause respiratory tract irritation.Skin contact:Causes skin irritation.
Causes serious eye irritation.
May cause gastrointestinal tract irritation if swallowed.

| Hazardous Component(s) | LD50s and LC50s | Immediate and Delayed Health Effects |
|------------------------|--|--------------------------------------|
| Silicon dioxide | Oral LD50 (Rat) = > 22,500 mg/kg Oral LD50 (Mouse) = > 15,000 mg/kg Inhalation LC50 (Rat, 4 h) = > 2.08 mg/l Inhalation LC50 (Rat, 4 h) = > 0.69 mg/l | Nuisance dust |

| Hazardous Component(s) | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|------------------------|----------------|-----------------|---|
| Silicon dioxide | No | No | No |

12. ECOLOGICAL INFORMATION

Ecological information:

Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Follow all local, state, federal and provincial regulations for disposal. Cured rubber can be incinerated or landfilled following EPA and local regulations.

TRANSPORT INFORMATION 14.

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

| Proper shipping name: | Not regulated |
|---------------------------|---------------|
| Hazard class or division: | None |
| Identification number: | None |
| Packing group: | None |

International Air Transportation (ICAO/IATA)

| Proper shipping name: |
|---------------------------|
| Hazard class or division: |
| Identification number: |
| Packing group: |

Not regulated None None None

Water Transportation (IMO/IMDG)

Proper shipping name: Hazard class or division: Identification number: Packing group:

Not regulated None None None

15. REGULATORY INFORMATION

United States Regulatory Information

| TSCA 8 (b) Inventory Status: | All components are listed as active or are exempt from listing on the Toxic Substances |
|--|--|
| TSCA 12 (b) Export Notification: | Control Act (TSCA) inventory. None above reporting de minimis |
| CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA Section 313: | None above reporting de minimis. Immediate Health, Delayed Health None above reporting de minimis. |
| California Proposition 65: | No California Proposition 65 listed chemicals are known to be present. |
| Canada Regulatory Information | |
| CEPA DSL/NDSL Status: | All components are listed on or are exempt from listing on the Canadian Domestic |

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2, 3, 8, 11

Substances List.

| Prepared by: | Product Safety and Regulatory Affairs |
|--------------|---------------------------------------|
| | |

Issue date: 08/23/2022

IDH number: 1508974

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.