



Revision Number: 003.0

Issue date: 09/24/2021

## 1. PRODUCT AND COMPANY IDENTIFICATION

**Product name:** Loctite PL 400 All Weather  
**Product type/use:** Acrylic Adhesive  
**Restriction of Use:** None identified  
**Company address:**  
 Henkel Corporation  
 One Henkel Way  
 Rocky Hill, Connecticut 06067

**IDH number:** 2136221

**Region:** United States

**Contact information:**

Telephone: +1 (860) 571-5100  
 MEDICAL EMERGENCY Phone: Poison Control Center  
 1-877-671-4608 (toll free) or 1-303-592-1711  
 TRANSPORT EMERGENCY Phone: CHEMTREC  
 1-800-424-9300 (toll free) or 1-703-527-3887  
 Internet: www.henkelna.com

This product contains one or more components regulated under a Significant New Use Rule (SNUR) by the US EPA. See Section 15 for more information.

## 2. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

**WARNING:** FLAMMABLE LIQUID AND VAPOR.  
 CAUSES SERIOUS EYE IRRITATION.  
 MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR  
 REPEATED EXPOSURE.

| HAZARD CLASS                                       | HAZARD CATEGORY |
|--|-----------------|
| FLAMMABLE LIQUID                                   | 3               |
| EYE IRRITATION                                     | 2A              |
| SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE | 2               |

### PICTOGRAM(S)



### Precautionary Statements

**Prevention:** Keep away from heat, sparks, open flames, hot surfaces - no smoking. Keep container tightly closed. No release into water. Use explosion-proof equipment. Use non-sparking tools. Take action to prevent static discharges. Do not breathe vapors, mist, or spray. Wash affected area thoroughly after handling. Wear protective gloves, eye protection, and face protection.

**Response:** If on skin (or hair): Take off immediately all contaminated clothing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if you feel unwell. If eye irritation persists: Get medical attention. In case of fire: Use foam, dry chemical or carbon dioxide to extinguish.

**Storage:** Store in a well-ventilated place. Keep cool.

**Disposal:** Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s) | CAS Number | Percentage* |
|------------------------|------------|-------------|
| Limestone              | 1317-65-3  | 30 - 60     |

IDH number: 2136221

Product name: Loctite PL 400 All Weather

|  |            |         |
|--|------------|---------|
| Urea                                       | 57-13-6    | 1 - 5   |
| Kaolin                                     | 1332-58-7  | 1 - 5   |
| Ethylene glycol                            | 107-21-1   | 1 - 5   |
| acetone                                    | 67-64-1    | 1 - 5   |
| Quartz (SiO <sub>2</sub> ), <1% respirable | 14808-60-7 | 0.1 - 1 |

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

## 4. FIRST AID MEASURES

|                      |  |
|----------------------|--|
| <b>Inhalation:</b>   | Move to fresh air in case of accidental inhalation of vapours.   |
| <b>Skin contact:</b> | Wash affected area immediately with soap and water.  |
| <b>Eye contact:</b>  | Immediately flush eyes with plenty of water for at least 15 minutes. If symptoms develop and persist, get medical attention. |
| <b>Ingestion:</b>    | Consult a physician if necessary.  |
| <b>Symptoms:</b>     | See Section 11.  |

## 5. FIRE FIGHTING MEASURES

|   |  |
|---|--|
| <b>Extinguishing media:</b>               | Carbon dioxide, foam, powder Water fog.  |
| <b>Special firefighting procedures:</b>   | Use water spray to keep fire exposed containers cool and disperse vapors. Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. |
| <b>Unusual fire or explosion hazards:</b> | Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.  |
| <b>Hazardous combustion products:</b>     | Oxides of carbon. Oxides of nitrogen.  |

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

|                                   |  |
|-----------------------------------|--|
| <b>Environmental precautions:</b> | Not available.   |
| <b>Clean-up methods:</b>          | Absorb spill with inert material. Shovel material into appropriate container for disposal. Remove all sources of ignition. |

## 7. HANDLING AND STORAGE

|                  |  |
|------------------|--|
| <b>Handling:</b> | Avoid prolonged or repeated skin contact with this material. Keep away from sources of ignition - no smoking. Keep out of the reach of children. |
| <b>Storage:</b>  | For safe storage, store at or above 0 °C (32°F) Keep from freezing. Store in a cool, dry area. Keep containers closed when not in use.           |

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s)                     | ACGIH TLV   | OSHA PEL  | AIHA WEEL                          | OTHER |
|--|---|---|------------------------------------|-------|
| Limestone                                  | 10 mg/m3 TWA<br>Inhalable particles.<br>3 mg/m3 TWA<br>Respirable particles.<br>10 mg/m3 TWA Total<br>dust. | 5 mg/m3 PEL<br>Respirable fraction.<br>15 mg/m3 PEL Total<br>dust.<br>5 mg/m3 TWA<br>Respirable fraction.<br>50 MPPCF TWA<br>Total dust.<br>15 mg/m3 TWA Total<br>dust.<br>15 MPPCF TWA<br>Respirable fraction.   | None                               | None  |
| Urea                                       | None  | None  | 10 mg/m3 TWA Total<br>particulate. | None  |
| Kaolin                                     | 2 mg/m3 TWA<br>Respirable fraction.   | 5 mg/m3 PEL<br>Respirable fraction.<br>15 mg/m3 PEL Total<br>dust.<br>15 MPPCF TWA<br>Respirable fraction.<br>50 MPPCF TWA<br>Total dust.<br>5 mg/m3 TWA<br>Respirable fraction.<br>15 mg/m3 TWA Total<br>dust.   | None                               | None  |
| Ethylene glycol                            | 25 ppm TWA Vapor<br>fraction<br>50 ppm STEL Vapor<br>fraction<br>10 mg/m3 STEL<br>Aerosol, inhalable.       | None  | None                               | None  |
| acetone                                    | 250 ppm TWA<br>500 ppm STEL   | 1,000 ppm (2,400<br>mg/m3) PEL  | None                               | None  |
| Quartz (SiO <sub>2</sub> ), <1% respirable | 0.025 mg/m3 TWA<br>Respirable fraction.   | 0.05 mg/m3 TWA<br>(Respirable dust.)<br>(Respirable dust.)<br>0.025 mg/m3<br>OSHA_ACT<br>(Respirable dust.)<br>0.05 mg/m3 PEL<br>Respirable dust.<br>2.4 MPPCF TWA<br>Respirable.<br>0.1 mg/m3 TWA<br>Respirable. | None                               | None  |

### Engineering controls:

Use local ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.

### Respiratory protection:

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

### Eye/face protection:

Safety goggles or safety glasses with side shields.

### Skin protection:

Use impermeable gloves and protective clothing as necessary to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Physical state:

Liquid

### Color:

Tan

### Odor:

Acrylic

### Odor threshold:

Not available.

### pH:

8.5

### Vapor pressure:

Not available.

IDH number: 2136221

Product name: Loctite PL 400 All Weather

|   |  |
|---|--|
| <b>Boiling point/range:</b>                     | 100 °C (212°F)   |
| <b>Melting point/ range:</b>                    | Not available.   |
| <b>Specific gravity:</b>                        | 1.367  |
| <b>Vapor density:</b>                           | Not available.   |
| <b>Flash point:</b>                             | 54 °C (129.2 °F)   |
| <b>Flammable/Explosive limits - lower:</b>      | Not available.   |
| <b>Flammable/Explosive limits - upper:</b>      | Not available.   |
| <b>Autoignition temperature:</b>                | Not available.   |
| <b>Flammability:</b>                            | Not applicable   |
| <b>Evaporation rate:</b>                        | Not available.   |
| <b>Solubility in water:</b>                     | Not available.   |
| <b>Partition coefficient (n-octanol/water):</b> | Not available.   |
| <b>VOC content:</b>                             | 0.1 %; 49 g/l (by weight, calculated using CARB method; g/L less water, less exempts calculated using SCAQMD method) |
| <b>Viscosity:</b>                               | 190,000 - 300,000 cp   |
| <b>Decomposition temperature:</b>               | Not available.   |

## 10. STABILITY AND REACTIVITY

|  |  |
|--|--|
| <b>Stability:</b>                        | Stable under normal conditions of storage and use. |
| <b>Hazardous reactions:</b>              | Will not occur.                                    |
| <b>Hazardous decomposition products:</b> | Oxides of carbon. Oxides of nitrogen.              |
| <b>Incompatible materials:</b>           | None known   |
| <b>Reactivity:</b>                       | Not available.                                     |
| <b>Conditions to avoid:</b>              | Heat. Do not freeze.                               |

## 11. TOXICOLOGICAL INFORMATION

|                                     |                                       |
|-------------------------------------|---------------------------------------|
| <b>Relevant routes of exposure:</b> | Inhalation, Skin contact, Eye contact |
|-------------------------------------|---------------------------------------|

### Potential Health Effects/Symptoms

|                      |  |
|----------------------|--|
| <b>Inhalation:</b>   | May cause irritation to nose and throat. Inhalation of high vapor concentrations may produce respiratory irritation, and may cause central nervous system (CNS) depression. Abrasion of cured material such as by sanding or grinding could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of this product causes no such release. |
| <b>Skin contact:</b> | May cause moderate skin irritation.  |
| <b>Eye contact:</b>  | May cause slight irritation to eyes on contact.  |
| <b>Ingestion:</b>    | Not expected to be harmful by ingestion. Ingestion of large amounts may produce gastrointestinal disturbances including irritation, nausea, and diarrhea.  |

| Hazardous Component(s)                     | LD50s and LC50s  | Immediate and Delayed Health Effects  |
|--|--|---|
| Limestone                                  | None   | Nuisance dust   |
| Urea                                       | Oral LD50 (Rat) = 8,471 mg/kg  | Central nervous system, Irritant, Metabolic   |
| Kaolin                                     | Oral LD50 (Rat) = > 5,000 mg/kg<br>Dermal LD50 (Rat) = > 5,000 mg/kg   | Nuisance dust   |
| Ethylene glycol                            | Oral LD50 (Rat) = 5.89 g/kg<br>Oral LD50 (Mouse) = 14.6 g/kg<br>Dermal LD50 (Rabbit) = 9,530 mg/kg   | Blood, Bone Marrow, Central nervous system, Developmental, Eyes, Irritant, Kidney, Liver, Metabolic |
| acetone                                    | Oral LD50 (Mouse) = 5.2 g/kg<br>Oral LD50 (Mouse) = 3,000 mg/kg<br>Oral LD50 (Rabbit) = 5,340 mg/kg<br>Oral LD50 (Rat) = 5,800 mg/kg<br>Oral LD50 (Rat) = 9,800 mg/kg<br>Dermal LD50 (Rabbit) = 20,000 mg/kg<br>Inhalation LC50 (Rat, 4 h) = 76 mg/l<br>Inhalation LC50 (Rat, 4 h) = 50.1 mg/l | Central nervous system, Irritant  |
| Quartz (SiO <sub>2</sub> ), <1% respirable | None   | Immune system, Lung, Some evidence of carcinogenicity   |

| Hazardous Component(s)                     | NTP Carcinogen                | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|--|-------------------------------|-----------------|--|
| Limestone                                  | No                            | No              | No                                       |
| Urea                                       | No                            | No              | No                                       |
| Kaolin                                     | No                            | No              | No                                       |
| Ethylene glycol                            | No                            | No              | No                                       |
| acetone                                    | No                            | No              | No                                       |
| Quartz (SiO <sub>2</sub> ), <1% respirable | Known To Be Human Carcinogen. | Group 1         | Yes                                      |

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Dispose of according to Federal, State and local governmental regulations.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

### U.S. Department of Transportation Ground (49 CFR)

|                                  |               |
|----------------------------------|---------------|
| <b>Proper shipping name:</b>     | Not regulated |
| <b>Hazard class or division:</b> | None          |
| <b>Identification number:</b>    | None          |
| <b>Packing group:</b>            | None          |

### International Air Transportation (ICAO/IATA)

|                                  |           |
|----------------------------------|-----------|
| <b>Proper shipping name:</b>     | Adhesives |
| <b>Hazard class or division:</b> | 3         |
| <b>Identification number:</b>    | UN 1133   |
| <b>Packing group:</b>            | III       |

|  |           |
|--|-----------|
| <b>Water Transportation (IMO/IMDG)</b> |           |
| <b>Proper shipping name:</b>           | ADHESIVES |
| <b>Hazard class or division:</b>       | 3         |
| <b>Identification number:</b>          | UN 1133   |
| <b>Packing group:</b>                  | III       |

## 15. REGULATORY INFORMATION

### United States Regulatory Information

|   |   |
|---|---|
| <b>TSCA 8 (b) Inventory Status:</b>     | All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.  |
| <b>TSCA 5(a) SNUR:</b>                  | This product contains the following component(s) subject to a Significant New Use Rule (SNUR) by the US EPA:<br>Mercury (CAS # 7439-97-6). The SNUR is codified at Section number: 40 CFR 721.10068                       |
| <b>TSCA 12 (b) Export Notification:</b> | None above reporting de minimis   |
| <b>CERCLA/SARA Section 302 EHS:</b>     | None above reporting de minimis.<br>Hydroquinone (CAS# 123-31-9). Formaldehyde (CAS# 50-00-0). Ammonia (CAS# 7664-41-7). Ethylene oxide (CAS# 75-21-8).   |
| <b>CERCLA/SARA Section 311/312:</b>     | Fire, Immediate Health, Delayed Health  |
| <b>CERCLA/SARA Section 313:</b>         | This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Ethylene glycol (CAS# 107-21-1). |
| <b>California Proposition 65:</b>       | This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. This product contains a chemical known in the State of California to cause cancer.                   |

### Canada Regulatory Information

|                              |   |
|------------------------------|---|
| <b>CEPA DSL/NDSL Status:</b> | Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details. |
| <b>CEPA DSL/NDSL Status:</b> | All components are listed on or are exempt from listing on the Canadian Domestic Substances List.   |

## 16. OTHER INFORMATION

**This safety data sheet contains changes from the previous version in sections:** This Safety Data Sheet contains changes from the previous version in Section(s): 8, 11

**Prepared by:** Product Safety and Regulatory Affairs

**Issue date:** 09/24/2021

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.