Safety Data Sheet



Revision Number: 001.7 Issue date: 10/16/2023

PRODUCT AND COMPANY IDENTIFICATION

Product name: **Loctite General Performance Spray IDH** number:

Adhesive

Product type/use: Adhesive Restriction of Use: None identified

Company address:

One Henkel Way Rocky Hill, Connecticut 06067

Henkel Corporation

Region: **United States**

Contact information: Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

2235316

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: EXTREMELY FLAMMABLE AEROSOL.

CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

CAUSES SKIN IRRITATION.

CAUSES SERIOUS EYE IRRITATION. MAY CAUSE DROWSINESS OR DIZZINESS.

CAUSES DAMAGE TO ORGANS.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE AEROSOL.	1
GASES UNDER PRESSURE	Compr. Gas
SKIN IRRITATION	2
EYE IRRITATION	2A
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	1
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3



Precautionary Statements

Disposal:

IDH number: 2235316

Keep away from heat, sparks, open flames, hot surfaces - no smoking. Do not spray on an Prevention:

open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe mist or spray. Wash affected area thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves, eye

protection, and face protection.

IF ON SKIN: Wash with plenty of water. IF INHALED: Remove victim to fresh air and keep at Response:

rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed: Call a poison center or physician. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off

contaminated clothing.

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from Storage:

sunlight. Do not expose to temperatures exceeding 50.DEGREE.C/122.DEGREE.F. Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

3 % of the mixture consists of ingredient(s) of unknown acute toxicity.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*	
Methyl acetate	79-20-9	10 - 30	
acetone	67-64-1	10 - 30	
dimethyl ether	115-10-6	5 - 10	
propane	74-98-6	5 - 10	
Naphtha, hydrotreated light, <0,1%	64742-49-0	5 - 10	
benzene	04742-49-0	3-10	
1,1-Difluoroethane	75-37-6	5 - 10	
CP Styrene, butadiene, divinylbenzene	Proprietary	5 - 10	
n-Heptane	142-82-5	5 - 10	
Alkanes, C12-14-iso	68551-19-9	1 - 5	
Methanol	67-56-1	1 - 5	

^{*} Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: Move to fresh air. In case of adverse health effects seek medical advice.

Skin contact: Wash affected area immediately with soap and water. If symptoms develop

and persist, get medical attention. Remove contaminated clothes.

Eye contact: In case of contact with the eyes, rinse immediately with plenty of water for 15

minutes, and seek immediate medical attention.

Ingestion: If material is ingested, immediately contact a physician or poison control

center. Do not induce vomiting: contains petroleum distillates and/or aromatic solvents. If vomiting occurs, prevent aspiration by keeping the patient's head

below the knees.

Symptoms: See Section 11.

Notes to physician: This material is an aspiration hazard. Potential danger from aspiration must

be weighed against possible oral toxicity when deciding whether to induce

vomiting.

5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Firefighters should wear self-contained breathing apparatus. Water may be

ineffective, but may be used to cool exposed containers to prevent pressure build-up and possible auto-ignition or explosion when exposed to extreme

heat. If water is used, fog nozzles are preferable.

Unusual fire or explosion hazards: Contents under pressure. Do not handle or store near an open flame, heat or

other sources of ignition. Do not puncture or incinerate pressurized containers. Exposure to temperatures above 49°C (120°F) may cause

container to burst.

Hazardous combustion products: Not available.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Prevent further leakage or spillage if safe to do so. Wear appropriate

protective equipment and clothing during clean-up. Do not allow product to

enter sewer or waterways.

IDH number: 2235316 Product name: Loctite General Performance Spray Adhesive

Clean-up methods:

Absorb spill with inert material. Shovel material into appropriate container for disposal. Follow all local, state, federal and provincial regulations for disposal.

HANDLING AND STORAGE

Handling: Keep out of the reach of children. Keep in a cool, well ventilated area. Prevent

contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Ventilate working rooms thoroughly. Avoid naked flames, sparking and sources of ignition. Switch off electrical devices. Do not smoke, do not weld. Do not empty waste into waste water drains. Do not

puncture or incinerate pressurized containers.

For safe storage, store at or below 50 °C (122°F) Storage:

Keep away from heat, spark and flame. Store in a cool, dry, well-ventilated

EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Methyl acetate	200 ppm TWA 250 ppm STEL	200 ppm (610 mg/m3) PEL	None	None
acetone	250 ppm TWA 500 ppm STEL	1,000 ppm (2,400 mg/m3) PEL	None	None
dimethyl ether	None	None	1,000 ppm (1,880 mg/m3) TWA	None
propane	D: Simple asphyxiant, EX: Explosion hazard (Simple asphyxiant.)	1,000 ppm (1,800 mg/m3) PEL	None	None
Naphtha, hydrotreated light, <0,1% benzene	None	100 ppm (400 mg/m3) PEL	None	None
1,1-Difluoroethane	None	None	1,000 ppm (2,700 mg/m3) TWA	None
CP Styrene, butadiene, divinylbenzene	None	None	None	None
n-Heptane	400 ppm TWA 500 ppm STEL	500 ppm (2,000 mg/m3) PEL	None	None
Alkanes, C12-14-iso	None	None	None	None
Methanol	200 ppm TWA 250 ppm STEL (SKIN)	200 ppm (260 mg/m3) PEL	None	None

Engineering controls: Provide local and general exhaust ventilation to effectively remove and

prevent buildup of any vapors or mists generated from the handling of this

product.

Respiratory protection: If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or

vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

Eye/face protection: Safety goggles or safety glasses with side shields.

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin

contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Aerosol no valuation Color: Odor: Of hydrocarbons Odor threshold: Not available. Not available. Vapor pressure: Not available. Boiling point/range: 52 °C (125.6 °F)

Melting point/ range: Not available. Vapor density: Not available.

-104.4 °C (-155.92 °F) Flammable/Explosive limits - lower: Not available.

Flammable/Explosive limits - upper: Not available. Autoignition temperature: Not applicable

Flash point:

IDH number: 2235316 Product name: Loctite General Performance Spray Adhesive Extremely flammable aerosol.

Flammability: Evaporation rate: Not available. Solubility in water: Insoluble Partition coefficient (n-octanol/water): Not available.

VOC content: 28.7 %; 890 g/l (by weight, calculated using CARB method; g/L less water,

less exempts calculated using SCAQMD method)

Viscosity: Not available. **Decomposition temperature:** Not available.

STABILITY AND REACTIVITY

Stability: Not available.

Hazardous reactions: None under normal processing.

Hazardous decomposition

products:

IDH number: 2235316

Oxides of carbon. Irritating vapors.

Incompatible materials: Strong oxidizing agents.

Reactivity: Not available.

Do not puncture, incinerate, or expose to temperatures above 48.9 $^{\circ}$ C (120 $^{\circ}$ F). Heat, flames, sparks and other sources of ignition. Store away from incompatible materials. Conditions to avoid:

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation: May be harmful if inhaled. Intentional misuse by deliberately concentrating and inhaling the

contents may be harmful or fatal.

Prolonged and/or repeated skin contact may result in mild irritation or redness. Repeated or prolonged contact can result in drying of skin. Symptoms may include redness, burning, drying, Skin contact:

cracking and skin burns.

Eye contact: Symptoms can include irritation, redness, scratching of the cornea, and tearing. Mild eye

irritation.

Ingestion: May be harmful if swallowed. Aspiration may occur during swallowing or vomiting, resulting in

lung damage.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
Methyl acetate	Oral LD50 (Rabbit) = 3.7 g/kg	Blood, Central nervous system, Eyes, Irritant	
acetone	Oral LD50 (Mouse) = 5.2 g/kg Oral LD50 (Mouse) = 3,000 mg/kg Oral LD50 (Rabbit) = 5,340 mg/kg Oral LD50 (Rat) = 5,800 mg/kg Oral LD50 (Rat) = 9,800 mg/kg Dermal LD50 (Rabbit) = 20,000 mg/kg Inhalation LC50 (Rat, 4 h) = 76 mg/l Inhalation LC50 (Rat, 4 h) = 50.1 mg/l	Central nervous system, Irritant	
dimethyl ether	Inhalation LC50 (Rat, 4 h) = 164000 ppm Inhalation LC50 (Rat, 4 h) = > 20000 ppm	Irritant, Central nervous system	
propane	Inhalation LC50 (Rat, 4 h) = > 13023 ppm Inhalation LC50 (Rat, 4 h) = > 13023 ppm	Cardiac, Central nervous system, Irritant	
Naphtha, hydrotreated light, <0,1% benzene	Inhalation LC50 (Rat, 4 h) = $> 5,610$ mg/m3 Inhalation LC50 (Rat, 4 h) = $> 7,630$ mg/m3	Central nervous system, Irritant, Kidney, Lung	
1,1-Difluoroethane	Inhalation LC50 (Rat, 4 h) = > 437500 ppm	Cardiac, Central nervous system, Developmental, Irritant, Respiratory	
CP Styrene, butadiene, divinylbenzene	None	No Records	
n-Heptane	Inhalation LC50 (Rat, 4 h) = > 73.5 mg/l Inhalation LC50 (Rat, 4 h) = > 29.29 mg/l	Central nervous system, Irritant	
Alkanes, C12-14-iso	None	No Data	
Methanol	Oral LD50 (Rat) = 5,628 mg/kg Oral LD50 (Mouse) = 7,300 mg/kg Oral LD50 (Rabbit) = 14.4 g/kg Dermal LD50 (Rabbit) = 15,800 mg/kg	Eyes, Irritant, Metabolic, Nervous System	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Methyl acetate	No	No	No
acetone	No	No	No
dimethyl ether	No	No	No
propane	No	No	No
Naphtha, hydrotreated light, <0,1% benzene	No	No	No
1,1-Difluoroethane	No	No	No
CP Styrene, butadiene, divinylbenzene	No	No	No
n-Heptane	No	No	No
Alkanes, C12-14-iso	No	No	No
Methanol	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

IDH number: 2235316

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Aerosols Hazard class or division: Identification number: **UN 1950** Packing group: None DOT Hazardous Substance(s): Acetone

International Air Transportation (ICAO/IATA)

Proper shipping name: Aerosols, flammable

Hazard class or division: Identification number: UN 1950 Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: AEROSOLS (Heptanes)

Hazard class or division: 2.1 UN 1950 Identification number: Packing group: None Marine pollutant: Heptanes

REGULATORY INFORMATION

United States Regulatory Information

TSCA 12 (b) Export Notification:

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances

Control Act (TSCA) inventory. None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis.

CERCLA/SARA Section 311/312: Immediate Health, Delayed Health, Fire, Sudden Release

CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of

section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40

CFR 372). Methanol (CAS# 67-56-1).

Methyl acetate (CAS# 79-20-9) 100 lbs. (45.4 kg) **CERCLA Reportable quantity:**

acetone (CAS# 67-64-1) 5,000 lbs. (2,270 kg) dimethyl ether (CAS# 115-10-6) 100 lbs. (45.4 kg) propane (CAS# 74-98-6) 100 lbs. (45.4 kg) n-Heptane (CAS# 142-82-5) 100 lbs. (45.4 kg)

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: This Safety Data Sheet contains changes from the previous version in Section(s): 2,3,10,11,15,16

Prepared by: Product Safety and Regulatory Affairs

Issue date: 10/16/2023

IDH number: 2235316 Product name: Loctite General Performance Spray Adhesive **DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.

IDH number: 2235316