



## Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 23

PATTEX PU FOAM FIX&FILL

SDS No. : 528637  
V004.0

Revision: 29.01.2024

printing date: 13.11.2024

Replaces version from: 09.06.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

PATTEX PU FOAM FIX&FILL

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Foam, 1-component with propellant gas

#### 1.3. Details of the supplier of the safety data sheet

Henkel Jebal Ali FZCO  
PO Box 61341 - Jebel Ali  
Dubai

Utd.Arab.Emir.

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or [www.henkel-adhesives.com](http://www.henkel-adhesives.com).

#### 1.4. Emergency telephone number

HAAD Poison and Drug Information Center UAE, TOLL FREE TEL. NUMBER 800-424

# Safety Data Sheet according to (EC) No 1907/2006 as amended

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification (CLP):

Flammable aerosols	Category 1
H222 Extremely flammable aerosol.	
H229 Pressurized container: May burst if heated.	
Skin irritation	Category 2
H315 Causes skin irritation.	
Serious eye irritation	Category 2
H319 Causes serious eye irritation.	
Respiratory sensitizer	Category 1
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
Skin sensitizer	Category 1
H317 May cause an allergic skin reaction.	
Carcinogenicity	Category 2
H351 Suspected of causing cancer.	
Specific target organ toxicity - single exposure	Category 3
H335 May cause respiratory irritation.	
Target organ: respiratory tract irritation	
Specific target organ toxicity - repeated exposure	Category 2
H373 May cause damage to organs through prolonged or repeated exposure.	
Acute toxicity	Category 4
H332 Harmful if inhaled.	
Effects on or via lactation	
H362 May cause harm to breast-fed children.	
Chronic hazards to the aquatic environment	Category 4
H413 May cause long lasting harmful effects to aquatic life.	

### 2.2. Label elements

#### Label elements (CLP):

##### Hazard pictogram:



##### Contains

Diphenylmethane diisocyanate, isomers and homologues  
alkanes, C14-17, chloro

##### Signal word:

Danger

# Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No.: 528637 V004.0 PATTEX PU FOAM FIX&FILL

Page 3 of 23

<b>Hazard statement:</b>	H222 Extremely flammable aerosol. H229 Pressurized container: May burst if heated. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H332 Harmful if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation. H351 Suspected of causing cancer. H362 May cause harm to breast-fed children. H373 May cause damage to organs through prolonged or repeated exposure.  H413 May cause long lasting harmful effects to aquatic life.
<b>Precautionary statement:</b>	P102 Keep out of reach of children.
<b>Precautionary statement: Prevention</b>	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P260 Do not breathe mist/vapours. P263 Avoid contact during pregnancy and while nursing. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/eye protection.
<b>Precautionary statement: Storage</b>	P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50.DEGREE.C/122.DEGREE.F.
<b>Precautionary statement: Disposal</b>	P501 Dispose of contents/container in accordance with national regulation.

## 2.3. Other hazards

Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

Information according to XVII. 56 REACH

Solvents contained in the product evaporate during processing and their vapors can form explosive/highly inflammable air/vapor mixtures.

Pregnant women should absolutely avoid inhalation and skin contact.

**Following substances are present in a concentration  $\geq$  the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):**

alkanes, C14-17, chloro 85535-85-9	PBT/vPvB
---------------------------------------	----------

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

# Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No.: 528637 V004.0 PATTEX PU FOAM FIX&FILL

Page 4 of 23

## Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number	content	Classification
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9		20- 40 %	Carc. 2 H351 Acute Tox. 4; Inhalation H332 STOT RE 2 H373 Eye Irrit. 2 H319 STOT SE 3 H335 Skin Irrit. 2 H315 Resp. Sens. 1 H334 Skin Sens. 1 H317
4,4'- methylenediphenyl diisocyanate 101-68-8	202-966-0	10- 20 %	Carc. 2 H351 Acute Tox. 4; Inhalation H332 STOT RE 2 H373 Eye Irrit. 2 H319 STOT SE 3 H335 Skin Irrit. 2 H315 Resp. Sens. 1 H334 Skin Sens. 1 H317
alkanes, C14-17, chloro 85535-85-9	287-477-0	10- 20 %	Aquatic Acute 1 H400 Lact. H362 Aquatic Chronic 1 H410 ===== EU. REACH Candidate List of Substances of Very High Concern for Authorization (SVHC) EU. REACH Candidate List of Substances of Very High Concern for Authorization (SVHC)
dimethyl ether 115-10-6	204-065-8	5- < 10 %	Flam. Gas 1A H220 Press. Gas Liquef. Gas H280
Petroleum gases, liquefied 68476-85-7	270-704-2	5- < 10 %	Flam. Gas 1A H220 Press. Gas H280, H281
Isobutane 75-28-5	200-857-2	5- < 10 %	Flam. Gas 1A H220 Press. Gas Liquef. Gas H280
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	227-534-9	1- < 5 %	STOT RE 2 H373 Carc. 2 H351 Acute Tox. 4; Inhalation H332 Eye Irrit. 2 H319 STOT SE 3 H335 Skin Irrit. 2 H315

# Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No.: 528637 V004.0 PATTEX PU FOAM FIX&FILL

Page 5 of 23

			Skin Sens. 1 H317 Resp. Sens. 1 H334
2,2'-Methylenediphenyl diisocyanate 2536-05-2	219-799-4	0,01- < 0,1 %	STOT RE 2 H373 Carc. 2 H351 Acute Tox. 4; Inhalation H332 Eye Irrit. 2 H319 STOT SE 3 H335 Skin Irrit. 2 H315 Resp. Sens. 1 H334 Skin Sens. 1 H317

For full text of the H - statements and other abbreviations see section 16 "Other information".  
Substances without classification may have community workplace exposure limits available.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

General information:

In case of adverse health effects seek medical advice.

Inhalation:

Move to fresh air, consult doctor if complaint persists.  
Delayed effects possible after inhalation.

Skin contact:

Fresh foam : Wipe off affected skin area immediately with a soft cloth and then remove residues with vegetable oil; apply skin care product. Cured foam can be removed only mechanically.

Eye contact:

Immediately flush eyes with soft jet of water or eye rinse solution for at least 5 minutes. If pains remain (intensive smarting, sensitivity to light, visual disturbance) continue flushing and contact/seek doctor or hospital.

Ingestion:

Rinse mouth, do not induce vomiting, consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

SKIN: Redness, inflammation.

Causes serious eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

## SECTION 5: Firefighting measures

# Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No.: 528637 V004.0 PATTEX PU FOAM FIX&FILL

Page 6 of 23

## 5.1. Extinguishing media

### Suitable extinguishing media:

carbon dioxide, foam, powder, water spray jet, fine water spray

### Extinguishing media which must not be used for safety reasons:

High pressure waterjet

## 5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>) can be released.

In the event of fire, isocyanate vapors may be formed.

## 5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Wear protective equipment.

### Additional information:

Cool endangered containers with water spray jet.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment.

Avoid contact with skin and eyes.

Ensure adequate ventilation.

Danger of slipping on spilled product.

### 6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

### 6.3. Methods and material for containment and cleaning up

Remove with liquid-absorbing material (sand, peat, sawdust).

Dispose of contaminated material as waste according to Section 13.

### 6.4. Reference to other sections

See advice in section 8

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

During processing and drying after adhesion, ventilate well. Avoid all sources of fire such as stoves and ovens. Switch off all electrical devices such as parabolic heaters, hot plates, storage heaters etc. in good time for them to have cooled down before commencing work. Avoid all sparks, including those occurring at electrical switches and devices.

Ventilate working rooms thoroughly. Avoid naked flames, sparking and sources of ignition. Switch off electrical devices. Do not smoke, do not weld. Do not waste into waste water drains.

Transport by automobile: leave the container wrapped in a cloth in the trunk, never in the passenger area.

Avoid skin and eye contact.

### Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Remove any dirt that gets onto the skin with vegetable oil; skin care.

### 7.2. Conditions for safe storage, including any incompatibilities

For pressurized can: protect from direct sunshine and temperatures above 50°C.

Storage at 5 to 25°C is recommended.

Keep container tightly sealed.

Store in a cool, well-ventilated place.

Do not store together with oxidants.

Do not store together with flammable solutions.

Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

# Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No.: 528637 V004.0 PATTEX PU FOAM FIX&FILL

Page 7 of 23

## 7.3. Specific end use(s)

Foam, 1-component with propellant gas

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational Exposure Limits

Valid for  
Utd.Arab.Emir.

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
4,4'-Methylenediphenyl diisocyanate 101-68-8 [DIPHENYL METHANE DI ISOCYANATE [METHYLENE BISPHENYL ISOCYANATE (MDI)]]	0,005	0,051	Time Weighted Average (TWA):		AD TLV
4,4'-Methylenediphenyl diisocyanate 101-68-8 [DIPHENYL METHANE DI ISOCYANATE]	0,005	0,051	Time Weighted Average (TWA):		GCC TLV
4,4'-Methylenediphenyl diisocyanate 101-68-8 [DIPHENYLMETHANE DIISOCYANATE]	0,005	0,051	Time Weighted Average (TWA):		UAE OEL
Petroleum gases, liquefied 68476-85-7 [L.P.G (LIQUEFIED PETROLEUM GAS)]	1.000	1.800	Time Weighted Average (TWA):		AD TLV
Petroleum gases, liquefied 68476-85-7 [LPG ( LIQUIDIFIED PETROLEUM GAS )]	1.000		Time Weighted Average (TWA):		DB OEL
Petroleum gases, liquefied 68476-85-7 [L.P.G]	1.000	1.800	Time Weighted Average (TWA):		GCC TLV
Petroleum gases, liquefied 68476-85-7 [L.P.G.]	1.000	1.800	Time Weighted Average (TWA):		UAE OEL
Isobutane 75-28-5 [ALIPHATIC HYDROCARBON GASES ALKANE [C1-C4]]	800		Time Weighted Average (TWA):		AD TLV

# Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No.: 528637 V004.0 PATTEX PU FOAM FIX&FILL

Page 8 of 23

## Occupational Exposure Limits

Valid for  
Bharain

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
4,4'-Methylenediphenyl diisocyanate 101-68-8 [DIPHENYL METHANE DIISOCYANATE]	0,005	0,051	Time Weighted Average (TWA):		BH TLV
4,4'-Methylenediphenyl diisocyanate 101-68-8 [DIPHENYL METHANE DI ISOCYANATE]	0,005	0,051	Time Weighted Average (TWA):		GCC TLV
Petroleum gases, liquefied 68476-85-7 [L.P.G]	1.000	1.800	Time Weighted Average (TWA):		BH TLV
Petroleum gases, liquefied 68476-85-7 [L.P.G]	1.000	1.800	Time Weighted Average (TWA):		GCC TLV

## Occupational Exposure Limits

Valid for  
Egypt

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
4,4'-Methylenediphenyl diisocyanate 101-68-8 [METHYLENE BISPHENYL DIISOCYANATE (MDI)]	0,005	0,051	Time Weighted Average (TWA):		EG OEL
Petroleum gases, liquefied 68476-85-7 [Liquified petroleum gas]	1.000	1.800	Time Weighted Average (TWA):		EG OEL

## Occupational Exposure Limits

Valid for  
Jordan

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
4,4'-Methylenediphenyl diisocyanate 101-68-8 [DIPHENYLMETHANE DIISOCYANATE]	0,02	0,2	Time Weighted Average (TWA):		JO TLV

## Occupational Exposure Limits

Valid for  
Kuwait

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Petroleum gases, liquefied 68476-85-7 [L.P.G]	1.000	1.800	Time Weighted Average (TWA):		GCC TLV
Petroleum gases, liquefied 68476-85-7 [LIQUID PETROLUEM GAS (LPG)]	2.000		Harmful Concentration for risk to health and life:		KW OEL
Petroleum gases, liquefied 68476-85-7	1.000	1.800	Time Weighted Average (TWA):		KW OEL



# Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No.: 528637 V004.0 PATTEX PU FOAM FIX&FILL

Page 9 of 23

[LIQUID PETROLUEM GAS (LPG)]					
------------------------------	--	--	--	--	--

## Occupational Exposure Limits

Valid for  
Israel

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Diphenylmethane diisocyanate, isomers and homologs 9016-87-9 [ISOCYANATES]	0,005		Time Weighted Average (TWA):		IL OEL
Diphenylmethane diisocyanate, isomers and homologs 9016-87-9 [ISOCYANATES]	0,0025		Action level (AL):		IL OEL
Diphenylmethane diisocyanate, isomers and homologs 9016-87-9 [ISOCYANATES]	0,02		Short-term exposure limit (STEL):		IL OEL
4,4'-Methylenediphenyl diisocyanate 101-68-8 [METHYLENE BISPHENYL ISOCYANATE (MDI)]	0,005		Time Weighted Average (TWA):		IL OEL
Isobutane 75-28-5 [Butane, all isomers]	1.000		Short-term exposure limit (STEL):		IL OEL
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1 [ISOCYANATES]	0,0025		Action level (AL):		IL OEL
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1 [ISOCYANATES]	0,005		Time Weighted Average (TWA):		IL OEL
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1 [ISOCYANATES]	0,02		Short-term exposure limit (STEL):		IL OEL
2,2'-Methylenediphenyl diisocyanate 2536-05-2 [ISOCYANATES]	0,005		Time Weighted Average (TWA):		IL OEL
2,2'-Methylenediphenyl diisocyanate 2536-05-2 [ISOCYANATES]	0,02		Short-term exposure limit (STEL):		IL OEL
2,2'-Methylenediphenyl diisocyanate 2536-05-2 [ISOCYANATES]	0,0025		Action level (AL):		IL OEL

## Occupational Exposure Limits

Valid for  
Kenya

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Diphenylmethane diisocyanate, isomers and homologs 9016-87-9 [ISOCYANATES, ALL (AS-NCO)]		0,07	Short term OEL-CL:		KE OEL-CL
Diphenylmethane diisocyanate, isomers and homologs 9016-87-9 [ISOCYANATES, ALL (AS-NCO)]		0,02	Time-weighted average (TWA) OEL-CL:		KE OEL-CL
4,4'-Methylenediphenyl diisocyanate 101-68-8 [ISOCYANATES, ALL (AS-NCO)]		0,02	Time-weighted average (TWA) OEL-CL:		KE OEL-CL
4,4'-Methylenediphenyl diisocyanate 101-68-8		0,07	Short term OEL-CL:		KE OEL-CL

# Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No.: 528637 V004.0 PATTEX PU FOAM FIX&FILL

Page 10 of 23

[ISOCYANATES, ALL (AS-NCO)]					
4,4'-Methylenediphenyl diisocyanate 101-68-8 [4,4'-METHYLENE-DIPHENYL DIISOCYANATE (MDI)]		0,02		Time-weighted average (TWA) OEL-RL:	KE OEL-RL
4,4'-Methylenediphenyl diisocyanate 101-68-8 [4,4'-METHYLENE-DIPHENYL DIISOCYANATE (MDI)]		0,07		Short-term OEL-RL:	KE OEL-RL
Petroleum gases, liquefied 68476-85-7 [LIQUIFIED PETROLEUM GAS (LPG)]	1.250	2.250		Short-term OEL-RL:	KE OEL-RL
Petroleum gases, liquefied 68476-85-7 [LIQUIFIED PETROLEUM GAS (LPG)]	1.000	1.800		Time-weighted average (TWA) OEL-RL:	KE OEL-RL
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1 [ISOCYANATES, ALL (AS-NCO)]		0,02		Time-weighted average (TWA) OEL-CL:	KE OEL-CL
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1 [ISOCYANATES, ALL (AS-NCO)]		0,07		Short term OEL-CL:	KE OEL-CL
2,2'-Methylenediphenyl diisocyanate 2536-05-2 [ISOCYANATES, ALL (AS-NCO)]		0,07		Short term OEL-CL:	KE OEL-CL
2,2'-Methylenediphenyl diisocyanate 2536-05-2 [ISOCYANATES, ALL (AS-NCO)]		0,02		Time-weighted average (TWA) OEL-CL:	KE OEL-CL

## Biological Exposure Indices:

None

## 8.2. Exposure controls:

### Respiratory protection:

The product should only be used at workplaces with intensive ventilation/extraction. If intensive ventilation/extraction is not possible then self-contained independent respiratory protection should be worn.

### Hand protection:

Use attached gloves. Perforation time < 5 minutes.

### Eye protection:

Goggles which can be tightly sealed.  
Protective eye equipment should conform to EN166.

### Skin protection:

Suitable protective clothing  
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

### Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance	pressurized can liquid brownish
Odor	ether-like
Odour threshold	No data available / Not applicable

# Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No.: 528637 V004.0 PATTEX PU FOAM FIX&FILL

Page 11 of 23

pH	Not applicable, Product is non-soluble (in water).
Initial boiling point	-42 °C (-43.6 °F)
Flash point	Not applicable
Decomposition temperature	No data available / Not applicable
Vapour pressure (20 °C (68 °F))	0,5 MPaReferring to liquefied propellant at 20 °C
Density (20 °C (68 °F))	1 g/cm <sup>3</sup>
Bulk density	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic) (40 °C (104 °F); )	> 20,5 mm <sup>2</sup> /s
Explosive properties	No data available / Not applicable
Solubility (qualitative) (20 °C (68 °F); Solvent: Water)	Not soluble, reacts with water to cure and release CO <sub>2</sub> .
Solidification temperature	No data available / Not applicable
Melting point	Not applicable, Product is a liquid
Flammability	No data available / Not applicable
Auto-ignition temperature	350 °C (662 °F)
Explosive limits lower	1,5 % (V)
Partition coefficient: n-octanol/water	No data available / Not applicable
Evaporation rate	No data available / Not applicable
Vapor density (20 °C)	1,7
Oxidising properties	No data available / Not applicable

## 9.2. Other information

No data available / Not applicable

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reaction with water, formation of CO<sub>2</sub>  
Pressure build-up in closed containers.  
Reaction with water, alcohols, amines.

### 10.2. Chemical stability

Stable under recommended storage conditions.

### 10.3. Possibility of hazardous reactions

See section reactivity

### 10.4. Conditions to avoid

Temperatures over appr. 50 °C  
Humidity

### 10.5. Incompatible materials

See section reactivity.

### 10.6. Hazardous decomposition products

At higher temperatures isocyanate may be released.  
Carbon dioxide is generated under contact with moisture, leading to pressure in the cans. Danger of cans bursting!

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### General toxicological information:

Cross-reactions with other isocyanate compounds are possible.

# Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No.: 528637 V004.0 PATTEX PU FOAM FIX&FILL

Page 12 of 23

## Inhalative toxicity:

The toxicity of the product is due to its narcotic effect after inhalation.

In the event of protracted or repeated exposure, damage to health cannot be excluded.

## Acute oral toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	LD50	> 2.000 mg/kg	oral		rat	OECD Guideline 401 (Acute Oral Toxicity)
4,4'- methylenediphenyl diisocyanate 101-68-8	LD50	> 2.000 mg/kg	oral		rat	other guideline:
alkanes, C14-17, chloro 85535-85-9	LD50	> 4.000 mg/kg	oral		rat	not specified
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	LD50	> 2.000 mg/kg	oral		rat	other guideline:
2,2'-Methylenediphenyl diisocyanate 2536-05-2	LD50	> 2.000 mg/kg	oral		rat	EU Method B.1 (Acute Toxicity (Oral))

## Acute inhalative toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	Acute toxicity estimate (ATE)	1,5 mg/l	dust/mist	4 h		Expert judgement
dimethyl ether 115-10-6	LC50	164000 ppm	gas	4 h	rat	not specified
Petroleum gases, liquefied 68476-85-7	LC50	539600 ppm	gas	2 h	mouse	not specified
Isobutane 75-28-5	LC50	260200 ppm	gas	4 h	mouse	not specified

## Acute dermal toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	LD50	> 9.400 mg/kg	dermal		rat	OECD Guideline 402 (Acute Dermal Toxicity)
4,4'- methylenediphenyl diisocyanate 101-68-8	LD50	> 9.400 mg/kg	dermal		rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
alkanes, C14-17, chloro 85535-85-9	LD50	> 2.800 mg/kg	dermal		rat	not specified
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	LD50	> 9.400 mg/kg	dermal		rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
2,2'-Methylenediphenyl diisocyanate 2536-05-2	LD50	> 9.400 mg/kg	dermal		rabbit	OECD Guideline 402 (Acute Dermal Toxicity)

# Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No.: 528637 V004.0 PATTEX PU FOAM FIX&FILL

Page 13 of 23

## Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
4,4'- methylenediphenyl diisocyanate 101-68-8	irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
alkanes, C14-17, chloro 85535-85-9	slightly irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

## Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	irritating		human	Weight of evidence
4,4'- methylenediphenyl diisocyanate 101-68-8	irritating		human	Weight of evidence

# Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No.: 528637 V004.0 PATTEX PU FOAM FIX&FILL

Page 14 of 23

## Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	sensitising	Skin sensitisation	guinea pig	OECD Guideline 406 (Skin Sensitisation)
4,4'-methylenediphenyl diisocyanate 101-68-8	sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
4,4'-methylenediphenyl diisocyanate 101-68-8	sensitising	Respiratory sensitisation	guinea pig	not specified
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	sensitising	Respiratory sensitisation	guinea pig	not specified
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
2,2'-Methylenediphenyl diisocyanate 2536-05-2	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
2,2'-Methylenediphenyl diisocyanate 2536-05-2	sensitising	Respiratory sensitisation	guinea pig	not specified

# Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No.: 528637 V004.0 PATTEX PU FOAM FIX&FILL

Page 15 of 23

## Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		EU Method B.13/14 (Mutagenicity)
4,4'- methylenediphenyl diisocyanate 101-68-8	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		EU Method B.13/14 (Mutagenicity)
4,4'- methylenediphenyl diisocyanate 101-68-8	negative	inhalation		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
dimethyl ether 115-10-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
dimethyl ether 115-10-6	negative	inhalation: gas		Drosophila melanogaster	equivalent or similar to OECD Guideline 477 (Genetic Toxicology: Sex-linked Recessive Lethal Test in Dros. melanog.)
Petroleum gases, liquefied 68476-85-7	negative	inhalation: gas		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Isobutane 75-28-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Isobutane 75-28-5	negative	oral: feed		Drosophila melanogaster	not specified
	negative	inhalation: gas		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
o-(p- Isocyanatobenzyl)phenyl isocyanate 5873-54-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
o-(p- Isocyanatobenzyl)phenyl isocyanate 5873-54-1	negative	inhalation		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
2,2'-Methylenediphenyl diisocyanate 2536-05-2	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
2,2'-Methylenediphenyl diisocyanate 2536-05-2	negative	inhalation		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

# Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No.: 528637 V004.0 PATTEX PU FOAM FIX&FILL

Page 16 of 23

## Carcinogenicity:

Hazardous components CAS-No.	Result	Species	Sex	Exposure timeFrequency of treatment	Route of application	Method
4,4'-methylenediphenyl diisocyanate 101-68-8	carcinogenic	rat	male/female	2 y 6 h/d	inhalation: aerosol	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
dimethyl ether 115-10-6	not carcinogenic	rat	male/female	2 y 6 h/d, 5 d/w	inhalation	equivalent or similar OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
o-(p- Isocyanatobenzyl)phenyl isocyanate 5873-54-1	carcinogenic	rat	male/female	2 y 6 h/d, 5 d/w	inhalation: aerosol	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
2,2'-Methylenediphenyl diisocyanate 2536-05-2	carcinogenic	rat	male/female	2 y 6 h/d, 5 d/w	inhalation: aerosol	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)



# Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No.: 528637 V004.0 PATTEX PU FOAM FIX&FILL

Page 17 of 23

## Reproductive toxicity:

Hazardous substances CAS-No.	Result / Classification	Species	Exposure time	Species	Method
dimethyl ether 115-10-6	NOAEL P = 2.5 %	other inhalation: gas	2 y	rat	other guideline:
	NOAEL P = 1.6 %	screening inhalation: gas	M: 30 d / F: 51 d	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Petroleum gases, liquefied 68476-85-7	NOAEL P = 10000 ppm	Fertility inhalation: gas	13 w	rat	not specified
Isobutane 75-28-5	NOAEL P = 21,4 mg/l NOAEL F1 = 21,4 mg/l	screening inhalation: gas		rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

## Repeated dose toxicity

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	NOAEL=0,0002 mg/l	inhalation: aerosol	2 y6 h per d, 5 d per week	rat	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
4,4'- methylenediphenyl diisocyanate 101-68-8	NOAEL=0,0002 mg/l	inhalation: aerosol	main: 2 y; satellite:1 y6 h/d; 5 d/w	rat	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
dimethyl ether 115-10-6	NOAEL=47,106 mg/12.5 %	inhalation: gas	2 y6 h/d; 5 d/w	rat	equivalent or similar to OECD Guideline 452 (Chronic Toxicity Studies)
Petroleum gases, liquefied 68476-85-7	NOAEL=10000 ppm	inhalation: gas	14 w6 h/d, 5 d/w	rat	equivalent or similar to OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)
Isobutane 75-28-5	NOAEL=9000 ppm	inhalation: gas	28 d6 h/d, 7 d/w	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
o-(p- Isocyanatobenzyl)phenyl isocyanate 5873-54-1	NOAEL=0,2 mg/m <sup>3</sup>	inhalation: aerosol	2 y6 h/d, 5 d/w	rat	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
2,2'-Methylenediphenyl diisocyanate 2536-05-2	NOAEL=0,2 mg/m <sup>3</sup>	inhalation: aerosol	2 y6 h/d, 5 d/w	rat	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

## SECTION 12: Ecological information

### General ecological information:

Do not empty into drains, soil or bodies of water.

# Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No.: 528637 V004.0 PATTEX PU FOAM FIX&FILL

Page 18 of 23

## 12.1. Toxicity

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	LC50	> 1.000 mg/l	Fish	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	EC50	> 1.000 mg/l	Daphnia	24 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	EC50	> 1.640 mg/l	Algae	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	EC50	> 100 mg/l	Bacteria	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	NOEC	10 mg/l	chronic Daphnia	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
4,4'-methylenediphenyl diisocyanate 101-68-8	LL50	> 100 mg/l	Fish	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
4,4'-methylenediphenyl diisocyanate 101-68-8	EC50	> 100 mg/l	Daphnia	48 h	Daphnia magna	EU Method C.2 (Acute Toxicity for Daphnia)
4,4'-methylenediphenyl diisocyanate 101-68-8	EL50	> 100 mg/l	Algae	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
4,4'-methylenediphenyl diisocyanate 101-68-8	NOELR	100 mg/l	Algae	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
4,4'-methylenediphenyl diisocyanate 101-68-8	EC50	> 1.000 mg/l	Bacteria	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
4,4'-methylenediphenyl diisocyanate 101-68-8	NOEC	10 mg/l	chronic Daphnia	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
alkanes, C14-17, chloro 85535-85-9	NOEC	3,4 mg/l	Fish	20 d	Oryzias latipes	OECD Guideline 212 (Fish, Short-term Toxicity Test on Embryo and Sac-Fry Stages)
alkanes, C14-17, chloro 85535-85-9	LC50	> 5.000 mg/l	Fish	96 h	Alburnus alburnus	OECD Guideline 203 (Fish, Acute Toxicity Test)
alkanes, C14-17, chloro 85535-85-9	EC50	0,0059 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
alkanes, C14-17, chloro 85535-85-9	EC50	> 3,2 mg/l	Algae	72 h	not specified	OECD Guideline 201 (Alga, Growth Inhibition Test)
alkanes, C14-17, chloro 85535-85-9	NOEC	0,1 mg/l	Algae	72 h	not specified	OECD Guideline 201 (Alga, Growth Inhibition Test)
alkanes, C14-17, chloro 85535-85-9	EC50	> 2.000 mg/l	Bacteria	3 h	not specified	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
alkanes, C14-17, chloro 85535-85-9	NOEC	0,01 mg/l	chronic Daphnia	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
dimethyl ether	LC50	> 4.000 mg/l	Fish	96 h	Poecilia reticulata	OECD Guideline

# Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No.: 528637 V004.0 PATTEX PU FOAM FIX&FILL

Page 19 of 23

115-10-6 dimethyl ether 115-10-6	EC50	> 4.000 mg/l	Daphnia	48 h	Daphnia magna	203 (Fish, Acute Toxicity Test) OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
dimethyl ether 115-10-6	EC50	> 1.000 mg/l	Algae	72 h	not specified	OECD Guideline 201 (Alga. Growth Inhibition Test)
dimethyl ether 115-10-6	EC10	> 1.600 mg/l	Bacteria	30 min	Pseudomonas putida	DIN 38412, part 27 (Bacterial oxygen consumption test)
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	LC50	Toxicity > Water Solubility	Fish	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	EC50	Toxicity > Water Solubility	Daphnia	24 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	EC50	Toxicity > Water Solubility	Algae	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	OECD Guideline 201 (Alga. Growth Inhibition Test)
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	NOELR	Toxicity > Water Solubility	Algae	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	OECD Guideline 201 (Alga. Growth Inhibition Test)
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	NOEC	Toxicity > Water solubility	chronic Daphnia	21 day	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
2,2'-Methylenediphenyl diisocyanate 2536-05-2	LC50	Toxicity > Water solubility	Fish	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
2,2'-Methylenediphenyl diisocyanate 2536-05-2	EC50	Toxicity > Water solubility	Daphnia	24 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
2,2'-Methylenediphenyl diisocyanate 2536-05-2	EC50	Toxicity > Water solubility	Algae	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	OECD Guideline 201 (Alga. Growth Inhibition Test)
2,2'-Methylenediphenyl diisocyanate 2536-05-2	NOELR	Toxicity > Water solubility	Algae	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	OECD Guideline 201 (Alga. Growth Inhibition Test)
2,2'-Methylenediphenyl diisocyanate 2536-05-2	NOEC	Toxicity > Water solubility	chronic Daphnia	21 day	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

## 12.2. Persistence and degradability

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
---------------------------------	--------	----------------------	---------------	--------

# Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No.: 528637 V004.0 PATTEX PU FOAM FIX&FILL

Page 20 of 23

Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	not inherently biodegradable	aerobic	0 %	OECD Guideline 302 C (Inherent Biodegradability: Modified MITI Test (II))
	not readily biodegradable.	not specified	0 %	OECD 301 A - F
4,4'-methylenediphenyl diisocyanate 101-68-8	not readily biodegradable.	aerobic	0 %	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
alkanes, C14-17, chloro 85535-85-9	not readily biodegradable.	aerobic	> 13 - 66 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
dimethyl ether 115-10-6	readily biodegradable	aerobic	> 60 %	OECD 301 A - F
Isobutane 75-28-5	readily biodegradable	aerobic	71,43 %	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	not inherently biodegradable	aerobic	0 %	OECD Guideline 302 C (Inherent Biodegradability: Modified MITI Test (II))
2,2'-Methylenediphenyl diisocyanate 2536-05-2	not inherently biodegradable	aerobic	0 %	OECD Guideline 302 C (Inherent Biodegradability: Modified MITI Test (II))

## 12.3. Bioaccumulative potential / 12.4. Mobility in soil

Hazardous components CAS-No.	LogPow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9		200		Cyprinus carpio		OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)
4,4'-methylenediphenyl diisocyanate 101-68-8	4,51	92 - 200	28 d	Cyprinus carpio	22 °C	OECD Guideline 305 E (Bioaccumulation: Flow-through Fish Test) OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
4,4'-methylenediphenyl diisocyanate 101-68-8						
alkanes, C14-17, chloro 85535-85-9	7	349	35 d	Oncorhynchus mykiss		OECD Guideline 305 (Bioconcentration: Flow-through Fish Test) other (measured)
alkanes, C14-17, chloro 85535-85-9						
dimethyl ether 115-10-6	0,07				25 °C	QSAR (Quantitative Structure Activity Relationship)
Isobutane 75-28-5	2,88				20 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	5,22	200	28 day	Cyprinus carpio		OECD Guideline 305 E (Bioaccumulation: Flow-through Fish Test) QSAR (Quantitative Structure Activity Relationship)
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1						
2,2'-Methylenediphenyl diisocyanate 2536-05-2	5,22	200	28 day	Cyprinus carpio		OECD Guideline 305 E (Bioaccumulation: Flow-through Fish Test) QSAR (Quantitative Structure Activity Relationship)
2,2'-Methylenediphenyl diisocyanate 2536-05-2						

## 12.5. Results of PBT and vPvB assessment

Hazardous components CAS-No.	PBT/vPvB

# Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No.: 528637 V004.0 PATTEX PU FOAM FIX&FILL

Page 21 of 23

4,4'-methylenediphenyl diisocyanate 101-68-8	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
alkanes, C14-17, chloro 85535-85-9	Fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
dimethyl ether 115-10-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Isobutane 75-28-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
2,2'-Methylenediphenyl diisocyanate 2536-05-2	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

## 12.6. Other adverse effects

No data available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

Waste code

160504 gases in pressure containers (including halons) containing dangerous substances

## SECTION 14: Transport information

### 14.1. UN number or ID number

ADR	1950
RID	1950
ADN	1950
IMDG	1950
IATA	1950

### 14.2. UN proper shipping name

ADR	AEROSOLS
RID	AEROSOLS
ADN	AEROSOLS
IMDG	AEROSOLS
IATA	Aerosols, flammable

### 14.3. Transport hazard class(es)

ADR	2.1
RID	2.1
ADN	2.1
IMDG	2.1
IATA	2.1

### 14.4. Packing group

ADR  
RID  
ADN  
IMDG  
IATA

### 14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

### 14.6. Special precautions for user

ADR	not applicable Tunnelcode: (D)
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

# Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No.: 528637 V004.0 PATTEX PU FOAM FIX&FILL

Page 23 of 23

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

No information available:

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable

### 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

## SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

- H220 Extremely flammable gas.
- H280 Contains gas under pressure; may explode if heated.
- H281 Contains refrigerated gas; may cause cryogenic burns or injury.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H362 May cause harm to breast-fed children.
- H373 May cause damage to organs through prolonged or repeated exposure.
  
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

### Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

This Safety Data Sheet has been generated based on Regulation (EC) No 1907/2006 and it is applicable for Gulf Cooperation Council (GCC) and Africa only. No warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory, including export laws and regulations. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory affairs for additional assistance.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your\_company.com).

**Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.**