Revision Number: 001.1

Issue date: 09/08/2025

1. IDENTIFICATION

Product name: **Fester Imperfacil Clasico White 5A**
IDH number: 2503492
Product type/ Liquid Acrylic Membrane
Recommended use:
Restriction of Use: None identified
Region: Mexico
Company address:
Henkel Capital S.A. de C.V.
Boulevard Magnocentro 8 – P2
Centro Urbano San Fernando la Herradura
Huixquilucan Edo. de Mexico, C.P. 52760
Contact information:
Telephone: +52 (55) 33003000
SETIQ: Phone 01-800-00-214-00 (5559-1588)24 hours.
SETIQ,,Telephone 01-800-00-214-00 (5559-1588)

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING: H319 - CAUSES SERIOUS EYE IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
EYE IRRITATION	2A

PICTOGRAM(S)

Precautionary Statements

Prevention: P264 - Wash affected area thoroughly after handling.
P280 - Wear eye and face protection.

Response: P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 - If eye irritation persists: Get medical attention.

Storage: Not prescribed

Disposal: Not prescribed

Other hazards Not available.

Classification complies with NOM-018-STPS-2015 and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	UN no.:	Percentage*
Limestone	1317-65-3		30 - 60
Titanium dioxide	13463-67-7		1 - 5
Propane-1,2-diol	57-55-6		0.1 - 1

Aluminium hydroxide	21645-51-2		0.1 - 1
Si-oxide amorphous (fumed)	7631-86-9		0.1 - 1
Quartz (SiO2), <1% respirable	14808-60-7		0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

First Aid Measures by likely routes of exposure

Inhalation: If adverse health effects develop seek medical attention. If inhaled, immediately remove the affected person to fresh air.

Skin contact: Remove contaminated clothes. Immediately wash skin thoroughly with soap and water. Rinse immediately with plenty of running water, seek medical advice if necessary.

Eye contact: Flush eyes with plenty of water for at least 5 minutes. If irritation persists seek medical attention. Take care not to rinse contaminated water into the unaffected eye.

Ingestion: If adverse health effects develop seek medical attention. Drink 1-2 glasses of water. Do not initiate vomiting; instantly call for medical help. Do not induce vomiting.

Most important symptoms and effects (acute and delayed): The most important known symptoms and effects, both acute and delayed, are described in Section 11: Toxicological Information.

Indication of any immediate medical attention / special treatment needed: Not available.

5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray mist or foam. carbon dioxide Type ABC Extinguisher

Improper extinguishing agents: Not available.

Special firefighting procedures: Wear self-contained breathing apparatus. Wear full protective clothing.

Unusual fire or explosion hazards: In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO2) can be released.

Hazardous combustion products: carbon monoxide Carbon dioxide.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not empty into drains. Do not let product enter drains. Do not dispose of in wastepaper bin or trash-can. Wear appropriate protective equipment and clothing during clean-up. Prevent contamination of soil and water.

Clean-up methods: Cover with dry sand, remove mechanically. Wear protective clothing, gloves and safety glasses. Absorb liquid with sand. Collect it in PVC or PE containers Avoid skin and eye contact. Remove the absorbed material, and place in an appropriate chemical waste container for disposal. Wear appropriate personal protective equipment. Remove with liquid-absorbing material (sand, peat, sawdust).

7. HANDLING AND STORAGE

Handling: Avoid skin and eye contact. Provide adequate ventilation. Open and handle container with care. Keep out of the reach of children. Keep away from sources of ignition - no smoking. Use only in well-ventilated areas. Wear suitable protective clothing, safety glasses and gloves. Keep container closed.

Storage: Temperatures between + 5 °C and + 40 °C.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Limestone	10 mg/m3 TWA Inhalable particles. 3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Total dust.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 5 mg/m3 TWA Respirable fraction. 50 MPPCF TWA Total dust. 15 mg/m3 TWA Total dust. 15 MPPCF TWA Respirable fraction.	None	None
Titanium dioxide	0.2 mg/m3 TWA Respirable nanoscale particles 2.5 mg/m3 TWA Respirable finescale particles	15 mg/m3 PEL Total dust. 15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction.	None	None
Quartz (SiO2), <1% respirable	0.025 mg/m3 TWA Respirable fraction.	0.05 mg/m3 TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m3 OSHA_ACT (Respirable dust.) 0.05 mg/m3 PEL Respirable dust. 2.4 MPPCF TWA Respirable 0.1 mg/m3 TWA Respirable	None	None

Engineering controls: Ensure good ventilation/extraction. Use only in well ventilated areas.

Respiratory protection: Ensure adequate ventilation. In case of insufficient ventilation wear suitable respiratory equipment.

Eye/face protection:	Avoid eye contact. Wear chemical goggles and / or face shield.
Skin protection:	Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Color:	White
Odor:	Acrylic
Odor threshold:	Not available.
pH:	Not available.
Vapor pressure:	Not available.
Boiling point/range:	> 100 °C (> 212°F)
Melting point/ range:	Not available.
Density/Relative density:	Not available.
Relative vapor density:	Not available.
Flash point:	Aqueous. Does not flash.
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	Not available.
Solubility:	Soluble Water
Partition coefficient n-octanol/water (logarithmic value):	Not available.
VOC content:	Not available.
Dynamic viscosity:	Not available.
Kinematic viscosity:	Not available.
Particle characteristics:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Not available.
Reactivity:	Not available.
Hazardous reactions:	Not available.
Hazardous decomposition products:	Not available.
Incompatible materials:	None known
Conditions to avoid:	Protect from direct sunlight.

11. TOXICOLOGICAL INFORMATION

Likely routes of exposure	Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation: May cause slight irritation. Abrasion of cured material such as by sanding or grinding could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of this product causes no such release.

Skin contact: May cause skin irritation.

Eye contact: Causes serious eye irritation.

Ingestion: May be harmful if swallowed.

Hazardous Component(s)	LD50s and LC50s
Limestone	None
Titanium dioxide	Inhalation LC50 (Rat, 4 h) = > 6.82 mg/l Inhalation LC50 (Rat, 4 h) = > 2.28 mg/l Inhalation LC50 (Rat, 4 h) = > 3.56 mg/l
Propane-1,2-diol	Oral LD50 (Rabbit) = 18 g/kg Oral LD50 (Mouse) = 23.9 g/kg Oral LD50 (Rat) = 30 g/kg
Aluminium hydroxide	Oral LD50 (Rat) = > 5,000 mg/kg
Si-oxide amorphous (fumed)	Oral LD50 (Rat) = > 22,500 mg/kg Oral LD50 (Mouse) = > 15,000 mg/kg Inhalation LC50 (Rat, 4 h) = > 2.08 mg/l Inhalation LC50 (Rat, 4 h) = > 0.69 mg/l
Quartz (SiO2), <1% respirable	None

Hazardous Component(s)	Immediate Health Effects	Delayed Health Effects	Chronic Health Effects
Limestone	Nuisance dust		
Titanium dioxide	Irritant		Respiratory Some evidence of carcinogenicity
Propane-1,2-diol	Irritant		
Aluminium hydroxide	Irritant		Lung Respiratory
Si-oxide amorphous (fumed)	Nuisance dust		
Quartz (SiO2), <1% respirable			Immune system Lung Some evidence of carcinogenicity

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Limestone	No	No	No
Titanium dioxide	No	Group 2B	No
Propane-1,2-diol	No	No	No
Aluminium hydroxide	No	No	No
Si-oxide amorphous (fumed)	No	No	No
Quartz (SiO2), <1% respirable	Known To Be Human Carcinogen.	Group 1	Yes

12. ECOLOGICAL INFORMATION

Ecological information: Do not empty into drains, soil or bodies of water.

Ecotoxicity: Not available.

Persistence and degradability: Not available.

Bioaccumulative potential: Not available.

Mobility: Not available.

Other ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of in accordance with local and national regulations.

14. TRANSPORT INFORMATION

Road transport ADR:

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

15. REGULATORY INFORMATION

No additional information

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 3, 4, 7, 8, 11

Prepared by: Product Safety and Regulatory Affairs
Issue date: 09/08/2025

DISCLAIMER: This information is considered correct, but it´s not exhaustive and will be used only as a guide, which is based on current knowledge of the chemical substance(s) and/or mixture and apply to the appropriate product for safety precautions.

The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Capital does not assume responsibility for any results obtained by persons over whose methods Henkel Capital has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Capital's products. In light of the foregoing, Henkel Capital specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Capital's products. Henkel Capital further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on the Mexican Official Standard (NOM-018-STPS-2015) of the harmonized system for the identification and communication of hazards and risks from hazardous chemicals in the workplace and provides information in accordance with Mexican law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.