



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 11

BITUTAPE PRIMER

SDS No. : 566924
V002.1

Revision: 20.03.2023
printing date: 07.02.2026

Replaces version from: 22.07.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

BITUTAPE PRIMER

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:
Bituminous product

1.3. Details of the supplier of the safety data sheet

Henkel Jebal Ali FZCO
PO Box 61341 - Jebel Ali
Dubai

Utd.Arab.Emir.

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

1.4. Emergency telephone number

HAAD Poison and Drug Information Center UAE, TOLL FREE TEL. NUMBER 800-424

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Flammable liquids	Category 3
H226 Flammable liquid and vapour.	
Specific target organ toxicity - single exposure	Category 3
H336 May cause drowsiness or dizziness.	
Target organ: Central nervous system	
Chronic hazards to the aquatic environment	Category 3
H412 Harmful to aquatic life with long lasting effects.	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No.: 566924 V002.1 BITUTAPE PRIMER

Page 2 of 11

	Nonane
Signal word:	Warning
Hazard statement:	H226 Flammable liquid and vapour. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects.
Supplemental information	EUH066 Repeated exposure may cause skin dryness or cracking.
Precautionary statement: Prevention	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment.
Precautionary statement: Disposal	P501 Dispose of contents/container in accordance with national regulation.

2.3. Other hazards

None if used properly.
Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

Following substances are present in a concentration \geq the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration \geq the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number	content	Classification
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9		40- 60 %	Asp. Tox. 1 H304 Flam. Liq. 3 H226 STOT SE 3 H336
Nonane 111-84-2	203-913-4	1- < 5 %	Flam. Liq. 3 H226 Asp. Tox. 1 H304 Skin Irrit. 2 H315 STOT SE 3 H336 Aquatic Acute 1 H400 Aquatic Chronic 1 H410

For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

In case of adverse health effects seek medical advice.

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap. Skin care. Remove contaminated clothes immediately.

Eye contact:

Immediately flush eyes with soft jet of water or eye rinse solution for at least 5 minutes. If pains remain (intensive smarting, sensitivity to light, visual disturbance) continue flushing and contact/seek doctor or hospital.

Ingestion:

Rinse mouth and throat. Drink 1-2 glasses of water. Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Vapors may cause drowsiness and dizziness.

Repeated exposure may cause skin dryness or cracking.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

carbon dioxide, foam, powder, water spray jet, fine water spray

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO₂) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Wear protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment.

Ensure adequate ventilation.

Danger of slipping on spilled product.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Remove with liquid-absorbing material (sand, peat, sawdust).

Dispose of contaminated material as waste according to Section 13.

Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No.: 566924 V002.1 BITUTAPE PRIMER

Page 4 of 11

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ensure that workrooms are adequately ventilated.

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from heat and direct sunlight.

Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

7.3. Specific end use(s)

Bituminous product

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Utd.Arab.Emir.

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Asphalt 8052-42-4 [ASPHALT (BITUMEN) FUME AS BENZENE-SOLUBLE AEROSOL, INHALABLE FRACTION OF THE AEROSOL]		0,5	Time Weighted Average (TWA):		AD TLV
Asphalt 8052-42-4 [ASPHALT (FUMES)]		5	Time Weighted Average (TWA):		DB OEL
Asphalt 8052-42-4 [ASPHALT (FUMES)]		5	Time Weighted Average (TWA):		GCC TLV
Asphalt 8052-42-4 [ASPHALT (FUMES)]		5	Time Weighted Average (TWA):		UAE OEL
Nonane 111-84-2 [NONANE, ALL ISOMERS]	200	1.050	Time Weighted Average (TWA):		AD TLV
Nonane 111-84-2 [NONANE]	200	1.050	Time Weighted Average (TWA):		GCC TLV
Nonane 111-84-2 [NONANE]	200	1.050	Time Weighted Average (TWA):		UAE OEL

Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No.: 566924 V002.1 BITUTAPE PRIMER

Page 5 of 11

Occupational Exposure Limits

Valid for
Bharain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Asphalt 8052-42-4 [ASPHALT (FUMES)]		5	Time Weighted Average (TWA):		BH TLV
Asphalt 8052-42-4 [ASPHALT (FUMES)]		5	Time Weighted Average (TWA):		GCC TLV
Nonane 111-84-2 [NONANE]	200	1.050	Time Weighted Average (TWA):		BH TLV
Nonane 111-84-2 [NONANE]	200	1.050	Time Weighted Average (TWA):		GCC TLV

Occupational Exposure Limits

Valid for
Egypt

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Asphalt 8052-42-4 [ASPHALT (PETROLEUM) FUMES (AS BENZENE SOLUBLE AEROSOLS)]		0,5	Time Weighted Average (TWA):		EG OEL

Occupational Exposure Limits

Valid for
Jordan

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Asphalt 8052-42-4 [ASPHALT]		5	Time Weighted Average (TWA):		JO TLV

Occupational Exposure Limits

Valid for
Kuwait

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Asphalt 8052-42-4 [ASPHALT (FUMES)]		5	Time Weighted Average (TWA):		GCC TLV
Asphalt 8052-42-4 [ASPHALT (FUME)]		5	Short-term Exposure Limit (STEL):		KW OEL
Asphalt 8052-42-4 [ASPHALT (FUME)]			Harmful Concentration for risk to health and life:	Unknown	KW OEL

Occupational Exposure Limits

Valid for

Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No.: 566924 V002.1 BITUTAPE PRIMER

Page 6 of 11

Israel

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Asphalt 8052-42-4 [Asphalt (Bitumen) fume, as benzene-soluble aerosol, inhalable fraction]		0,5	Time Weighted Average (TWA):		IL OEL
Nonane 111-84-2 [NONANE]	200		Time Weighted Average (TWA):		IL OEL

Occupational Exposure Limits

Valid for
Kenya

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Asphalt 8052-42-4 [ASPHALT, PETROLEUM FUMES]		5	Time-weighted average (TWA) OEL-RL:		KE OEL-RL
Asphalt 8052-42-4 [ASPHALT, PETROLEUM FUMES]		10	Short-term OEL-RL:		KE OEL-RL
Naphtha (petroleum), hydrotreated heavy 64742-48-9 [WHITE SPIRIT]	125	720	Short-term OEL-RL:		KE OEL-RL
Naphtha (petroleum), hydrotreated heavy 64742-48-9 [WHITE SPIRIT]	100	575	Time-weighted average (TWA) OEL-RL:		KE OEL-RL

Biological Exposure Indices:

None

8.2. Exposure controls:

Respiratory protection:

Suitable breathing mask when there is inadequate ventilation.
Combination filter: ABEKP (EN 14387)
This recommendation should be matched to local conditions.

Hand protection:

In the case of longer contact protective gloves made from nitrile rubber are recommended according to EN 374.
Perforation time > 30 minutes
material thickness > 0.1 mm

In the case of longer and repeated contact please note that in practice the penetration times may be considerably shorter than those determined according to EN 374. The protective gloves must always be checked for their suitability for use at the specific workplace (e.g. mechanical and thermal stress, product compatibility, antistatic effects, etc.). The gloves must be replaced immediately at the first signs of wear and tear. The information provided by the manufacturers and given in the relevant trade association regulations for industrial safety must always be observed. We recommend that a hand care plan is drawn up in cooperation with a glove manufacturer and the trade association in accordance with the local operating conditions.

Eye protection:

Goggles which can be tightly sealed.
Protective eye equipment should conform to EN166.

Skin protection:

Suitable protective clothing
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No.: 566924 V002.1 BITUTAPE PRIMER

Page 7 of 11

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	liquid liquid Black
Odor	Typical
Odour threshold	No data available / Not applicable
pH	Not applicable, Product is non-soluble (in water).
Initial boiling point	> 140 °C (> 284 °F)
Flash point	38 °C (100.4 °F)
Decomposition temperature	> 1.000 °C (> 1832 °F)
Vapour pressure (20 °C (68 °F))	1,9 hPa
Density (25 °C (77 °F))	0,85 - 0,9 g/cm3
Bulk density	No data available / Not applicable
Viscosity (; 25 °C (77 °F))	168 - 184 mPa.s
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Solubility (qualitative) (20 °C (68 °F); Solvent: Water)	Not miscible
Solidification temperature	0 °C (32 °F)
Melting point	Not applicable, Product is a liquid
Flammability	No data available / Not applicable
Auto-ignition temperature	230 °C (446 °F)
Explosive limits lower	0,7 %(V)
upper	7 %(V)
Partition coefficient: n-octanol/water	No data available / Not applicable
Evaporation rate	No data available / Not applicable
Vapor density (20 °C)	> 1
Oxidising properties	No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

None if used for intended purpose.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

None if used for intended purpose.

Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No.: 566924 V002.1 BITUTAPE PRIMER

Page 8 of 11

10.5. Incompatible materials

None if used properly.

10.6. Hazardous decomposition products

None known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

STOT-single exposure:

May cause drowsiness or dizziness.

Acute oral toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	LD50	> 5.000 mg/kg	oral		rat	OECD Guideline 401 (Acute Oral Toxicity)
Nonane 111-84-2	LD50	> 5.000 mg/kg	oral		rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)

Acute inhalative toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	LC50	> 5,6 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)

Acute dermal toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	LD50	> 5.000 mg/kg	dermal		rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Nonane 111-84-2	LD50	> 2.000 mg/kg	dermal		rabbit	not specified

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	mildly irritating	4 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

SECTION 12: Ecological information

General ecological information:

Do not empty into drains, soil or bodies of water.

Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No.: 566924 V002.1 BITUTAPE PRIMER

Page 9 of 11

12.1. Toxicity

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	LL50	Toxicity > Water solubility	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	EL50	Toxicity > Water solubility	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	EL50	Toxicity > Water solubility	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
	NOELR	Toxicity > Water solubility	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Nonane 111-84-2	EC50	0,2 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

12.2. Persistence and degradability

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	readily biodegradable	aerobic	80 %	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Nonane 111-84-2	readily biodegradable	aerobic	100 %	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))

12.3. Bioaccumulative potential / 12.4. Mobility in soil

Hazardous components CAS-No.	LogPow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Nonane 111-84-2	5,65					OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

12.5. Results of PBT and vPvB assessment

Hazardous components CAS-No.	PBT/vPvB
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No.: 566924 V002.1 BITUTAPE PRIMER

Page 10 of 11

Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

Waste code

170302

SECTION 14: Transport information

14.1. UN number or ID number

ADR	1999
RID	1999
ADN	1999
IMDG	1999
IATA	1999

14.2. UN proper shipping name

ADR	TARS, LIQUID
RID	TARS, LIQUID
ADN	TARS, LIQUID
IMDG	TARS, LIQUID
IATA	Tars, liquid

14.3. Transport hazard class(es)

ADR	3
RID	3
ADN	3
IMDG	3
IATA	3

14.4. Packing group

ADR	III
RID	III
ADN	III
IMDG	III
IATA	III

14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable Tunnelcode: (D/E)
-----	-------------------------------------

Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No.: 566924 V002.1 BITUTAPE PRIMER

Page 11 of 11

RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable

VOC content	42,2 %
(VOCV 814.018 VOC regulation CH)	

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

This Safety Data Sheet has been generated based on Regulation (EC) No 1907/2006 and it is applicable for Gulf Cooperation Council (GCC) and Africa only. No warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory, including export laws and regulations. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory affairs for additional assistance.

Dear Customer,
Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.