

# Safety Data Sheet



Revision Number: 005.0

Issue date: 02/26/2025

## 1. IDENTIFICATION

**Product name:** LOCTITE PL POLYURETHANE WINDOW DOOR AND SIDING SEALANT,,  
**Product type/ Recommended use:** Sealant  
**Restriction of Use:** None identified  
**Company address:** Henkel Corporation  
One Henkel Way  
Rocky Hill, Connecticut 06067

**IDH number:** 1618182

**Region:** United States

**Contact information:**  
Telephone: +1 (860) 571-5100  
MEDICAL EMERGENCY Phone: Poison Control Center  
1-877-671-4608 (toll free) or 1-303-592-1711  
TRANSPORT EMERGENCY Phone: CHEMTREC  
1-800-424-9300 (toll free) or 1-703-527-3887  
MEDICAL EMERGENCY Phone: Poison Control Center  
1-877-671-4608 (toll free) or 1-303-592-1711  
TRANSPORT EMERGENCY Phone: CHEMTREC  
1-800-424-9300 (toll free) or 1-703-527-3887  
Internet: www.henkelna.com

This product contains a chemical which is subject to a proposed Environmental Protection Agency (EPA) Significant New Use Restriction (SNUR).

## 2. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

**DANGER:** H317 - MAY CAUSE AN ALLERGIC SKIN REACTION.  
H319 - CAUSES SERIOUS EYE IRRITATION.  
H332 - HARMFUL IF INHALED.  
H334 - MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING DIFFICULTIES IF INHALED.  
H351 - SUSPECTED OF CAUSING CANCER.  
H360 - MAY DAMAGE FERTILITY OR THE UNBORN CHILD.

HAZARD CLASS	HAZARD CATEGORY
ACUTE TOXICITY INHALATION	4
EYE IRRITATION	2A
RESPIRATORY SENSITIZATION	1
SKIN SENSITIZATION	1
CARCINOGENICITY	2
REPRODUCTIVE TOXICITY	1B

### PICTOGRAM(S)



### Precautionary Statements

**Prevention:** P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P261 - Avoid breathing dust or fumes.  
P264 - Wash affected area thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P272 - Contaminated work clothing should not be allowed out of the workplace.  
P280 - Wear protective gloves, clothing, eye and face protection.  
P284 - [In case of inadequate ventilation] wear respiratory protection.  
P302+P352 - IF ON SKIN: Wash with plenty of water.

**Response:**

IDH number: 1618182

Product name: LOCTITE PL POLYURETHANE WINDOW DOOR AND SIDING SEALANT,,

P304+P340+P312 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 - IF exposed or concerned: Get medical attention.  
P333+P313 - If skin irritation or rash occurs: Get medical attention.  
P337+P313 - If eye irritation persists: Get medical attention.  
P342+P311 - If experiencing respiratory symptoms: Call a poison center or physician.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P405 - Store locked up.  
P501 - Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

**Storage:**  
**Disposal:**

**Other hazards** Not available.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

**See Section 11 for additional toxicological information.**

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*
Limestone	1317-65-3	10 - 30
Titanium dioxide	13463-67-7	1 - 5
Talc	14807-96-6	1 - 5
Calcium oxide	1305-78-8	1 - 5
Stoddard solvent, <0.1% Benzene	8052-41-3	1 - 5
Bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexane-1,2-diylobiscarbamate	59719-67-4	1 - 5
Toluene-2,6-diisocyanate	91-08-7	0.1 - 1
dibutyltin dilaurate	77-58-7	0.1 - 1
4-isocyanatosulphonyltoluene	4083-64-1	0.1 - 1

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 4. FIRST AID MEASURES

#### First Aid Measures by likely routes of exposure

<b>Inhalation:</b>	If inhaled, immediately remove the affected person to fresh air. Immediate medical treatment necessary.
<b>Skin contact:</b>	Wash affected area immediately with soap and water. If symptoms develop and persist, get medical attention. Remove contaminated clothes.
<b>Eye contact:</b>	In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention.
<b>Ingestion:</b>	Do not induce vomiting, seek medical advice immediately.
<b>Most important symptoms and effects (acute and delayed):</b>	The most important known symptoms and effects, both acute and delayed, are described in Section 11: Toxicological Information.
<b>Indication of any immediate medical attention / special treatment needed:</b>	An individual having a dermal or pulmonary sensitization reaction to this material should be removed from further exposure to any diisocyanate. Treatment based on judgement of the physician in response to reactions of the patient.

### 5. FIRE FIGHTING MEASURES

<b>Extinguishing media:</b>	Water fog. Foam Carbon dioxide.
<b>Improper extinguishing agents:</b>	Not available.

<b>Special firefighting procedures:</b>	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray.
<b>Unusual fire or explosion hazards:</b>	None known.
<b>Hazardous combustion products:</b>	Nitrous gases Irritating fumes. Isocyanate vapors.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

<b>Environmental precautions:</b>	Do not empty into drains / surface water / ground water.
<b>Clean-up methods:</b>	Ensure adequate ventilation. Scrape up spilled material and place in a closed container for disposal. Wear suitable protective clothing, gloves and eye/face protection.

## 7. HANDLING AND STORAGE

<b>Handling:</b>	Avoid contact with eyes, skin and clothing. Avoid extreme temperatures. Wash thoroughly after handling. Protect from moisture. Use only with adequate ventilation.
<b>Storage:</b>	For safe storage, store between 18.3 °C (64.9 °F) and 40 °C (104°F) Avoid moisture. Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials.

**Shelf Life Statement: Not available.**

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Limestone	10 mg/m3 TWA Inhalable particles. 3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Total dust.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 5 mg/m3 TWA Respirable fraction. 50 MPPCF TWA Total dust. 15 mg/m3 TWA Total dust. 15 MPPCF TWA Respirable fraction.	None	None
Titanium dioxide	0.2 mg/m3 TWA Respirable nanoscale particles 2.5 mg/m3 TWA Respirable finescale particles	15 mg/m3 PEL Total dust. 15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction.	None	None
Talc	2 mg/m3 TWA Respirable fraction.	0.1 mg/m3 TWA Respirable 20 MPPCF TWA 2.4 MPPCF TWA Respirable	None	50 ppm
Calcium oxide	2 mg/m3 TWA	5 mg/m3 PEL	None	None
Stoddard solvent, <0.1% Benzene	100 ppm TWA	500 ppm (2,900 mg/m3) PEL	None	None
Toluene-2,6-diisocyanate	0.005 ppm STEL Inhalable fraction and vapor. 0.001 ppm TWA Inhalable fraction and vapor. (SKIN) Inhalable fraction and vapor. (Dermal sensitization) (Respiratory sensitization)	None	None	None
dibutyltin dilaurate	0.1 mg/m3 TWA (as Sn) 0.2 mg/m3 STEL (as Sn) (SKIN) (as Sn)	0.1 mg/m3 PEL (as Sn)	None	None

**Engineering controls:**

Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination below occupational exposure limits.

**Respiratory protection:**

Observe OSHA regulations for respirator use (29 CFR 1910.134). Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists. Respirator with combination filter for vapor/particulate.

**Eye/face protection:**

Safety glasses with side-shields. Full face protection should be used if the potential for splashing or spraying of product exists.

**Skin protection:**

Suitable protective clothing

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Thixotropic solid
<b>Color:</b>	White
<b>Odor:</b>	Slight
<b>Odor threshold:</b>	Not available.
<b>pH:</b>	Not applicable
<b>Vapor pressure:</b>	Not available.
<b>Boiling point/range:</b>	Not available.
<b>Melting point/ range:</b>	Not applicable
<b>Density/Relative density:</b>	1.20 at 25 °C (77°F)
<b>Relative vapor density:</b>	Not available.
<b>Flash point:</b>	Does not flash.
<b>Flammable/Explosive limits - lower:</b>	Not available.
<b>Flammable/Explosive limits - upper:</b>	Not available.
<b>Autoignition temperature:</b>	Not applicable
<b>Flammability:</b>	Not applicable
<b>Evaporation rate:</b>	Not available.
<b>Solubility:</b>	Insoluble Water
<b>Partition coefficient n-octanol/water (logarithmic value):</b>	Not available.
<b>VOC content:</b>	2.92 %; 35 g/l (by weight, calculated using CARB method; g/L less water, less exempts calculated using SCAQMD method)
<b>Dynamic viscosity:</b>	Not available.
<b>Kinematic viscosity:</b>	Not available.
<b>Particle characteristics:</b>	Not available.
<b>Decomposition temperature:</b>	Not available.

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable under normal conditions of storage and use.
<b>Hazardous reactions:</b>	Contact with moisture, other materials that react with isocyanates, or temperatures above 350° F (177° C), may cause polymerization.
<b>Hazardous decomposition products:</b>	Irritating and/or toxic fumes and gases may be emitted upon the product's decomposition. nitrogen oxides Aromatic isocyanates. carbon oxides. carbon monoxide Hydrogen cyanide.
<b>Incompatible materials:</b>	Oxidizing agents. Alcohols. Water. Strong bases.
<b>Reactivity:</b>	Not available.
<b>Conditions to avoid:</b>	Avoid moisture.

## 11. TOXICOLOGICAL INFORMATION

<b>Likely routes of exposure:</b>	Skin, Inhalation, Eyes, Ingestion
-----------------------------------	-----------------------------------

**Potential Health Effects/Symptoms**

**Inhalation:** This product may cause sensitization by inhalation and skin contact. As a result of previous repeated overexposures or a single large dose, certain individuals will develop isocyanate sensitization (chemical asthma) which will cause them to react to a later exposure to isocyanate at levels well below the TLV. Chronic overexposure to isocyanates has been reported to cause lung damage. May cause allergic respiratory reaction. Causes respiratory tract irritation. Persons suffering from allergic reactions to isocyanates should avoid contact with the product.

**Skin contact:** Contact with skin can cause irritation and allergic reaction (sensitization) in some individuals. This product may discolor the skin.

**Eye contact:** Causes serious eye irritation.

**Ingestion:** Not expected under normal conditions of use. May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s
Limestone	None
Titanium dioxide	Inhalation LC50 (Rat, 4 h) = > 6.82 mg/l Inhalation LC50 (Rat, 4 h) = > 2.28 mg/l Inhalation LC50 (Rat, 4 h) = > 3.56 mg/l
Talc	None
Calcium oxide	Inhalation LC50 (Rat, 4 h) = 40 mg/m3 Inhalation LC50 (Rat, 4 h) = 160 mg/m3
Stoddard solvent, <0.1% Benzene	None
Bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexane-1,2-diy]biscarbamate	None
Toluene-2,6-diisocyanate	None
dibutyltin dilaurate	Oral LD50 (Rat) = 175 mg/kg
4-isocyanatosulphonyltoluene	None

Hazardous Component(s)	Immediate Health Effects	Delayed Health Effects	Chronic Health Effects
Limestone	Nuisance dust		
Titanium dioxide	Irritant		Respiratory Some evidence of carcinogenicity
Talc	Irritant		Lung Some evidence of carcinogenicity
Calcium oxide	Irritant Corrosive		Eyes
Stoddard solvent, <0.1% Benzene	Irritant		Central nervous system
Bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexane-1,2-diy]biscarbamate			
Toluene-2,6-diisocyanate	Corrosive Irritant	Allergen	Bone Marrow Eyes Mutagen Respiratory Some evidence of carcinogenicity
dibutyltin dilaurate	Irritant		Central nervous system Eyes
4-isocyanatosulphonyltoluene			

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Limestone	No	No	No
Titanium dioxide	No	Group 2B	No
Talc	No	Group 2A	No
Calcium oxide	No	No	No
Stoddard solvent, <0.1% Benzene	No	No	No
Bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexane-1,2-diy]biscarbamate	No	No	No
Toluene-2,6-diisocyanate	Reasonably Anticipated to be a Human Carcinogen.	Group 2B	No
dibutyltin dilaurate	No	No	No
4-isocyanatosulphonyltoluene	No	No	No

## 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

### U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated  
Hazard class or division: None  
Identification number: None  
Packing group: None

### International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated  
Hazard class or division: None  
Identification number: None  
Packing group: None

### Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated  
Hazard class or division: None  
Identification number: None  
Packing group: None

## 15. REGULATORY INFORMATION

### United States Regulatory Information

**TSCA 8 (b) Inventory Status:** All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.

**TSCA 12 (b) Export Notification:** Toluene-2,6-diisocyanate (CAS# 91-08-7).

**CERCLA/SARA Section 302 EHS:** Toluene-2,6-diisocyanate (CAS# 91-08-7). Toluene-2,4-diisocyanate (CAS# 584-84-9).  
**CERCLA/SARA Section 311/312:** Please refer to the GHS classification in Section 2  
**CERCLA/SARA Section 313:** This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Toluene-2,6-diisocyanate (CAS# 91-08-7).

**CERCLA Reportable quantity:** Toluene-2,6-diisocyanate (CAS# 91-08-7) 100 lbs. (45.4 kg)

**California Proposition 65:** This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

### Canada Regulatory Information

**CEPA DSL/NDSL Status:** Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.

## 16. OTHER INFORMATION

**This safety data sheet contains changes from the previous version in sections:** This Safety Data Sheet contains changes from the previous version in Section(s): 2, 3, 8, 11, 15

**Prepared by:** Product Safety and Regulatory Affairs

**Issue date:** 02/26/2025

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.