

Revision Number: 002.0 Issue date: 10/31/2017

# 1. PRODUCT AND COMPANY IDENTIFICATION

**Product name:** Fester Acriton Sellador Para Imp Product type: Sealant **Restriction of Use:** None identified Region: Mexico

Company address: **Contact information:** 

Henkel Capital S.A. de C.V.

Boulevard Magnocentro 8 - P2

Huixquilucan Edo. de Mexico, C.P. 52760

IDH number: 1627608

Telephone: +52 (55) 33003000

SETIQ,, Telephone 01-800-00-214-00 (5559-1588)

### 2. HAZARDS IDENTIFICATION

# **EMERGENCY OVERVIEW** NOT CLASSIFIED. READ ENTIRE SAFETY DATA SHEET.

HAZARD CLASS	HAZARD CATEGORY
None	None

PICTOGRAM(S)
None

#### **Precautionary Statements**

Prevention: Not prescribed Response: Not prescribed Storage: Not prescribed Disposal: Not prescribed

Classification complies with NOM-018-STPS-2015 and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	UN no.:	Percentage*
2-Butoxyethanol	111-76-2	2810	1 - 5

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections

# 4. FIRST AID MEASURES

Inhalation: If adverse health effects develop seek medical attention. If inhaled,

immediately remove the affected person to fresh air.

Skin contact: Remove contaminated clothes. Immediately wash skin thoroughly with soap

and water. Rinse immediately with plenty of running water, seek medical

advice if necessary.

Eye contact: Flush eyes with plenty of water for at least 5 minutes. If irritation persists seek

medical attention. Take care not to rinse contaminated water into the

unaffected eye.

Ingestion: If adverse health effects develop seek medical attention. Drink 1-2 glasses of

water. Do not initiate vomiting; instantly call for medical help. Do not induce

vomiting.

Symptoms: See Section 11.

#### 5. FIRE FIGHTING MEASURES

Extinguishing media: Carbon dioxide. foam Sand. Dry powder.

Special firefighting procedures: Wear protective equipment. Remove all sources of ignition.

Unusual fire or explosion hazards: Formation of toxic gases is possible during heating or in fires.

Hazardous combustion products: Toxic fumes.

### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not empty into drains. Do not let product enter drains. Do not dispose of in

wastepaper bin or trash-can. Wear appropriate protective equipment and clothing during clean-up. Prevent contamination of soil and water.

Clean-up methods: Cover with dry sand, remove mechanically. Wear protective clothing, gloves

and safety glasses. Absorb liquid with sand. Collect it in PVC or PE containers Avoid skin and eye contact. Remove the absorbed material, and place in an appropriate chemical waste container for disposal. Wear appropriate personal protective equipment. Remove with liquid-absorbing material (sand, peat,

sawdust).

### 7. HANDLING AND STORAGE

**Handling:** Avoid skin and eye contact. Provide adequate ventilation. Open and handle

container with care. Keep out of the reach of children. Keep away from sources of ignition - no smoking. Use only in well-ventilated areas. Wear suitable protective clothing, safety glasses and gloves. Keep container closed.

Storage: Not available.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
2-Butoxyethanol	20 ppm TWA	50 ppm (240 mg/m3) PEL (SKIN)	None	None

Engineering controls: Ensure good ventilation/extraction. Use only in well ventilated areas.

Respiratory protection: Ensure adequate ventilation. Suitable respiratory protection: In case of

insufficient ventilation wear suitable respiratory equipment.

IDH number: 1627608 Product name: Fester Acriton Sellador Para Imp

Eye/face protection: Avoid eye contact. Protective goggles Wear chemical goggles and / or face

shield.

**Skin protection:**Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid White Color: Odor: Typical Odor threshold: Not available. 8.5 - 9.5 pH: Not available. Vapor pressure: Boiling point/range: Not available. Melting point/ range: Not available. Vapor density: Not available. Flash point: Aqueous solution Flammable/Explosive limits - lower: Not available. Flammable/Explosive limits - upper: Not available. Autoignition temperature: Not available. Flammability: Not applicable **Evaporation rate:** Not available. Solubility in water: Not available. Partition coefficient (n-octanol/water): Not available. **VOC** content: Not available. Viscosity: Not available. **Decomposition temperature:** Not available.

# 10. STABILITY AND REACTIVITY

**Stability**: Stable under normal conditions of storage and use.

Reactivity: Not available.

**Hazardous reactions:** None under normal processing.

Hazardous decomposition

products:

IDH number: 1627608

No decomposition if used according to specifications.

**Incompatible materials:** None if used for intended purpose.

**Conditions to avoid:** Excessive heat. Avoid contact with acids and oxidizing agents.

### 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

#### **Potential Health Effects/Symptoms**

**Inhalation:** This product is irritating to the respiratory system.

Skin contact: Causes skin irritation.

Eye contact: Causes eye irritation.

Ingestion: Harmful if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
2-Butoxyethanol	Oral LD50 (Rat) = 560 mg/kg Oral LD50 (Mouse) = 1.2 g/kg Oral LD50 (Rabbit) = 0.32 g/kg Oral LD50 (Rat) = 1.48 g/kg Oral LD50 (Mouse) = 1,519 mg/kg Dermal LD50 (Rabbit) = 400 mg/kg Inhalation LC50 (Rat. 4 h) = 486 ppm	Blood, Central nervous system, Irritant, Kidney, Liver

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
riazardous component(s)	WIF Carcinogen	IANG Gardinogen	(Specifically Regulated)
2-Butoxyethanol	No	No	No

# 12. ECOLOGICAL INFORMATION

**Ecological information:** If used properly the product does not enter the drains. Do not empty into

drains / surface water / ground water.

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of waste and residues in accordance with local authority

requirements.

## 14. TRANSPORT INFORMATION

**Road transport ADR:** 

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:
Not regulated
None
None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

## 15. REGULATORY INFORMATION

No additional information

### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

IDH number: 1627608 Product name: Fester Acriton Sellador Para Imp

Prepared by: Product Safety and Regulatory Affairs

**Issue date:** 10/31/2017

DISCLAIMER: This information is considered correct, but it's not exhaustive and will be used only as a guide, which is based on current knowledge of the chemical substance(s) and/or mixture and apply to the appropriate product for safety precautions.

The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Capital does not assume responsibility for any results obtained by persons over whose methods Henkel Capital has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Capital's products. In light of the foregoing, Henkel Capital specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Capital's products. Henkel Capital further disclaims any liability for consequential or incidental damages of any kind, including lost profits.