



Revision Number: 005.0

Issue date: 09/16/2025

1. IDENTIFICATION

| | | | |
|---------------------------------------|--|-----------------------------|--|
| Product name: | LePage PL600 Landscape Block Adhesive | IDH number: | 1654127 |
| Product type/ Recommended use: | Adhesive | Region: | Canada |
| Restriction of Use: | None identified | Contact information: | Telephone: +1 (905) 814-6511 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com |
| Company address: | Henkel Canada Corporation Meadowpine Boulevard 2515 Mississauga, Ontario L5N 6C3 | | |

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: H225 - HIGHLY FLAMMABLE LIQUID AND VAPOUR.
H319 - CAUSES SERIOUS EYE IRRITATION.

| HAZARD CLASS | HAZARD CATEGORY |
|------------------|-----------------|
| FLAMMABLE LIQUID | 2 |
| EYE IRRITATION | 2A |

PICTOGRAM(S)



Precautionary Statements

| | |
|--------------------|--|
| Prevention: | P210 - Keep away from heat, sparks, open flames, hot surfaces - no smoking. P233 - Keep container tightly closed. P240 - Ground and bond container and receiving equipment. P241 - Use explosion-proof equipment. P242 - Use non-sparking tools. P243 - Take action to prevent static discharges. P264 - Wash affected area thoroughly after handling. |
| Response: | P280 - Wear protective gloves, clothing, eye and face protection. P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 - If eye irritation persists: Get medical attention. |
| Storage: | P370+P378 - In case of fire: Use foam, dry chemical or carbon dioxide to extinguish. |
| Disposal: | P403+P235 - Store in a well-ventilated place. Keep cool. P501 - Dispose of contents and/or container according to Federal, State/Provincial and local |

IDH number: 1654127

Product name: LePage PL600 Landscape Block Adhesive

governmental regulations.

Other hazards Not available.

Classification complies with Canadian Hazardous Products Regulations and is consistent with the provision of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s) | CAS Number | Weight %* |
|--|------------|-----------|
| Kaolin | 1332-58-7 | 10 - 30 |
| acetone | 67-64-1 | 10 - 30 |
| Petroleum resins | 64742-16-1 | 5 - 10 |
| Methyl acetate | 79-20-9 | 1 - 5 |
| Quartz (SiO ₂) respirable particulates (RCS) >=10% | 14808-60-7 | 0.1 - 1 |
| Cristobalite | 14464-46-1 | 0.1 - 1 |
| Titanium dioxide | 13463-67-7 | 0.1 - 1 |

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

First Aid Measures by likely routes of exposure

| | |
|--|--|
| Inhalation: | If inhaled, immediately remove the affected person to fresh air. If breathing is difficult, give oxygen. If symptoms develop and persist, get medical attention. |
| Skin contact: | Immediately wash skin thoroughly with soap and water. If symptoms develop and persist, get medical attention. |
| Eye contact: | In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention. |
| Ingestion: | Do not induce vomiting, seek medical advice immediately. |
| Most important symptoms and effects (acute and delayed): | The most important known symptoms and effects, both acute and delayed, are described in Section 11: Toxicological Information. |
| Indication of any immediate medical attention / special treatment needed: | Not available. |

5. FIRE FIGHTING MEASURES

| | |
|---|--|
| Extinguishing media: | Foam, dry chemical or carbon dioxide. In case of fire, keep containers cool with water spray. |
| Improper extinguishing agents: | Not available. |
| Special firefighting procedures: | Wear a self-contained breathing apparatus with a full face piece operated in pressure-demand or other positive pressure mode. Wear full protective clothing. |
| Unusual fire or explosion hazards: | Closed containers may explode when exposed to extreme heat. Vapors may form explosive mixtures with air. Vapors are heavier than air and may travel along floor to an ignition source. |

Hazardous combustion products:

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:

Eliminate all sources of ignition or flammables that may come into contact with a spill of this material. Ventilate area. Prevent further leakage or spillage if safe to do so. Wear appropriate protective equipment and clothing during clean-up. Do not allow product to enter sewer or waterways.

Clean-up methods:

Use noncombustible absorbent material such as sand. Use non-sparking tools for clean-up. Absorb spill with inert material. Shovel material into appropriate container for disposal. Dispose of according to Federal, State and local governmental regulations.

7. HANDLING AND STORAGE

Handling:

Do not pressurize, cut, heat or weld containers. Empty product containers may contain product residue. Do not reuse empty containers. Use only in well-ventilated areas. Keep out of the reach of children. Keep away from heat, spark and flame. Containers should be grounded and bonded to the receiving container.

Storage:

For safe storage, store between -20 °C (-4°F) and 50 °C (122°F)
Keep away from heat, spark and flame. Keep containers closed when not in use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s) | ACGIH TLV | OSHA PEL | AIHA WEEL | OTHER |
|---|---|--|-----------|-------|
| Dolomite | 3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Inhalable particles. | 50 MPPCF TWA Total dust. 15 mg/m3 TWA Total dust. 15 MPPCF TWA Respirable fraction. 5 mg/m3 TWA Respirable fraction. 5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. | None | None |
| Kaolin | 2 mg/m3 TWA Respirable fraction. | 5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 15 MPPCF TWA Respirable fraction. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust. | None | None |
| acetone | 250 ppm TWA 500 ppm STEL | 1,000 ppm (2,400 mg/m3) PEL | None | None |
| Methyl acetate | 200 ppm TWA 250 ppm STEL | 200 ppm (610 mg/m3) PEL | None | None |
| Quartz (SiO2) respirable particulates (RCS) >=10% | 0.025 mg/m3 TWA Respirable fraction. | 0.05 mg/m3 TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m3 OSHA_ACT (Respirable dust.) 0.05 mg/m3 PEL Respirable dust. 2.4 MPPCF TWA Respirable 0.1 mg/m3 TWA Respirable | None | None |
| Cristobalite | 5 mg/m3 TWA Inhalable fraction. 1 FIBERS/CM3 TWA Fiber. 0.025 mg/m3 TWA Respirable fraction. | 1.2 MPPCF TWA Respirable 0.05 mg/m3 TWA Respirable 0.05 mg/m3 TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m3 OSHA_ACT (Respirable dust.) 0.05 mg/m3 PEL Respirable dust. | None | None |
| Titanium dioxide | 0.2 mg/m3 TWA Respirable nanoscale particles 2.5 mg/m3 TWA Respirable finescale particles | 15 mg/m3 PEL Total dust. 15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. | None | None |

| | |
|--------------------------------|---|
| Engineering controls: | Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination below occupational exposure limits. |
| Respiratory protection: | Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists. When workplace hazards warrant the use of a respirator, appropriate respirators must be used, and a program that follows 29 CFR 1910.134 must be followed. |
| Eye/face protection: | Safety goggles or safety glasses with side shields. |
| Skin protection: | Chemical resistant, impermeable gloves. |

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|---|
| Physical state: | Liquid |
| Color: | Beige |
| Odor: | Acetone |
| Odor threshold: | Not available. |
| pH: | 7 |
| Vapor pressure: | Not available. |
| Boiling point/range: | 56 - 57 °C (132.8 - 134.6 °F) |
| Melting point/ range: | < 0 °C (< 32°F) |
| Density/Relative density: | 1.44 |
| Relative vapor density: | 2.0 |
| Flash point: | -17 °C (1.4 °F) |
| Flammable/Explosive limits - lower: | Not available. |
| Flammable/Explosive limits - upper: | Not available. |
| Autoignition temperature: | Not available. |
| Flammability: | Not applicable |
| Evaporation rate: | 14.4 |
| Solubility: | Slightly soluble Water |
| Partition coefficient n-octanol/water (logarithmic value): | Not available. |
| VOC content: | 0.22 %; 5.67 g/l (by weight, calculated using CARB method; g/L less water, less exempts calculated using SCAQMD method) |
| Dynamic viscosity: | 375,000 mPa.s |
| Kinematic viscosity: | Not available. |
| Particle characteristics: | Not available. |
| Decomposition temperature: | Not available. |

10. STABILITY AND REACTIVITY

| | |
|--|--|
| Stability: | Stable under normal conditions of storage and use. |
| Hazardous reactions: | Will not occur. |
| Hazardous decomposition products: | Carbon dioxide, carbon monoxide and irritating and/or toxic gases and particulate may be generated by thermal decomposition or combustion. |
| Incompatible materials: | Strong oxidizing agents. |
| Reactivity: | Not available. |
| Conditions to avoid: | Heat, flames, sparks and other sources of ignition. |

11. TOXICOLOGICAL INFORMATION

| | |
|-----------------------------------|-----------------------------------|
| Likely routes of exposure: | Skin, Inhalation, Eyes, Ingestion |
|-----------------------------------|-----------------------------------|

Potential Health Effects/Symptoms

Inhalation: Irritates the nose, throat and respiratory system. Exposure to high doses may cause central nervous system depression. Such doses may also cause adverse effects in the liver, kidneys, and lungs. Abrasion of cured material such as by sanding or grinding could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of this product causes no such release. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Skin contact: Prolonged and/or repeated skin contact with this product may cause irritation/dermatitis.

Eye contact: Contact with eyes can cause eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Ingestion: Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

| Hazardous Component(s) | LD50s and LC50s |
|--|--|
| Kaolin | Oral LD50 (Rat) = > 5,000 mg/kg Dermal LD50 (Rat) = > 5,000 mg/kg |
| acetone | Oral LD50 (Mouse) = 5.2 g/kg Oral LD50 (Mouse) = 3,000 mg/kg Oral LD50 (Rabbit) = 5,340 mg/kg Oral LD50 (Rat) = 5,800 mg/kg Oral LD50 (Rat) = 9,800 mg/kg Dermal LD50 (Rabbit) = 20,000 mg/kg Inhalation LC50 (Rat, 4 h) = 76 mg/l Inhalation LC50 (Rat, 4 h) = 50.1 mg/l |
| Petroleum resins | None |
| Methyl acetate | Oral LD50 (Rabbit) = 3.7 g/kg |
| Quartz (SiO ₂) respirable particulates (RCS) >=10% | None |
| Cristobalite | None |
| Titanium dioxide | Inhalation LC50 (Rat, 4 h) = > 6.82 mg/l Inhalation LC50 (Rat, 4 h) = > 2.28 mg/l Inhalation LC50 (Rat, 4 h) = > 3.56 mg/l |

| Hazardous Component(s) | Immediate Health Effects | Delayed Health Effects | Chronic Health Effects |
|--|--------------------------|------------------------|---|
| Kaolin | Nuisance dust | | |
| acetone | Irritant | | Central nervous system |
| Petroleum resins | | | Central nervous system |
| Methyl acetate | Irritant | | Blood Central nervous system Eyes |
| Quartz (SiO ₂) respirable particulates (RCS) >=10% | | | |
| Cristobalite | | | |
| Titanium dioxide | Irritant | | Respiratory Some evidence of carcinogenicity |

| Hazardous Component(s) | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|--|-------------------------------|-----------------|--|
| Kaolin | No | No | No |
| acetone | No | No | No |
| Petroleum resins | No | Group 2B | No |
| Methyl acetate | No | No | No |
| Quartz (SiO ₂) respirable particulates (RCS) >=10% | Known To Be Human Carcinogen. | Group 1 | Yes |
| Cristobalite | Known To Be Human Carcinogen. | Group 1 | Yes |
| Titanium dioxide | No | Group 2B | No |

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

Canada Transportation of Dangerous Goods - Ground

Proper shipping name: ADHESIVES
Hazard class or division: 3
Identification number: UN 1133
Packing group: II

International Air Transportation (ICAO/IATA)

Proper shipping name: Adhesives
Hazard class or division: 3
Identification number: UN 1133
Packing group: II

Water Transportation (IMO/IMDG)

Proper shipping name: ADHESIVES
Hazard class or division: 3
Identification number: UN 1133
Packing group: II

15. REGULATORY INFORMATION

Canada Regulatory Information

CEPA DSL/NDSL Status: Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: This Safety Data Sheet contains changes from the previous version in Section(s): 15

Prepared by: Product Safety and Regulatory Affairs

Issue date: 09/16/2025

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on the Canadian Hazardous Products Regulations (WHMIS 2015) and provides information in accordance with Canadian law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.