



## Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 19

Pattex trans. 12x50 g UE PXT90

SDS No. : 197593  
V004.0

Revision: 24.03.2026  
printing date: 26.03.2026

Replaces version from: 01.10.2024

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Pattex trans. 12x50 g UE PXT90

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:  
Contact adhesive

#### 1.3. Details of the supplier of the safety data sheet

Henkel Jebal Ali FZCO  
PO Box 61341 - Jebel Ali  
Dubai

Utd.Arab.Emir.

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website [www.mysds.henkel.com](http://www.mysds.henkel.com) or [www.henkel-adhesives.com](http://www.henkel-adhesives.com).

#### 1.4. Emergency telephone number

HAAD Poison and Drug Information Center UAE, TOLL FREE TEL. NUMBER 800-424

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (CLP):

Flammable liquids	Category 2
H225 Highly flammable liquid and vapour.	
Serious eye irritation	Category 2
H319 Causes serious eye irritation.	
Specific target organ toxicity - single exposure	Category 3
H336 May cause drowsiness or dizziness.	
Target organ: Central nervous system	

#### 2.2. Label elements

##### Label elements (CLP):

Hazard pictogram:



Contains

acetone

<b>Signal word:</b>	Danger
<b>Hazard statement:</b>	H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.
<b>Supplemental information</b>	EUH066 Repeated exposure may cause skin dryness or cracking.
<b>Precautionary statement:</b>	P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children.
<b>Precautionary statement: Prevention</b>	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing mist/vapours. P271 Use only outdoors or in a well-ventilated area. P280 Wear eye protection.
<b>Precautionary statement: Disposal</b>	P501 Dispose of contents/container in accordance with national regulation.

### 2.3. Other hazards

Solvents contained in the product evaporate during processing and their vapors can form explosive/highly inflammable air/vapor mixtures.

Pregnant women should absolutely avoid inhalation and skin contact.

Following substances are present in a concentration  $\geq$  the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration  $\geq$  the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg. No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
acetone 67-64-1 200-662-2 01-2119471330-49	60- < 80 %	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336		EU OEL EUEXPL2D
Ethyl acetate 141-78-6 205-500-4 01-2119475103-46	10- < 20 %	Flam. Liq. 2, H225 STOT SE 3, H336 Eye Irrit. 2, H319		EU OEL

If no ATE values are displayed, please refer to LD/LC50 values in Section 11.

For full text of the H - statements and other abbreviations see section 16 "Other information".

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

General information:

In case of adverse health effects seek medical advice.

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap. Skin care. Remove contaminated clothes immediately.

Eye contact:

Immediately flush eyes with soft jet of water or eye rinse solution for at least 5 minutes. If pains remain (intensive smarting, sensitivity to light, visual disturbance) continue flushing and contact/seek doctor or hospital.

Ingestion:

Rinse mouth, do not induce vomiting, consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

Causes serious eye irritation.

Vapors may cause drowsiness and dizziness.

Repeated exposure may cause skin dryness or cracking.

### 4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media:

carbon dioxide, foam, powder, water spray jet, fine water spray

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

### 5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO<sub>2</sub>) can be released.

### 5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Wear protective equipment.

Additional information:

Cool endangered containers with water spray jet.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment.

Avoid contact with skin and eyes.

Ensure adequate ventilation.

Danger of slipping on spilled product.

### 6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

**6.3. Methods and material for containment and cleaning up**

Remove with liquid-absorbing material (sand, peat, sawdust).  
Dispose of contaminated material as waste according to Section 13.

**6.4. Reference to other sections**

See advice in section 8

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

During processing and drying after adhesion, ventilate well. Avoid all sources of fire such as stoves and ovens. Switch off all electrical devices such as parabolic heaters, hot plates, storage heaters etc. in good time for them to have cooled down before commencing work. Avoid all sparks, including those occurring at electrical switches and devices.  
Ventilate working rooms thoroughly. Avoid naked flames, sparking and sources of ignition. Switch off electrical devices. Do not smoke, do not weld. Do not empty waste into waste water drains.  
Avoid skin and eye contact.

Hygiene measures:

Wash hands before work breaks and after finishing work.  
Do not eat, drink or smoke while working.

**7.2. Conditions for safe storage, including any incompatibilities**

Store frost-free.  
Close the container carefully after use and store it at a good ventilated place.  
Store protected from heat influence.  
< + 30 °C  
Keep only in original container.

Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

**7.3. Specific end use(s)**

Contact adhesive

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational Exposure Limits**

Valid for  
Utd.Arab.Emir.

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Acetone 67-64-1 [ACETONE]	500	1.188	Time Weighted Average (TWA):		AD TLV
Acetone 67-64-1 [ACETONE]	750	1.782	Short Term Exposure Limit (STEL):		AD TLV
Acetone 67-64-1 [ACETONE]	1.000	2.380	Short Term Exposure Limit (STEL):		GCC TLV
Acetone 67-64-1 [ACETONE]	750	1.780	Time Weighted Average (TWA):		GCC TLV
Acetone 67-64-1 [ACETONE]	750	1.780	Time Weighted Average (TWA):		UAE OEL
Acetone 67-64-1 [ACETONE]	1.000	2.380	Short Term Exposure Limit (STEL):		UAE OEL
Acetone 67-64-1 [ACETONE]	750		Time Weighted Average (TWA):		DB OEL
Acetone 67-64-1 [ACETONE]	1.000		Short Term Exposure Limit (STEL):		DB OEL
Ethyl acetate 141-78-6 [ETHYL ACETATE]	400	1.440	Time Weighted Average (TWA):		AD TLV
Ethyl acetate 141-78-6 [ETHYL ACETATE]	400	1.440	Time Weighted Average (TWA):		GCC TLV
Ethyl acetate 141-78-6 [ETHYL ACETATE]	400	1.440	Time Weighted Average (TWA):		UAE OEL
Ethyl acetate 141-78-6 [ETHYL ACETATE]	400		Time Weighted Average (TWA):		DB OEL

**Safety Data Sheet according to (EC) No 1907/2006 as amended**

SDS No.: 197593 V004.0

Page 6 of 19

**Occupational Exposure Limits**

Valid for  
Bahrain

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Acetone 67-64-1 [ACETONE]	750	1.780	Time Weighted Average (TWA):		BH TLV
Acetone 67-64-1 [ACETONE]	1.000	2.380	Short Term Exposure Limit (STEL):		BH TLV
Acetone 67-64-1 [ACETONE]	1.000	2.380	Short Term Exposure Limit (STEL):		GCC TLV
Acetone 67-64-1 [ACETONE]	750	1.780	Time Weighted Average (TWA):		GCC TLV
Ethyl acetate 141-78-6 [ETHYL ACETATE]	400	1.440	Time Weighted Average (TWA):		GCC TLV
Ethyl acetate 141-78-6 [ETHYL ACETATE]	400	1.440	Time Weighted Average (TWA):		BH TLV

**Occupational Exposure Limits**

Valid for  
Egypt

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Acetone 67-64-1 [ACETONE]	750	1.780	Short-term Exposure Limit (STEL):		EG OEL
Acetone 67-64-1 [ACETONE]	500	1.187	Time Weighted Average (TWA):		EG OEL
Ethyl acetate 141-78-6 [ETHYL ACETATE]	400	1.440	Time Weighted Average (TWA):		EG OEL

**Occupational Exposure Limits**

Valid for  
Jordan

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Ethyl acetate 141-78-6 [ETHYL ACETATE]	400	1.400	Time Weighted Average (TWA):		JO TLV

**Occupational Exposure Limits**

Valid for  
Kuwait

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Acetone 67-64-1 [ACETONE]	1.000	2.380	Short Term Exposure Limit (STEL):		GCC TLV
Acetone	750	1.780	Time Weighted Average		GCC TLV

**Safety Data Sheet according to (EC) No 1907/2006 as amended**

SDS No.: 197593 V004.0

Page 7 of 19

67-64-1 [ACETONE]			(TWA):		
Acetone 67-64-1 [ACETONE]	750	1.800	Time Weighted Average (TWA):		KW OEL
Acetone 67-64-1 [ACETONE]	1.000	2.400	Short-term Exposure Limit (STEL):		KW OEL
Acetone 67-64-1 [ACETONE]	2.500		Harmful Concentration for risk to health and life:		KW OEL

**Occupational Exposure Limits**

Valid for  
Israel

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Acetone 67-64-1 [Acetone]	500		Short-term exposure limit (STEL):		IL OEL
Acetone 67-64-1 [Acetone]	250		Time Weighted Average (TWA):		IL OEL
Ethyl acetate 141-78-6 [ETHYL ACETATE]	400		Time Weighted Average (TWA):		IL OEL

**Occupational Exposure Limits**

Valid for  
Kenya

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Acetone 67-64-1 [ACETONE]	1.500	3.560	Short-term OEL-RL:		KE OEL-RL
Acetone 67-64-1 [ACETONE]	750	1.780	Time-weighted average (TWA) OEL-RL:		KE OEL-RL
Ethyl acetate 141-78-6 [ETHYL ACETATE]	400	1.400	Time-weighted average (TWA) OEL-RL:		KE OEL-RL

**Biological Exposure Indices:**

None

Ingredient [Regulated substance]	Parameters	Biological specimen	Sampling time	Conc.	Basis of biol. exposure index	Remark	Additional Information
Acetone 67-64-1 [ACETONE]	acetone	Urine	Sampling time: End of shift.	100 mg/l	KW BEL		
Acetone 67-64-1 [ACETONE Acetone]	acetone	Urine	Sampling time: End of shift.	25 mg/l	IL BEI	Nonspecific	Source of Limit value: ACGIH

**8.2. Exposure controls:**

**Respiratory protection:**

The product should only be used at workplaces with intensive ventilation/extraction. If intensive ventilation/extraction is not possible then self-contained independent respiratory protection should be worn.

**Hand protection:**

Recommended are gloves made from Nitril rubber ( Material thickness >0,1 mm, Perforation time < 30s).Gloves should be replaced after each short time contact or contamination. Available at laboratory specialized trade or at pharmacies / chemist's shops.

In the case of longer contact protective gloves made from chloroprene rubber are recommended according to EN 374.

material thickness > 0.6 mm

Perforation time > 10 minutes

In the case of longer and repeated contact please note that in practice the penetration times may be considerably shorter than those determined according to EN 374. The protective gloves must always be checked for their suitability for use at the specific workplace (e.g. mechanical and thermal stress, product compatibility, antistatic effects, etc.). The gloves must be replaced immediately at the first signs of wear and tear. The information provided by the manufacturers and given in the relevant trade association regulations for industrial safety must always be observed. We recommend that a hand care plan is drawn up in cooperation with a glove manufacturer and the trade association in accordance with the local operating conditions.

**Eye protection:**

Goggles which can be tightly sealed.

Protective eye equipment should conform to EN166.

**Skin protection:**

Suitable protective clothing

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

**Advices to personal protection equipment:**

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

## SECTION 9: Physical and chemical properties

**9.1. Information on basic physical and chemical properties**

Delivery form	liquid
Colour	Colourless / Colorless
Odor	Typical
Physical state	liquid
Melting point	Not applicable, Product is a liquid
Solidification temperature	-2 °C (28.4 °F)
Initial boiling point	58 °C (136.4 °F); Boiling point
Flammability	Flammable liquid
Explosive limits	
lower	0,9 %(V); No data available.
upper	14,3 %(V); Upper/lower explosion limit
Flash point	-22 °C (-7.6 °F); no method / method unknown
Auto-ignition temperature	415 °C (779 °F)
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use
pH	Not applicable, Product is non-soluble (in water).
Viscosity (kinematic)	2.900 - 4.500 mm <sup>2</sup> /s
(40 °C (104 °F); )	
Viscosity, dynamic	2.500 - 4.000 mPa.s ISO 2555-89 Viscosity according to Brookfield
(Brookfield; 20 °C (68 °F); speed of rotation: 50 min-1; Spindle No: 5)	
Solubility (qualitative)	Partially miscible
(20 °C (68 °F); Solvent: Water)	
Partition coefficient: n-octanol/water	Not applicable
	Mixture
Vapour pressure	716 mbar
(50 °C (122 °F))	
Vapour pressure	230 mbar

(20 °C (68 °F))	
Density	0,85 - 0,89 g/cm3 QP2107.1; Density
(20 °C (68 °F))	
Relative vapour density:	1,32
(20 °C)	
Particle characteristics	Not applicable Product is a liquid

**9.2. Other information**

No data available / Not applicable

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

None if used for intended purpose.

**10.2. Chemical stability**

Stable under recommended storage conditions.

**10.3. Possibility of hazardous reactions**

See section reactivity

**10.4. Conditions to avoid**

None if used for intended purpose.

**10.5. Incompatible materials**

None if used properly.

**10.6. Hazardous decomposition products**

None known.

**SECTION 11: Toxicological information**

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Value type	Value	Species	Method
acetone 67-64-1	LD50	5.800 mg/kg	rat	not specified
Ethyl acetate 141-78-6	LD50	6.100 mg/kg	rat	not specified

**Acute dermal toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Value type	Value	Species	Method
acetone 67-64-1	LD50	> 15.688 mg/kg	rabbit	Draize Test
Ethyl acetate 141-78-6	LD50	> 20.000 mg/kg	rabbit	Draize Test

**Acute inhalative toxicity:**

The toxicity of the product is due to its narcotic effect after inhalation.  
In the event of protracted or repeated exposure, damage to health cannot be excluded.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
acetone 67-64-1	LC50	76 mg/l	vapour	4 h	rat	not specified
Ethyl acetate 141-78-6	LC50	57,7 mg/l	vapour	4 h	rat	not specified
Ethyl acetate 141-78-6	LC50	> 22,5 mg/l	vapour	6 h	rat	other guideline:

**Skin corrosion/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
acetone 67-64-1	not irritating		guinea pig	not specified
Ethyl acetate 141-78-6	slightly irritating	24 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

**Serious eye damage/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
acetone 67-64-1	irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Ethyl acetate 141-78-6	slightly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

**Respiratory or skin sensitization:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result	Test type	Species	Method
acetone 67-64-1	not sensitising	Guinea pig maximisation test	guinea pig	not specified
Ethyl acetate 141-78-6	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

**Germ cell mutagenicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
acetone 67-64-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
acetone 67-64-1	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
acetone 67-64-1	negative	mammalian cell gene mutation assay	without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Ethyl acetate 141-78-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Ethyl acetate 141-78-6	negative	in vitro mammalian chromosome aberration test	with and without		equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
acetone 67-64-1	negative	oral: drinking water		mouse	not specified
Ethyl acetate 141-78-6	negative	oral: gavage		hamster, Chinese	equivalent or similar to OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

**Carcinogenicity**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
acetone 67-64-1	not carcinogenic	dermal	424 d 3 times per week	mouse	female	not specified

**Reproductive toxicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Ethyl acetate 141-78-6	NOAEL P 1500 ppm	other:	inhalation	rat	other guideline:

**STOT-single exposure:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Assessment	Route of exposure	Target Organs	Remarks
acetone 67-64-1	May cause drowsiness or dizziness.			
Ethyl acetate 141-78-6	May cause drowsiness or dizziness.			

**STOT-repeated exposure:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
acetone 67-64-1	NOAEL 900 mg/kg	oral: drinking water	13 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Ethyl acetate 141-78-6	NOAEL 900 mg/kg	oral: gavage	90 d daily	rat	EPA OTS 795.2600 (Subchronic Oral Toxicity Test)

**Aspiration hazard:**

No data available.

**11.2 Information on other hazards**

**11.2.1 Endocrine disrupting properties**

No data available.

## SECTION 12: Ecological information

**General ecological information:**

Do not empty into drains, soil or bodies of water.

**12.1. Toxicity****Toxicity (Fish):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
acetone 67-64-1	LC50	8.120 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Ethyl acetate 141-78-6	LC50	220 mg/l	96 h	Pimephales promelas	other guideline:

**Toxicity (aquatic invertebrates):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
acetone 67-64-1	EC50	8.800 mg/l	48 h	Daphnia pulex	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Ethyl acetate 141-78-6	EC50	164 mg/l	48 h	Daphnia cucullata	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

**Chronic toxicity (aquatic invertebrates):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
acetone 67-64-1	NOEC	2.212 mg/l	28 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Ethyl acetate 141-78-6	NOEC	2,4 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

**Toxicity (Algae):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
acetone 67-64-1	NOEC	530 mg/l	8 d	Microcystis aeruginosa	DIN 38412-09
Ethyl acetate 141-78-6	EC50	> 2.000 mg/l	96 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Ethyl acetate 141-78-6	NOEC	2.000 mg/l	96 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)

**Toxicity (microorganisms):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
acetone 67-64-1	EC10	1.000 mg/l	30 min	Pseudomonas putida	DIN 38412, part 27 (Bacterial oxygen consumption test)
Ethyl acetate 141-78-6	EC10	2.900 mg/l	18 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm- Test)

**12.2. Persistence and degradability**

**Biodegradability (Screening Tests):**

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
acetone 67-64-1	readily biodegradable	aerobic	81 - 92 %	30 d	EU Method C.4-E (Determination of the "Ready" Biodegradability Closed Bottle Test)
Ethyl acetate 141-78-6	readily biodegradable	aerobic	100 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

**(Bio)degradability (Simulation Tests):**

No data available.

**12.3. Bioaccumulative potential**

**Partition Coefficient (octanol/water)**

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
acetone 67-64-1	-0,24		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Ethyl acetate 141-78-6	0,68	25 °C	EPA OPPTS 830.7560 (Partition Coefficient, n-octanol / H2O, Generator Column Method)

**Bioconcentration factor (BCF)**

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Bioconcentration factor (BCF)	Exposure time	Temperature	Species	Method
Ethyl acetate 141-78-6	30	3 d	22,5 °C	Leuciscus idus melanotus	other guideline:

**12.4. Mobility in soil**

No data available.

**12.5. Results of PBT / vPvB / PMT / vPvM assessment**

**PBT/vPvB**

This mixture does not contain any substances that are assessed to be a PBT or vPvB.  
Based on available data, the classification criteria are not met.

**PMT/vPvM**

This mixture does not contain any substances that are assessed to be a PMT or vPvM.  
Based on available data, the classification criteria are not met.

**12.6. Endocrine disrupting properties**

No data available.

**12.7. Other adverse effects**

No data available.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

Waste code

080409

**SECTION 14: Transport information****14.1. UN number or ID number**

ADR	1133
RID	1133
ADN	1133
IMDG	1133
IATA	1133

**14.2. UN proper shipping name**

ADR	ADHESIVES
RID	ADHESIVES
ADN	ADHESIVES
IMDG	ADHESIVES
IATA	Adhesives

**14.3. Transport hazard class(es)**

ADR	3
RID	3
ADN	3
IMDG	3
IATA	3

**14.4. Packing group**

ADR	II
RID	II
ADN	II
IMDG	II
IATA	II

**14.5. Environmental hazards**

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

**14.6. Special precautions for user**

ADR	Special provision 640D Tunnelcode: (D/E)
RID	Special provision 640D
ADN	Special provision 640D
IMDG	not applicable
IATA	not applicable

Packed goods < 450 L (ADR/IMDG) can be classified in packaging group III, based of the viscosity (ADR 2.2.3.1.4 und IMDG 2.3.2.2)

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

No information available:

Ozone Depleting Substance (ODS) (Regulation (EC) No 2024/590):

Not applicable

Persistent organic pollutants (Regulation (EU) 2019/1021):

Not applicable

**15.2. Chemical safety assessment**

A chemical safety assessment has been carried out.

### SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

- H225 Highly flammable liquid and vapour.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.

Abbreviations and acronyms:

- ADG(-Code): Australian Dangerous Goods (Code)
- ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
- ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road
- ASTM: American Society for Testing and Materials
- ATE: acute toxicity estimate
- AS: Australian Standard
- AwSV: Ordinance on Installations for the Handling of Substances Hazardous to Water
- CAS: Chemical Abstract Service
- CLP: Regulation (EC) No 1272/2008
- CMR: cancerogenic, mutagenic or reprotoxic
- DIN: German Institute for Standardization
- ECx: Effective concentration (x% effective level)
- ECHA: European Chemicals Agency
- EC-Nummer: Substance number in the EU-inventories EINECS/ELINCS
- ECLTV: European community threshold limit value
- ED: Substance identified as having endocrine disrupting properties
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- EN : European Standard
- ENCS: Japanese chemical inventory
- EPA: US Environmental Protection Agency
- EU: European Union
- EU EXPLD1: Substance listed in Annex I, Reg (EC) No. 2019/1148
- EU EXPLD2: Substance listed in Annex II, Reg (EC) No. 2019/1148
- EWC: European Waste Catalogue
- GHS: Globally Harmonised System for Classification and Labelling of Chemicals
- GLP: Good Laboratory Practice
- HSNO: Hazardous Substances and New Organisms
- IARC: International Agency for Research of Cancer
- IATA: International Air Transport Association
- IBC-Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
- IC50: half maximal inhibitory concentration
- ICAO: International Civil Aviation Organization
- IMDG-Code: International Maritime Code for Dangerous Goods
- IMO: International Maritime Organization
- ISO: International Standardization Organisation
- LC50: Median lethal concentration
- LD50: Median lethal dose
- MARPOL: International Convention for the Prevention of Marine Pollution from Ships
- n.o.s.: not otherwise specified
- NO(A)EC: No (adverse) effect concentration
- NO(A)EL: No (adverse) effect level
- NZS: New Zealand Standard
- OECD: Organisation for Economic Co-operation and Development
- OEL: Occupational Exposure Limit
- OPPT: US EPA Office of Pollution Prevention and Toxics
- OPPTS: US EPA Office of Prevention, Pesticides and Toxic Substances
- PBT: Persistent, bioaccumulative, toxic
- PMT: Persistent, mobile and toxic
- (Q)SAR: (Quantitative) structure–activity relationship
- REACH: Regulation (EC) No. 1907/2006
- RID: Regulations concerning the International Transport of Dangerous Goods by Rail
- SADT: Self Accelerating Decomposition Temperature
- SDS: Safety Data Sheet

STOT: Specific Target Organ Toxicity  
STOT SE: Specific Target Organ Toxicity - single exposure  
STOT RE: Specific Target Organ Toxicity - repeated exposure  
SUSMP: Standard for the Uniform Scheduling of Medicines and Poisons  
SVHC: Substance of very high concern (REACH Candidate List)  
TRGS: German Technical Rules for hazardous substances  
UN: United Nations  
VOC: Volatile Organic Compound  
814.018 VOC Reg CH: Swiss Ordinance 814.018 on the Incentive Tax on Volatile Organic Compounds  
vPvB: Very persistent, very bioaccumulative  
vPvM: Very persistent and very mobile  
VwVwS: Administrative Regulation on Substances Hazardous to Waters  
WGK: Water hazard class

**Further information:**

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

This Safety Data Sheet has been generated based on Regulation (EC) No 1907/2006 and it is applicable for Gulf Cooperation Council (GCC) and Africa only. No warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory, including export laws and regulations. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory affairs for additional assistance.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your\_company.com).

**Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.**