



Safety Data Sheet

Page 1 of 9

LOC 1OZ VINYL FABRIC & PLAS 6PG

SDS No. : 252842

V001.2

Date of issue: 08.05.2025

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: LOC 1OZ VINYL FABRIC & PLAS 6PG

Intended use: Adhesive

Supplier:

Henkel Australia Pty Ltd
135-141 Canterbury Road
Kilsyth, Victoria, 3137
Australia

Phone: +61 (3) 9724 6444

Emergency Telephone for Chemical Accidents: 24 HOUR EMERGENCY CONTACT NUMBER: 1800 032 379

Section 2. Hazards identification

Classification of the substance or mixture

Hazardous according to the criteria of Safe Work Australia.

GHS Classification:

<u>Hazard Class</u>	<u>Hazard Category</u>	<u>Target organ</u>
Flammable liquids	Category 2	
Serious eye irritation	Category 2A	
Skin sensitizer	Category 1	
Target Organ Systemic Toxicant - Single exposure	Category 3	Central nervous system

Hazard pictogram:



Signal word:

Danger

Hazard statement(s):	H225 Highly flammable liquid and vapour. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.
Precautionary Statement(s):	
Prevention:	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion-proof electrical/ventilating/lighting equipment. P242 Use non-sparking tools. P243 Take action to prevent static discharges. P261 Avoid breathing mist/vapours. P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves/protective clothing/eye protection/face protection.
Response:	P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
Storage:	P403+P233 Store in a well-ventilated place. Keep container tightly closed. P403+P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.
Disposal:	P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations.

Dangerous Goods information:

Classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

Section 3. Composition / information on ingredients

General chemical description: Mixture

Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion
Butanone	78-93-3	60- <= 100 %
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	41556-26-7	0.1- < 3 %

Section 4. First aid measures

Ingestion:	Do not induce vomiting. Have victim rinse mouth thoroughly with water. Seek medical advice.
Skin:	Rinse with running water and soap. Seek medical advice.
Eyes:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical advice.

Inhalation: Move to fresh air.
Keep warm and in a quiet place.
Seek medical advice.

First Aid facilities: Eye wash and safety shower
Normal washroom facilities

Medical attention and special treatment: Treat symptomatically.

Section 5. Fire fighting measures

Suitable extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Improper extinguishing media: High pressure waterjet

Decomposition products in case of fire: Thermal decomposition can lead to release of irritating gases and vapors.
Carbon monoxide.
Carbon dioxide.

Particular danger in case of fire: WARNING FLAMMABLE!
Vapors may form explosive mixtures with air.

Special protective equipment for fire-fighters: Wear full protective clothing.
Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA).

Additional fire fighting advice: Cool endangered containers with water spray jet.
Collect contaminated fire fighting water separately. It must not enter drains.

Section 6. Accidental release measures

Personal precautions: Keep away from sources of ignition.
Ensure adequate ventilation.
Avoid skin and eye contact.
Wear appropriate personal protective equipment.

Environmental precautions: Do not empty into drains / surface water / ground water.

Clean-up methods: Soak up with inert absorbent.
Use noncombustible absorbent material such as sand.
Dispose of contaminated material as waste according to Section 13.

Section 7. Handling and storage

Precautions for safe handling: Ventilate working rooms thoroughly. Avoid naked flames, sparking and sources of ignition. Switch off electrical devices. Do not smoke, do not weld. Do not empty waste into waste water drains.
Take measures to prevent the build-up of electrostatic charges.
Wear suitable protective clothing, gloves and eye/face protection.

Conditions for safe storage: Store in sealed original container.
Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.
Do not expose to direct sunlight.
Refer to AS 1940: The Storage and Handling of Flammable and Combustible Liquids.

Section 8. Exposure controls / personal protection

National exposure standards:

Ingredient [Regulated substance]	form of exposure	TWA (ppm)	TWA (mg/m3)	Peak Limit. (ppm)	Peak Limit. (mg/m3)	STEL (ppm)	STEL (mg/m3)
METHYL ETHYL KETONE (MEK) 78-93-3						300	890
METHYL ETHYL KETONE (MEK) 78-93-3		150	445				

Engineering controls: Use explosion-proof mechanical ventilation and local exhaust to control contaminants to within their occupational exposure limits during the use of this product.

Eye protection: Protective goggles

Skin protection: Wear suitable protective clothing.
The use of chemical resistant gloves such as Nitrile is recommended.
Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced.

Respiratory protection: If inhalation risk exists, wear a respirator or air supplied mask complying with the requirements of AS/NZS 1715 and AS/NZS 1716.

General protection measures: Use only in well-ventilated areas.

Section 9. Physical and chemical properties

Appearance: Cream
Liquid

Odor: Ketone

Specific gravity: 1.101

Boiling point: 65 - 121 °C (149 - 249.8 °F)

Flash point: -9 - -7 °C (15.8 - 19.4 °F)
(Supplier method)

Evaporation rate: 4.8
(Butyl acetate = 1)

Lower explosive limit: 1 %(V)

Upper explosive limit: 6.5 %(V)

Vapor pressure: 155 mm hg
(; 20 °C (68 °F))

Vapor density: > 1
Heavier than air

Density: 0.83 - 0.91 g/cm3

Solubility in water: Insoluble (23 °C)

Section 10. Stability and reactivity

Stability:	Stable under recommended storage conditions.
Conditions to avoid:	Heat, flames, sparks and other sources of ignition.
Incompatible materials:	Strong oxidizing agents.
Hazardous decomposition products:	Thermal decomposition can lead to release of irritating gases and vapors. Carbon monoxide. Carbon dioxide.
Hazardous polymerization:	Will not occur.

Section 11. Toxicological information

Health Effects:

Ingestion:	Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Skin:	May cause mild skin irritation. Repeated exposure may cause skin dryness or cracking. May cause skin sensitization.
Eyes:	Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Inhalation:	Vapours may cause drowsiness and dizziness. Vapors may cause headaches, nausea, dizziness and respiratory tract irritation.

Acute toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Butanone 78-93-3	LD50 LC50 LD50	2,193 mg/kg 34.5 mg/l > 6,400 mg/kg	oral inhalation dermal	4 h	rat rat rabbit	OECD Guideline 423 (Acute Oral toxicity) not specified not specified
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate 41556-26-7	LD50 Acute toxicity estimate (ATE)	2,369 - 3,920 mg/kg 2,369 mg/kg	oral oral		rat	not specified Expert judgement

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Butanone 78-93-3	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Butanone 78-93-3	irritating		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Butanone 78-93-3	not sensitising	Buehler test	guinea pig	equivalent or similar to OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Butanone 78-93-3	negative negative negative	bacterial reverse mutation assay (e.g Ames test) in vitro mammalian chromosome aberration test mammalian cell gene mutation assay	with and without not applicable with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay) equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Butanone 78-93-3	negative	intraperitoneal		mouse	equivalent or similar to OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Butanone 78-93-3	NOAEL=2500 ppm	inhalation	90 days6 hours/day, 5 days/week	rat	not specified
Butanone 78-93-3	LOAEL=5000 ppm	inhalation	90 days6 hours/day, 5 days/week	rat	not specified

Section 12. Ecological information

General ecological information: Do not empty into drains / surface water / ground water.

Ecotoxicity:

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Butanone 78-93-3	LC50	3,220 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Butanone 78-93-3	EC50	5,091 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Butanone 78-93-3	EC50	1,240 mg/l	Algae	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Butanone 78-93-3	EC10	1,010 mg/l	Algae	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Butanone 78-93-3	EC50	1,150 mg/l	Bacteria	16 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshe mm-Test)
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate 41556-26-7	LC50	0.9 mg/l	Fish	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate 41556-26-7	NOEC	0.22 mg/l	Algae	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate 41556-26-7	EC50	1.68 mg/l	Algae	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate 41556-26-7	EC50	> 100 mg/l	Bacteria	3 h	not specified	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

Persistence and degradability:

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Butanone 78-93-3	readily biodegradable	aerobic	98 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate 41556-26-7	not readily biodegradable.	aerobic	38 %	OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test)

Bioaccumulative potential / Mobility in soil:

Hazardous components CAS-No.	LogPow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Butanone 78-93-3	0.3				40 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate 41556-26-7		< 31.4	56 d	Cyprinus carpio		other guideline:
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate 41556-26-7	> 2.37 - 2.77				25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

Section 13. Disposal considerations

Waste disposal of product: In consultation with the responsible local authority, must be subjected to special treatment.

Disposal for uncleaned package: Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

Section 14. Transport information

Road and Rail Transport:

Dangerous Goods information: Classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

UN no.: 1133
Proper shipping name: ADHESIVES
Class or division: 3
Packing group: II
Emergency Telephone for Chemical Accidents: Refer to the Australian and New Zealand Emergency Response Guidebook

Marine transport IMDG:

UN no.: 1133
Proper shipping name: ADHESIVES
Class or division: 3
Packing group: II
EmS: F-E ,S-D
Seawater pollutant: -

Air transport IATA:

UN no.: 1133
Proper shipping name: Adhesives
Class or division: 3
Packing group: II
Packing instructions (passenger): 353
Packing instructions (cargo): 364

Section 15. Regulatory information

SUSMP Poisons Schedule 5

AIC: All components are listed or are exempt from listing on the Australian Inventory of Industrial Chemicals or Introduced under AICIS.

Section 16. Other information

Abbreviations/acronyms: ADGC - Australian Dangerous Goods Code
GHS: Globally Harmonized System
CAS: Chemical Abstracts Service
LD 50: Lethal Dose 50%
NOAEL: No Observed Adverse Effect Level
LC 50: Lethal Concentration 50%
IMDG: International Maritime Dangerous Goods code
STEL - Short term exposure limit
TWA - Time weighted average
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations
AIIC - Australian Inventory of Industrial Chemicals (AIIC)
AICIS - Australian Industrial Chemicals Introduction Scheme

Reason for issue: Reviewed SDS. Reissued with new date. involved chapters: 1 - 16

Date of previous issue: 03.07.2020

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material.

The information contained in the Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.