



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 25

SDS No. : 679848
V003.0

Revision: 30.01.2025

printing date: 18.03.2025

Replaces version from: 30.11.2023

Ceresit IN 53 lux

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Ceresit IN 53 lux

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Paints and coatings

1.3. Details of the supplier of the safety data sheet

Henkel Bautechnik (Ukraine)

Vyshhorod, Novopromyslova St. 2

07302 Kyiv region

Ukraine

Phone: +380 (800) 308 405

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website www.mysds.henkel.com or www.henkel-adhesives.com.

1.4. Emergency telephone number

0-800-308-405 (24 h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin sensitizer

Category 1

H317 May cause an allergic skin reaction.

Chronic hazards to the aquatic environment

Category 3

H412 Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains

Октил-3(2H)изотиазолон, 2-

Смесь изотиазолинонов (С(М)IT/MIT (3:1))

Signal word:

Warning

Hazard statement:	H317 May cause an allergic skin reaction. H412 Harmful to aquatic life with long lasting effects.
Supplemental information	EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Precautionary statement: Prevention	P273 Avoid release to the environment. P280 Wear protective gloves.
Precautionary statement: Response	P391 Collect spillage.

2.3. Other hazards

None if used properly.

Following substances are present in a concentration \geq the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration \geq the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
Титана двуокись 13463-67-7 236-675-5 01-2119489379-17	5- < 10 %	Carc. 2, Inhalation, H351		
Оксид хрома (III) 1308-38-9 215-160-9 01-2119433951-39	1- < 5 %			EU OEL
Углеводороды, C10-C13, н-алканы, изоалканы, циклические, < 2 % ароматических 64742-48-9 265-150-3, 918-481-9 01-2119457273-39	1- < 5 %	Asp. Tox. 1, H304		
Amines, N-(C16-18 and C18-unsatd. alkyl)trimethylene, di- 1219010-04-4 01-2119487014-41	0,01- < 0,1 %	Aquatic Acute 1, H400 Aquatic Chronic 1, H410 STOT RE 1, H372 Skin Corr. 1B, H314 Acute Tox. 4, Oral, H302 Eye Dam. 1, H318	M acute = 10 M chronic = 1	
Amines, C16-18 and C16-18-unsatd. alkyl 1213789-63-9 01-2119473797-19	0,01- < 0,1 %	Skin Corr. 1B, H314 Acute Tox. 4, Oral, H302 STOT RE 2, Oral, H373 Aquatic Acute 1, H400 STOT SE 3, H335 Asp. Tox. 1, H304 Eye Dam. 1, H318 Aquatic Chronic 2, H411	M acute = 10	
Diuron 330-54-1 206-354-4 01-2119517622-45	0,01- < 0,05 %	Aquatic Chronic 1, H410 Aquatic Acute 1, H400 STOT RE 2, H373 Acute Tox. 4, Oral, H302 Carc. 2, H351	M acute = 10 M chronic = 10 ===== oral:ATE = 1.000 mg/kg inhalation:ATE = 5,051 mg/l;dust/mist	
Carbendazim 10605-21-7 234-232-0 01-2120802826-54	0,01- < 0,05 %	Aquatic Chronic 1, H410 Muta. 1B, H340 Repr. 1B, H360FD Skin Sens. 1, H317 Aquatic Acute 1, H400	M acute = 10 M chronic = 10	
Октил-3(2H)изотиазолон, 2- 26530-20-1 247-761-7 01-2120768921-45	0,0015- < 0,01 % (15 ppm- < 100 ppm)	Acute Tox. 2, Inhalation, H330 Acute Tox. 3, Dermal, H311 Skin Corr. 1, H314 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Acute Tox. 3, Oral, H301 Aquatic Chronic 1, H410 Eye Dam. 1, H318	Skin Sens. 1A; H317; C >= 0,0015 % ===== M acute = 100 M chronic = 100 ===== dermal:ATE = 311 mg/kg oral:ATE = 125 mg/kg inhalation:ATE = 0,27 mg/l;dust/mist	
Смесь изотиазолинонов (C(M)IT/MIT (3:1)) 55965-84-9 01-2120764691-48	0,0015- < 0,005 % (15 ppm- < 50 ppm)	Aquatic Chronic 1, H410 Skin Corr. 1C, H314 Acute Tox. 2, Dermal, H310 Acute Tox. 3, Oral, H301 Eye Dam. 1, H318 Acute Tox. 2, Inhalation, H330 Aquatic Acute 1, H400 Skin Sens. 1A, H317	Skin Irrit. 2; H315; C 0,06 - < 0,6 % Skin Corr. 1C; H314; C >= 0,6 % Eye Irrit. 2; H319; C 0,06 - < 0,6 % Eye Dam. 1; H318; C >= 0,6 % Skin Sens. 1A; H317; C >= 0,0015 % ===== M acute = 100	

			M chronic = 100	
--	--	--	-----------------	--

**For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.**

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

In case of adverse health effects seek medical advice.

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing. If necessary, see a dermatologist.

Eye contact:

Immediately flush eyes with soft jet of water or eye rinse solution for at least 5 minutes. If pains remain (intensive smarting, sensitivity to light, visual disturbance) continue flushing and contact/seek doctor or hospital.

Ingestion:

Rinse mouth and throat. Drink 1-2 glasses of water. Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

carbon dioxide, foam, powder, water spray jet, fine water spray

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO₂) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Wear protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment.

Danger of slipping on spilled product.

Avoid contact with skin and eyes.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Remove with liquid-absorbing material (sand, peat, sawdust).

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Avoid skin and eye contact.

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Temperatures between + 5 °C and + 30 °C.

Store in a cool, dry place.

Protect from freezing.

Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

7.3. Specific end use(s)

Paints and coatings

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Ukraine

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Limestone 1317-65-3 [Carbon dusts: coke from coal, pitch, oil, shale Silicate-containing dust, silicates, aluminosilicates: asbestos cement Carbon dusts: anthracite containing up to 5% free SiO ₂ Silicate-containing dust, silicates, aluminosilicates: concrete, olivine, apatite, fosterite, clay, kaolin fireclay]		6	Time Weighted Average (TWA):		UA OELA
Limestone 1317-65-3 [Silicate-containing dust, silicates, aluminosilicates: asbestos dust with asbestos content from 10% to 20%]		1	Short Term Exposure Limit (STEL):		UA OELA
Limestone 1317-65-3 [Carbon dusts: other mined coals and coal dusts containing up to 5% free SiO ₂ Silicate-containing dust, silicates, aluminosilicates: asbestos groceries, asbestos rubber]		10	Time Weighted Average (TWA):		UA OELA
Limestone 1317-65-3 [Silicate-containing dust, silicates, aluminosilicates: asbestos dust with asbestos content from 10% to 20% Silicate-containing dust, silicates, aluminosilicates: natural asbestos (chrysotile, anthophyllite, actinolite, tremolite, magnesium)]		2	Time Weighted Average (TWA):		UA OELA
Limestone 1317-65-3 [Silicate-containing dust, silicates, aluminosilicates: natural asbestos (chrysotile, anthophyllite, actinolite, tremolite, magnesium)]		0,5	Short Term Exposure Limit (STEL):		UA OELA
Limestone 1317-65-3 [Carbon dusts: carbon fiber materials based on polyacrylonitrile fibers Carbon dusts: carbon fiber materials based on cellulose hydrate fibers]		2	Short Term Exposure Limit (STEL):		UA OELA
Limestone 1317-65-3 [Carbon dusts: carbon fiber materials based on polyacrylonitrile fibers Carbon dusts: carbon fiber materials based on cellulose hydrate fibers]			Skin designation:	Chemical is dangerous when exposed to the skin and the mucous membrane of the eyes	UA OELA
Limestone 1317-65-3 [Silicate-containing dust, silicates, aluminosilicates: asbestos cement Silicate-containing dust, silicates, aluminosilicates: asbestos groceries, asbestos rubber]		4	Short Term Exposure Limit (STEL):		UA OELA
Limestone 1317-65-3 [Carbon dusts: carbon fiber materials based on cellulose hydrate fibers Carbon dusts: carbon fiber materials based on polyacrylonitrile fibers]		4	Time Weighted Average (TWA):		UA OELA
Limestone		8	Time Weighted Average		UA OELA

1317-65-3 [Carbon dusts: natural and synthetic diamonds]			(TWA):		
Limestone 1317-65-3 [Silicate-containing dust, silicates, aluminosilicates: asbestos dust with asbestos content less than 10%]		2	Short Term Exposure Limit (STEL):		UA OELA
Limestone 1317-65-3 [Carbon dusts: other mined coals and coal dusts containing from 5 to 10% free SiO ₂ Carbon dusts: black industrial soot containing <35 mg benz(a)pyrene per kg Silicate-containing dust, silicates, aluminosilicates: vitreous silicates of volcanic origin (tuff, pumice, perlite) Silicate-containing dust, silicates, aluminosilicates: asbestos dust with asbestos content less than 10% Silicate-containing dust, silicates, aluminosilicates: mica (flagopit, muscovite), talc, talc dust (natural mixtures of talc with tr Carbon dust: metallized diamond)]		4	Time Weighted Average (TWA):		UA OELA
Titanium dioxide 13463-67-7 [Titanium and its dioxide]		10	Time Weighted Average (TWA):		UA OELA
Chromium (III) oxide 1308-38-9 [CHROMIUM METAL, INORGANIC CHROMIUM(II) COMPOUNDS AND INORGANIC CHROMIUM(III) COMPOUNDS (INSOLUBLE)]		2	Time Weighted Average (TWA):	Indicative	ECLTV
Chromium (III) oxide 1308-38-9 [Chromium (III) oxide]		1	Time Weighted Average (TWA):		UA OELA
Diiron trioxide 1309-37-1 [Diiron trioxide]		6	Time Weighted Average (TWA):		UA OELA
Propane-1,2-diol 57-55-6 [Propane-1,2-diol]		7	Time Weighted Average (TWA):		UA OELA
Carbendazim 10605-21-7 [Methyl-1H-benzimidazol-2-ylcarbamate]		0,1	Time Weighted Average (TWA):		UA OELA

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Chromium (III) oxide 1308-38-9	Soil				3,2 mg/kg		
Chromium (III) oxide 1308-38-9	sewage treatment plant (STP)		10 mg/l				
Chromium (III) oxide 1308-38-9	sediment (marine water)				1,31 mg/kg		
Chromium (III) oxide 1308-38-9	aqua (marine water)		0,0047 mg/l				
Chromium (III) oxide 1308-38-9	aqua (intermittent releases)		0,0047 mg/l				
Chromium (III) oxide 1308-38-9	sediment (freshwater)				18,2 mg/kg		
Chromium (III) oxide 1308-38-9	aqua (freshwater)		0,0047 mg/l				
Amines, N-(C16-18 and C18-unsatd. alkyl)trimethylene, di- 1219010-04-4	aqua (freshwater)		0,010 mg/l				
Amines, N-(C16-18 and C18-unsatd. alkyl)trimethylene, di- 1219010-04-4	aqua (marine water)		0,001 mg/l				
Amines, N-(C16-18 and C18-unsatd. alkyl)trimethylene, di- 1219010-04-4	aqua (intermittent releases)		0,00148 mg/l				
Amines, N-(C16-18 and C18-unsatd. alkyl)trimethylene, di- 1219010-04-4	sewage treatment plant (STP)		0,251 mg/l				
Amines, N-(C16-18 and C18-unsatd. alkyl)trimethylene, di- 1219010-04-4	sediment (freshwater)				1,72 mg/kg		
Amines, N-(C16-18 and C18-unsatd. alkyl)trimethylene, di- 1219010-04-4	sediment (marine water)				0,172 mg/kg		
Amines, N-(C16-18 and C18-unsatd. alkyl)trimethylene, di- 1219010-04-4	Soil				10 mg/kg		
Amines, C16-18 and C16-18-unsatd. alkyl 1213789-63-9	aqua (freshwater)		0,00026 mg/l				
Amines, C16-18 and C16-18-unsatd. alkyl 1213789-63-9	Soil				10 mg/kg		
Amines, C16-18 and C16-18-unsatd. alkyl 1213789-63-9	sewage treatment plant (STP)		0,550 mg/l				
Amines, C16-18 and C16-18-unsatd. alkyl 1213789-63-9	sediment (freshwater)				3,76 mg/kg		
Amines, C16-18 and C16-18-unsatd. alkyl 1213789-63-9	sediment (marine water)				0,376 mg/kg		
Amines, C16-18 and C16-18-unsatd. alkyl 1213789-63-9	aqua (marine water)		0,000026 mg/l				
diuron 330-54-1	sewage treatment plant (STP)		58 mg/l				
diuron 330-54-1	aqua (freshwater)		0,00032 mg/l				
diuron 330-54-1	sediment (freshwater)				0,05172 mg/kg		
diuron 330-54-1	Soil				0,012 mg/kg		
diuron 330-54-1	aqua (marine water)		0,000032 mg/l				
diuron 330-54-1	sediment (marine water)				0,005172 mg/kg		
2-Octyl-2H-isothiazol-3-one 26530-20-1	sediment (freshwater)				0,0475 mg/kg		
2-Octyl-2H-isothiazol-3-one 26530-20-1	sediment (marine water)				0,00475 mg/kg		
2-Octyl-2H-isothiazol-3-one 26530-20-1	aqua (freshwater)		0,0022 mg/l				
2-Octyl-2H-isothiazol-3-one	aqua		0,0012				

26530-20-1	(intermittent releases)		mg/l				
2-Octyl-2H-isothiazol-3-one 26530-20-1	aqua (marine water)		0,00022 mg/l				
2-Octyl-2H-isothiazol-3-one 26530-20-1	Soil				0,0082 mg/kg		
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone (3:1) 55965-84-9	aqua (freshwater)		0,00339 mg/l				
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone (3:1) 55965-84-9	aqua (marine water)		0,00339 mg/l				
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone (3:1) 55965-84-9	sewage treatment plant (STP)		0,23 mg/l				
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone (3:1) 55965-84-9	sediment (freshwater)				0,027 mg/kg		
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone (3:1) 55965-84-9	sediment (marine water)				0,027 mg/kg		
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone (3:1) 55965-84-9	Soil				0,01 mg/kg		
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone (3:1) 55965-84-9	Freshwater - intermittent		0,00339 mg/l				
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone (3:1) 55965-84-9	Marine water - intermittent		0,00339 mg/l				

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Titanium dioxide 13463-67-7	Workers	inhalation	Long term exposure - local effects		0,17 mg/m ³	
Titanium dioxide 13463-67-7	General population	inhalation	Long term exposure - local effects		0,028 mg/m ³	
Chromium (III) oxide 1308-38-9	Workers	Inhalation	Acute/short term exposure - local effects		2 mg/m ³	
Chromium (III) oxide 1308-38-9	Workers	Inhalation	Long term exposure - local effects		0,5 mg/m ³	
Chromium (III) oxide 1308-38-9	General population	Inhalation	Long term exposure - local effects		0,5 mg/m ³	
Amines, N-(C16-18 and C18-unsatd. alkyl)trimethylene, di- 1219010-04-4	Workers	inhalation	Long term exposure - systemic effects		0,035 mg/m ³	
Amines, N-(C16-18 and C18-unsatd. alkyl)trimethylene, di- 1219010-04-4	Workers	dermal	Long term exposure - systemic effects		0,01 mg/kg	
Amines, C16-18 and C16-18-unsatd. alkyl 1213789-63-9	Workers	Inhalation	Long term exposure - systemic effects		0,38 mg/m ³	
Amines, C16-18 and C16-18-unsatd. alkyl 1213789-63-9	Workers	inhalation	Long term exposure - local effects		1 mg/m ³	
Amines, C16-18 and C16-18-unsatd. alkyl 1213789-63-9	Workers	inhalation	Acute/short term exposure - local effects		1 mg/m ³	
Amines, C16-18 and C16-18-unsatd. alkyl 1213789-63-9	General population	inhalation	Long term exposure - systemic effects		0,035 mg/m ³	
Amines, C16-18 and C16-18-unsatd. alkyl 1213789-63-9	General population	oral	Long term exposure - systemic effects		40 µg/kg	
diuron 330-54-1	Workers	inhalation	Long term exposure - systemic effects		0,17 mg/m ³	
diuron 330-54-1	Workers	dermal	Long term exposure - systemic effects		5,79 mg/kg	
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone (3:1) 55965-84-9	Workers	inhalation	Long term exposure - local effects		0,02 mg/m ³	
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone (3:1) 55965-84-9	Workers	inhalation	Acute/short term exposure - local effects		0,04 mg/m ³	
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone (3:1) 55965-84-9	General population	inhalation	Long term exposure - local effects		0,02 mg/m ³	
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone (3:1) 55965-84-9	General population	inhalation	Acute/short term exposure - local effects		0,04 mg/m ³	
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone (3:1) 55965-84-9	General population	oral	Long term exposure - systemic effects		0,09 mg/kg	
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone (3:1) 55965-84-9	General population	oral	Acute/short term exposure - systemic effects		0,11 mg/kg	

Biological Exposure Indices:

None

8.2. Exposure controls:

Respiratory protection:

Suitable breathing mask when there is inadequate ventilation.

Combination filter: ABEKP (EN 14387)

This recommendation should be matched to local conditions.

Hand protection:

In the case of longer contact protective gloves made from nitrile rubber are recommended according to EN 374. material thickness > 0.1 mm

Perforation time > 10 minutes

In the case of longer and repeated contact please note that in practice the penetration times may be considerably shorter than those determined according to EN 374. The protective gloves must always be checked for their suitability for use at the specific workplace (e.g. mechanical and thermal stress, product compatibility, antistatic effects, etc.). The gloves must be replaced immediately at the first signs of wear and tear. The information provided by the manufacturers and given in the relevant trade association regulations for industrial safety must always be observed. We recommend that a hand care plan is drawn up in cooperation with a glove manufacturer and the trade association in accordance with the local operating conditions.

Eye protection:

Goggles which can be tightly sealed.

Protective eye equipment should conform to EN166.

Skin protection:

Suitable protective clothing

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Delivery form	dispersion
Colour	colored
Odor	characteristic
Physical state	liquid
Melting point	Currently under determination
Initial boiling point	Currently under determination
Flammability	Currently under determination
Explosive limits	Currently under determination
Flash point	Currently under determination
Auto-ignition temperature	Currently under determination
Decomposition temperature	Currently under determination
pH	Currently under determination
Viscosity (kinematic)	Currently under determination
Viscosity, dynamic (; 40 °C (104 °F))	13.000 - 18.000 mPa.s no method / method unknown
Solubility (qualitative)	Currently under determination
Partition coefficient: n-octanol/water	Currently under determination
Vapour pressure	Currently under determination
Density (20 °C (68 °F))	1,4 - 1,6 g/cm ³ no method / method unknown
Relative vapour density:	Currently under determination
Particle characteristics	Currently under determination

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

Reaction with acids: production of heat and carbon dioxide.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

None if used for intended purpose.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

None known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Titanium dioxide 13463-67-7	LD50	> 5.000 mg/kg	rat	OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)
Chromium (III) oxide 1308-38-9	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatic 64742-48-9	LD50	> 15.000 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Amines, N-(C16-18 and C18-unsatd. alkyl)trimethylene, di- 1219010-04-4	LD50	500 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
Amines, C16-18 and C16- 18-unsatd. alkyl 1213789-63-9	LD50	1.689 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
diuron 330-54-1	LD50	1.000 - 1.017 mg/kg	rat	not specified
diuron 330-54-1	Acute toxicity estimate (ATE)	1.000 mg/kg		Expert judgement
Carbendazim 10605-21-7	LD50	6.400 mg/kg	rat	not specified
2-Octyl-2H-isothiazol-3- one 26530-20-1	Acute toxicity estimate (ATE)	125 mg/kg		Expert judgement
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	LD50	66 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Titanium dioxide 13463-67-7	LD50	> 10.000 mg/kg	rabbit	not specified
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatic 64742-48-9	LD50	> 5.000 mg/kg	rabbit	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
Amines, C16-18 and C16- 18-unsatd. alkyl 1213789-63-9	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
diuron 330-54-1	LD50	> 5.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Carbendazim 10605-21-7	LD50	> 2.000 mg/kg	rabbit	not specified
2-Octyl-2H-isothiazol-3- one 26530-20-1	Acute toxicity estimate (ATE)	311 mg/kg		Expert judgement
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	LD50	87,12 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Titanium dioxide 13463-67-7	LC50	> 6,82 mg/l	dust	4 h	rat	not specified
Chromium (III) oxide 1308-38-9	LC50	> 5,41 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatic 64742-48-9	LC50	> 5,6 mg/l	dust/mist	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
diuron 330-54-1	LC50	> 5,05 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
diuron 330-54-1	Acute toxicity estimate (ATE)	5,051 mg/l	dust/mist			Expert judgement
2-Octyl-2H-isothiazol-3-one 26530-20-1	Acute toxicity estimate (ATE)	0,27 mg/l	dust/mist	4 h		Expert judgement
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	LC50	0,171 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Titanium dioxide 13463-67-7	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Chromium (III) oxide 1308-38-9	not irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatic 64742-48-9	mildly irritating	4 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Amines, N-(C16-18 and C18-unsatd. alkyl)trimethylene, di- 1219010-04-4	corrosive	1 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Amines, C16-18 and C16-18-unsatd. alkyl 1213789-63-9	corrosive	1 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
diuron 330-54-1	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	corrosive	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Titanium dioxide 13463-67-7	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Chromium (III) oxide 1308-38-9	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
diuron 330-54-1	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	Category 1 (irreversible effects on the eye)		rabbit	not specified

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Titanium dioxide 13463-67-7	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Titanium dioxide 13463-67-7	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Chromium (III) oxide 1308-38-9	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
diuron 330-54-1	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
2-Octyl-2H-isothiazol-3- one 26530-20-1	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	sensitising	Mouse local lymphnode assay (LLNA)	mouse	not specified

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Titanium dioxide 13463-67-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Titanium dioxide 13463-67-7	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Titanium dioxide 13463-67-7	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Titanium dioxide 13463-67-7	negative	in vitro mammalian cell micronucleus test	without		equivalent or similar to OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
Chromium (III) oxide 1308-38-9	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
diuron 330-54-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
diuron 330-54-1	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
diuron 330-54-1		in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	ambiguous	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	positive	in vitro mammalian chromosome aberration test	with and without		EPA OPP 84-2 (Mutagenicity Testing)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	positive	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	negative	DNA damage and repair assay, unscheduled DNA synthesis in mammalian cells in vitro	not applicable		OECD Guideline 482 (Genetic Toxicology: DNA Damage and Repair, Unscheduled DNA Synthesis in Mammalian Cells In Vitro)
Titanium dioxide 13463-67-7	negative	oral: gavage		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Chromium (III) oxide 1308-38-9	negative	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	negative	oral: gavage		mouse	OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	negative	oral: feed		Drosophila melanogaster	OECD Guideline 477 (Genetic Toxicology: Sex-linked Recessive Lethal Test in Drosophila melanogaster)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	negative	oral: gavage		rat	OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	negative	oral: gavage		rat	EPA OPP 84-2 (Mutagenicity Testing)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Titanium dioxide 13463-67-7	not carcinogenic	oral: feed	103 w daily	rat	male/female	not specified
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	not carcinogenic	oral: drinking water	2 y daily	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Titanium dioxide 13463-67-7	NOAEL P >= 1.000 mg/kg NOAEL F1 >= 1.000 mg/kg	one- generation study	oral: feed	rat	OECD Guideline 443 (Extended One-Generation Reproductive Toxicity Study)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	NOAEL P 30 ppm NOAEL F1 300 ppm NOAEL F2 300 ppm	Two generation study	oral: drinking water	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)

STOT-single exposure:

No data available.

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Titanium dioxide 13463-67-7	NOAEL > 1.000 mg/kg	oral: gavage	92 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Chromium (III) oxide 1308-38-9	NOAEL > 2.000 mg/kg	oral: feed	90 d 5 d/w	rat	not specified
Amines, N-(C16-18 and C18-unsatd. alkyl)trimethylene, di- 1219010-04-4	NOAEL 0,4 mg/kg	oral: gavage	90-91 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	NOAEL 16,3 mg/kg	oral: drinking water	90 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	NOAEL 0.34 mg/m3	inhalation: aerosol	90 d 6 h/d, 5 d/w	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	NOAEL 2,625 mg/kg	dermal	90 d 6 h/d	rat	EPA OPP 82-3 (Subchronic Dermal Toxicity 90 Days)

Aspiration hazard:

The mixture is classified based on Viscosity data.

Hazardous substances CAS-No.	Viscosity (kinematic) Value	Temperature	Method	Remarks
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatic 64742-48-9	1,13 mm ² /s	40 °C	not specified	
Amines, C16-18 and C16- 18-unsatd. alkyl 1213789-63-9	5,25 mm ² /s	40 °C		

SECTION 12: Ecological information

General ecological information:

Do not empty into drains, soil or bodies of water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Titanium dioxide 13463-67-7	LC50	Toxicity > Water solubility	48 h	Leuciscus idus	OECD Guideline 203 (Fish, Acute Toxicity Test)
Chromium (III) oxide 1308-38-9	LC50	Toxicity > Water solubility	96 h	Brachydanio rerio (new name: Danio rerio)	ISO 7346-1 (Determination of the Acute Lethal Toxicity of Substances to a Freshwater Fish [Brachydanio rerio Hamilton-Buchanan (Teleostei, Cyprinidae)])
Chromium (III) oxide 1308-38-9	NOEC	Toxicity > Water solubility	30 d	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 210 (fish early lite stage toxicity test)
Hydrocarbons, C10-C13, n- alkanes, isoalkanes, cyclics, < 2% aromatic 64742-48-9	LL50	> 1.000 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Amines, N-(C16-18 and C18- unsatd. alkyl)trimethylene, di- 1219010-04-4	LC50	0,148 mg/l	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Amines, C16-18 and C16-18- unsatd. alkyl 1213789-63-9	LC50	0,06 mg/l	96 h	Pimephales promelas	EPA OPPTS 850.1085 (Fish Acute Toxicity Test mitigated by humic acid)
diuron 330-54-1	NOEC	4,2 mg/l	7 d	Pimephales promelas	OECD Guideline 204 (Fish, Prolonged Toxicity Test: 14-day Study)
diuron 330-54-1	LC50	6,6 mg/l	96 h	Leuciscus idus melanotus	OECD Guideline 203 (Fish, Acute Toxicity Test)
Carbendazim 10605-21-7	LC50	> 10 mg/l	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
2-Octyl-2H-isothiazol-3-one 26530-20-1	LC50	0,036 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
2-Octyl-2H-isothiazol-3-one 26530-20-1	NOEC	0,022 mg/l	21 d	Oncorhynchus mykiss	OECD Guideline 210 (fish early lite stage toxicity test)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	LC50	0,22 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	NOEC	0,098 mg/l	28 d	Oncorhynchus mykiss	OECD Guideline 210 (fish early lite stage toxicity test)

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Titanium dioxide 13463-67-7	EC50	Toxicity > Water solubility	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Chromium (III) oxide 1308-38-9	LC50	Toxicity > Water solubility	48 h	Ceriodaphnia dubia	other guideline:
Hydrocarbons, C10-C13, n- alkanes, isoalkanes, cyclics, < 2% aromatic 64742-48-9	EL50	> 1.000 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Amines, N-(C16-18 and C18- unsatd. alkyl)trimethylene, di- 1219010-04-4	EC50	> 0,01 - 0,1 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Amines, C16-18 and C16-18- unsatd. alkyl 1213789-63-9	EC50	0,98 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
diuron	EC50	1,4 mg/l	48 h	Daphnia magna	OECD Guideline 202

330-54-1					(Daphnia sp. Acute Immobilisation Test)
Carbendazim 10605-21-7	EC50	0,16 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
2-Octyl-2H-isothiazol-3-one 26530-20-1	EC50	0,42 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	EC50	0,12 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Titanium dioxide 13463-67-7	NOEC	Toxicity > Water solubility	21 d	Daphnia magna	OECD Guideline 202 (Daphnia sp. Chronic Immobilisation Test)
Chromium (III) oxide 1308-38-9	NOEC	Toxicity > Water solubility	21 d	Daphnia magna	other guideline:
Amines, N-(C16-18 and C18- unsatd. alkyl)trimethylene, di- 1219010-04-4	NOEC	> 0,001 - 0,01 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Amines, C16-18 and C16-18- unsatd. alkyl 1213789-63-9	NOEC	0,013 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
2-Octyl-2H-isothiazol-3-one 26530-20-1	NOEC	0,0016 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	NOEC	0,0036 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Titanium dioxide 13463-67-7	EC50	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Titanium dioxide 13463-67-7	NOEC	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Chromium (III) oxide 1308-38-9	EC50	Toxicity > Water solubility	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Chromium (III) oxide 1308-38-9	EC10	Toxicity > Water solubility	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatic 64742-48-9	EL50	> 1.000 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatic 64742-48-9	NOELR	1.000 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Amines, N-(C16-18 and C18-unsatd. alkyl)trimethylene, di- 1219010-04-4	EC50	0,507 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Amines, C16-18 and C16-18-unsatd. alkyl 1213789-63-9	EC50	0,46 mg/l	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Amines, C16-18 and C16-18-unsatd. alkyl 1213789-63-9	NOEC	0,15 mg/l	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
diuron 330-54-1	NOEC	0,0032 mg/l	96 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
diuron 330-54-1	EC50	0,022 mg/l	96 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Carbendazim 10605-21-7	NOEC	1 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Carbendazim 10605-21-7	EC50	23 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-Octyl-2H-isothiazol-3-one 26530-20-1	EC50	0,00129 mg/l	48 h	Navicula pelliculosa	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-Octyl-2H-isothiazol-3-one 26530-20-1	EC10	0,000224 mg/l	48 h	Navicula pelliculosa	OECD Guideline 201 (Alga, Growth Inhibition Test)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	EC50	0,0052 mg/l	72 h	Skeletonema costatum	OECD Guideline 201 (Alga, Growth Inhibition Test)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	NOEC	0,00064 mg/l	48 h	Skeletonema costatum	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Titanium dioxide 13463-67-7	EC0	Toxicity > Water solubility	24 h	Pseudomonas fluorescens	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-Test)
diuron 330-54-1	EC 50	> 10.000 mg/l			OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Carbendazim 10605-21-7	EC20	> 1.000 mg/l	30 min	not specified	DIN 38412, part 27 (Bacterial oxygen consumption test)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	EC20	0,97 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatic 64742-48-9	readily biodegradable	aerobic	80 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Amines, N-(C16-18 and C18-unsatd. alkyl)trimethylene, di- 1219010-04-4	readily biodegradable	aerobic	66 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Amines, C16-18 and C16-18-unsatd. alkyl 1213789-63-9	readily biodegradable	aerobic	66 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
diuron 330-54-1		aerobic	0 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Carbendazim 10605-21-7	not readily biodegradable.	aerobic	22 - 42 %	21 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Carbendazim 10605-21-7	not inherently biodegradable	aerobic	< 10 %	21 d	OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test)
2-Octyl-2H-isothiazol-3-one 26530-20-1	not readily biodegradable.	aerobic	35 %	21 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	inherently biodegradable	aerobic	100 %	28 d	OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	readily biodegradable	aerobic	> 60 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

12.3. Bioaccumulative potential

Hazardous substances CAS-No.	Bioconcentration factor (BCF)	Exposure time	Temperature	Species	Method
Amines, C16-18 and C16-18-unsatd. alkyl 1213789-63-9	173			calculation	not specified
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	3,6			calculation	QSAR (Quantitative Structure Activity Relationship)

12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
Chromium (III) oxide 1308-38-9	2,97		not specified
Amines, N-(C16-18 and C18-unsatd. alkyl)trimethylene, di- 1219010-04-4	1,46	25,7 °C	OECD Guideline 123 (Partition Coefficient (1-Octanol / Water), Slow-Stirring Method)
Amines, C16-18 and C16-18-unsatd. alkyl 1213789-63-9	8,35	20 °C	EU Method A.8 (Partition Coefficient)
diuron 330-54-1	2,84	20 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Carbendazim 10605-21-7	1,6		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
2-Octyl-2H-isothiazol-3-one 26530-20-1	2,9		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	> -0,71 - 0,75	20 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
Titanium dioxide 13463-67-7	According to Annex XIII to Regulation (EC) No 1907/2006, a PBT and vPvB assessment shall not be conducted for inorganic substances.
Chromium (III) oxide 1308-38-9	According to Annex XIII to Regulation (EC) No 1907/2006, a PBT and vPvB assessment shall not be conducted for inorganic substances.
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatic 64742-48-9	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Amines, N-(C16-18 and C18-unsatd. alkyl)trimethylene, di- 1219010-04-4	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Amines, C16-18 and C16-18-unsatd. alkyl 1213789-63-9	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
diuron 330-54-1	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Carbendazim 10605-21-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
2-Octyl-2H-isothiazol-3-one 26530-20-1	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

Waste code

080119

SECTION 14: Transport information

- 14.1. UN number or ID number**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.2. UN proper shipping name**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.3. Transport hazard class(es)**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.4. Packing group**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.5. Environmental hazards**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.6. Special precautions for user**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.7. Maritime transport in bulk according to IMO instruments**
not applicable

SECTION 15: Regulatory information

No information available:

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**15.2. Chemical safety assessment**

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H310 Fatal in contact with skin.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H330 Fatal if inhaled.
- H335 May cause respiratory irritation.
- H340 May cause genetic defects.
- H351 Suspected of causing cancer.
- H360FD May damage fertility. May damage the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.

- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Product is intended for professional use.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.