

Safety Data Sheet



Revision Number: 006.0

Issue date: 02/26/2025

1. IDENTIFICATION

Product name: Loctite Polyseamseal Tub & Tile Sealant
Product type/Recommended use: Sealant
Restriction of Use: None identified
Company address: Henkel Corporation
One Henkel Way
Rocky Hill, Connecticut 06067

IDH number: 2154752

Region: United States

Contact information:
Telephone: +1 (860) 571-5100
MEDICAL EMERGENCY Phone: Poison Control Center
1-877-671-4608 (toll free) or 1-303-592-1711
TRANSPORT EMERGENCY Phone: CHEMTREC
1-800-424-9300 (toll free) or 1-703-527-3887
MEDICAL EMERGENCY Phone: Poison Control Center
1-877-671-4608 (toll free) or 1-303-592-1711
TRANSPORT EMERGENCY Phone: CHEMTREC
1-800-424-9300 (toll free) or 1-703-527-3887
Internet: www.henkelna.com

This product contains one or more components regulated under a Significant New Use Rule (SNUR) by the US EPA. See Section 15 for more information.

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING: H319 - CAUSES SERIOUS EYE IRRITATION.
H373 - MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

HAZARD CLASS	HAZARD CATEGORY
EYE IRRITATION	2A
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	2

PICTOGRAM(S)



Precautionary Statements

Prevention: P260 - Do not breathe dust.
P264 - Wash affected area thoroughly after handling.
P280 - Wear eye and face protection.

Response: P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314 - Get medical attention if you feel unwell.
P337+P313 - If eye irritation persists: Get medical attention.

Storage: Not prescribed

Disposal: P501 - Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Other hazards Not available.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*
Limestone	1317-65-3	10 - 30
Ethylene glycol	107-21-1	1 - 5
Titanium dioxide < 1% particles with diameter ≤ 10 µm	13463-67-7	1 - 5
Palygorskite ([Mg(Al _{0.5} -1Fe _{0-0.5})]Si ₄ (OH)O ₁₀ .4H ₂ O)	12174-11-7	0.1 - 1
Quartz (SiO ₂), <1% respirable	14808-60-7	0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

First Aid Measures by likely routes of exposure

Inhalation:	Move to fresh air. If symptoms persist, seek medical advice.
Skin contact:	Wash affected area immediately with soap and water. If symptoms develop and persist, get medical attention.
Eye contact:	In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention.
Ingestion:	Rinse out mouth. Do not drink. Never give anything by mouth to an unconscious person. If adverse health effects develop seek medical attention.
Most important symptoms and effects (acute and delayed):	The most important known symptoms and effects, both acute and delayed, are described in Section 11: Toxicological Information.
Indication of any immediate medical attention / special treatment needed:	Not available.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Improper extinguishing agents:	Not available.
Special firefighting procedures:	Water may be unsuitable as an extinguishing media, but may be helpful in keeping adjacent containers cool.
Unusual fire or explosion hazards:	This product is an aqueous mixture which will not burn. If evaporated to dryness, the solid residue may pose a slight fire hazard.
Hazardous combustion products:	Carbon dioxide Carbon monoxide. Oxides of nitrogen. Oxides of hydrocarbons.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Ventilate area. Do not allow product to enter sewer or waterways.
Clean-up methods:	Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Absorb spill with inert material. Shovel material into appropriate container for disposal. Wear appropriate protective equipment and clothing during clean-up.

7. HANDLING AND STORAGE

Handling: Avoid contact with eyes. Avoid prolonged or repeated skin contact with this material. Use only with adequate ventilation. Wash hands before breaks and immediately after handling the product. Keep out of the reach of children.

Storage: Keep from freezing.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Limestone	10 mg/m3 TWA Inhalable particles. 3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Total dust.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 5 mg/m3 TWA Respirable fraction. 50 MPPCF TWA Total dust. 15 mg/m3 TWA Total dust. 15 MPPCF TWA Respirable fraction.	None	None
Ethylene glycol	25 ppm TWA Vapor fraction 50 ppm STEL Vapor fraction 10 mg/m3 STEL Aerosol, inhalable.	None	None	None
Titanium dioxide < 1% particles with diameter ≤ 10 μm	0.2 mg/m3 TWA Respirable nanoscale particles 2.5 mg/m3 TWA Respirable finescale particles	15 mg/m3 PEL Total dust. 5 mg/m3 TWA Respirable fraction. 50 MPPCF TWA Total dust. 15 mg/m3 TWA Total dust. 15 MPPCF TWA Respirable fraction.	None	None
Palygorskite ([Mg(Al _{0.5} -1Fe _{0-0.5})]Si ₄ (OH)O ₁₀ .4H ₂ O)	1 FIBERS/CM ³ TWA Fiber. 0.2 FIBERS/CM ³ TWA Fiber.	None	None	None
Quartz (SiO ₂), <1% respirable	0.025 mg/m3 TWA Respirable fraction.	0.05 mg/m3 TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m3 OSHA_ACT (Respirable dust.) 0.05 mg/m3 PEL Respirable dust. 2.4 MPPCF TWA Respirable 0.1 mg/m3 TWA Respirable	None	None

Engineering controls: Use local exhaust ventilation.

Respiratory protection: No personal respiratory protective equipment normally required.

Eye/face protection: None required in normal use.

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Solid
Color:	Light beige
Odor:	Acetate
Odor threshold:	Not available.
pH:	6.5 - 7.5
Vapor pressure:	17.5 mm hg (20 °C (68°F))
Boiling point/range:	> 100 °C (> 212°F)
Melting point/ range:	Not available.
Density/Relative density:	1.3
Relative vapor density:	Heavier than air, (Air = 1)
Flash point:	Product is a solid. (ASTM D 4359)
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	0.3 (Butyl acetate = 1)
Solubility:	Soluble
Partition coefficient n-octanol/water (logarithmic value):	Not available.
VOC content:	1.16 %; 143 g/l (by weight, calculated using CARB method; g/L less water, less exempts calculated using SCAQMD method)
Dynamic viscosity:	360,000 - 520,000 cp
Kinematic viscosity:	Not available.
Particle characteristics:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Carbon dioxide. Carbon monoxide. Oxides of nitrogen. Hydrocarbons.
Incompatible materials:	None expected.
Reactivity:	Not available.
Conditions to avoid:	None known

11. TOXICOLOGICAL INFORMATION

Likely routes of exposure:	Skin, Inhalation, Eyes, Ingestion
-----------------------------------	-----------------------------------

Potential Health Effects/Symptoms

Inhalation:	Abrasion of cured material such as by sanding or grinding could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of this product causes no such release. May cause respiratory tract irritation.
Skin contact:	May cause skin irritation.
Eye contact:	Causes serious eye irritation.
Ingestion:	Not expected under normal conditions of use. May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s
Limestone	None
Ethylene glycol	Oral LD50 (Rat) = 5.89 g/kg Oral LD50 (Mouse) = 14.6 g/kg Dermal LD50 (Rabbit) = 9,530 mg/kg
Titanium dioxide < 1% particles with diameter ≤ 10 µm	None
Palygorskite ([Mg(Al _{0.5} -1Fe _{0-0.5})]Si ₄ (OH)O ₁₀ .4H ₂ O)	None
Quartz (SiO ₂), <1% respirable	None

Hazardous Component(s)	Immediate Health Effects	Delayed Health Effects	Chronic Health Effects
Limestone	Nuisance dust		
Ethylene glycol	Irritant		Blood Bone Marrow Central nervous system Developmental Eyes Kidney Liver Metabolic
Titanium dioxide < 1% particles with diameter ≤ 10 µm			
Palygorskite ([Mg(Al _{0.5} -1Fe _{0-0.5})]Si ₄ (OH)O ₁₀ .4H ₂ O)			
Quartz (SiO ₂), <1% respirable			Immune system Lung Some evidence of carcinogenicity

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Limestone	No	No	No
Ethylene glycol	No	No	No
Titanium dioxide < 1% particles with diameter ≤ 10 µm	No	Group 2B	No
Palygorskite ([Mg(Al _{0.5} -1Fe _{0-0.5})]Si ₄ (OH)O ₁₀ .4H ₂ O)	Reasonably Anticipated to be a Human Carcinogen.	Group 2B	No
Quartz (SiO ₂), <1% respirable	Known To Be Human Carcinogen.	Group 1	Yes

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.

TSCA 5(a) SNUR: This product contains the following component(s) subject to a Significant New Use Rule (SNUR) by the US EPA: Mercury (CAS # 7439-97-6). The SNUR is codified at Section number: 40 CFR 721.10068

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis.
CERCLA/SARA Section 311/312: Please refer to the GHS classification in Section 2
CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Ethylene glycol (CAS# 107-21-1).

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: This Safety Data Sheet contains changes from the previous version in Section(s): 3, 8, 11

Prepared by: Product Safety and Regulatory Affairs

Issue date: 02/26/2025

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.