



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 17

POLYPOXY FC RAL 7035 PART A

SDS No. : 655092
V003.0

Revision: 05.11.2024
printing date: 09.02.2026

Replaces version from: 08.08.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

POLYPOXY FC RAL 7035 PART A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

2-Component coating

1.3. Details of the supplier of the safety data sheet

Henkel Jebal Ali FZCO
PO Box 61341 - Jebel Ali
Dubai

Utd.Arab.Emir.

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website www.mysds.henkel.com or www.henkel-adhesives.com.

1.4. Emergency telephone number

HAAD Poison and Drug Information Center UAE, TOLL FREE TEL. NUMBER 800-424

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin irritation Category 2

H315 Causes skin irritation.

Skin sensitizer Category 1

H317 May cause an allergic skin reaction.

Serious eye irritation Category 2

H319 Causes serious eye irritation.

Toxic to reproduction Category 1B

H360F May damage fertility.

Chronic hazards to the aquatic environment Category 2

H411 Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

Signal word:	Danger
Hazard statement:	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H360F May damage fertility. H411 Toxic to aquatic life with long lasting effects.
Supplemental information	Restricted to professional users.
Precautionary statement: Prevention	P261 Avoid breathing mist/vapours. P273 Avoid release to the environment. P280 Wear protective gloves/eye protection.
Precautionary statement: Response	P302+P352 IF ON SKIN: Wash with plenty of soap and water. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 IF exposed or concerned: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.
Precautionary statement: Storage	P405 Store locked up.
Precautionary statement: Disposal	P501 Dispose of contents/container in accordance with national regulation.

2.3. Other hazards

None if used properly.

Following substances are present in a concentration \geq the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration \geq the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number	content	Classification
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 25068-38-6		20- < 40 %	Eye Irrit. 2 H319 Aquatic Chronic 2 H411 Skin Sens. 1 H317 Skin Irrit. 2 H315
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	271-846-8	5- < 10 %	Skin Irrit. 2 H315 Skin Sens. 1 H317 Repr. 1B H360F

For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures**General information:**

In case of adverse health effects seek medical advice.

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap. Skin care. Remove contaminated clothes immediately.

Eye contact:

Immediately flush eyes with soft jet of water or eye rinse solution for at least 5 minutes. If pains remain (intensive smarting, sensitivity to light, visual disturbance) continue flushing and contact/seek doctor or hospital.

Ingestion:

Rinse mouth and throat. Drink 1-2 glasses of water. Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

Causes serious eye irritation.

SKIN: Redness, inflammation.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media**Suitable extinguishing media:**

carbon dioxide, foam, powder, water spray jet, fine water spray

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO₂) can be released.

5.3. Advice for firefighters

- Wear protective equipment.
- Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- Wear protective equipment.
- Avoid contact with skin and eyes.
- Ensure adequate ventilation.
- Danger of slipping on spilled product.

6.2. Environmental precautions

- Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

- Remove with liquid-absorbing material (sand, peat, sawdust).
- Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

- See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Ensure that workrooms are adequately ventilated.
- Avoid skin and eye contact.

Hygiene measures:

- Do not eat, drink or smoke while working.
- Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities

- Avoid contact with air.
- Avoid moisture.
- Close the container carefully after use and store it at a good ventilated place.
- Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

7.3. Specific end use(s)

- 2-Component coating

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Utd.Arab.Emir.

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Talc (Mg ₃ H ₂ (SiO ₃) ₄) 14807-96-6 [TALC, CONTAINING NO ASBESTOS FIBERS, RESPIRABLE FRACTION]		2	Time Weighted Average (TWA):		AD TLV
Talc (Mg ₃ H ₂ (SiO ₃) ₄) 14807-96-6 [TALC (CONTAINING NO ASBESTORS FIBERS)]		2	Time Weighted Average (TWA):		GCC TLV
Talc (Mg ₃ H ₂ (SiO ₃) ₄) 14807-96-6 [TALC (CONTAINING NO ASBESTOS FIBERS)]		2	Time Weighted Average (TWA):		UAE OEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE]		10	Time Weighted Average (TWA):		AD TLV
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE]		10	Time Weighted Average (TWA):		GCC TLV
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE]		10	Time Weighted Average (TWA):		UAE OEL

Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No.: 655092 V003.0

Page 6 of 17

Occupational Exposure Limits

Valid for
Bahrain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Talc (Mg ₃ H ₂ (SiO ₃) ₄) 14807-96-6 [TALC (CONTAINING NO ASBESTOS FIBERS)]		2	Time Weighted Average (TWA):		BH TLV
Talc (Mg ₃ H ₂ (SiO ₃) ₄) 14807-96-6 [TALC (CONTAINING NO ASBESTOS FIBERS)]		2	Time Weighted Average (TWA):		GCC TLV
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE]		10	Time Weighted Average (TWA):		BH TLV
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE]		10	Time Weighted Average (TWA):		GCC TLV

Occupational Exposure Limits

Valid for
Egypt

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Limestone 1317-65-3 [CALCIUM CARBONATE (INCLUDING LIMESTONE AND MARBLE), TOTAL DUST CONTAINING NO MORE THAN 1% CRYSTALLIZED SILICA AND NO ASBESTOS]		10	Time Weighted Average (TWA):		EG OEL
Talc (Mg ₃ H ₂ (SiO ₃) ₄) 14807-96-6 [TALC, NONFIBROUS]			Time Weighted Average (TWA):		EG OEL
Titanium dioxide 13463-67-7 [Titanium dioxide]		10	Time Weighted Average (TWA):		EG OEL

Occupational Exposure Limits

Valid for
Jordan

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Talc (Mg ₃ H ₂ (SiO ₃) ₄) 14807-96-6 [ASBESTOS: TALC, RESPIRABLE DUST]		2	Time Weighted Average (TWA):		JO TLV
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE]	450	560	Short Term Exposure Limit (STEL):		JO TLV
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE]	100	375	Time Weighted Average (TWA):		JO TLV

Occupational Exposure Limits

Valid for
Kuwait

Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No.: 655092 V003.0

Page 7 of 17

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Limestone 1317-65-3 [MARBLE (CALCIUM CARBONATE), TOTAL]		10	Time Weighted Average (TWA):		KW OEL
Limestone 1317-65-3 [MARBLE (CALCIUM CARBONATE), INHALED]		5	Time Weighted Average (TWA):		KW OEL
Limestone 1317-65-3 [MARBLE (CALCIUM CARBONATE), INHALED]			Harmful Concentration for risk to health and life:	Unknown	KW OEL
Limestone 1317-65-3 [MARBLE (CALCIUM CARBONATE), TOTAL]			Harmful Concentration for risk to health and life:	Unknown	KW OEL
Talc (Mg ₃ H ₂ (SiO ₃) ₄) 14807-96-6 [TALC (CONTAINING NO ASBESTOS FIBERS)]		2	Time Weighted Average (TWA):		GCC TLV
Talc (Mg ₃ H ₂ (SiO ₃) ₄) 14807-96-6 [TALC (NOT CONTAINING ASBESTOS FIBERS) INHALED]		2	Time Weighted Average (TWA):		KW OEL
Talc (Mg ₃ H ₂ (SiO ₃) ₄) 14807-96-6 [TALC (NOT CONTAINING ASBESTOS FIBERS) INHALED]		1.000	Harmful Concentration for risk to health and life:		KW OEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE]		10	Time Weighted Average (TWA):		GCC TLV
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE]		5.000	Harmful Concentration for risk to health and life:		KW OEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE]		10	Time Weighted Average (TWA):		KW OEL

Occupational Exposure Limits

Valid for
Israel

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Limestone 1317-65-3 [Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles]		10	Time Weighted Average (TWA):		IL OEL
Limestone 1317-65-3 [Particles (insoluble or poorly soluble) not otherwise specified, respirable particles]		3	Time Weighted Average (TWA):		IL OEL
Talc (Mg ₃ H ₂ (SiO ₃) ₄) 14807-96-6 [Talc, containing no asbestos fibers, respirable fraction]		2	Time Weighted Average (TWA):		IL OEL
Titanium dioxide 13463-67-7 [Titanium dioxide, finescale particles, respirable fraction]		2,5	Time Weighted Average (TWA):		IL OEL
Titanium dioxide 13463-67-7 [Titanium dioxide, nanoscale particles, respirable fraction]		0,2	Time Weighted Average (TWA):		IL OEL

Occupational Exposure Limits

Valid for
Kenya

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Limestone 1317-65-3 [MARBLE TOTAL INHALABLE DUST LIMESTONE TOTAL INHALABLE DUST CALCIUM CARBONATE TOTAL INHALABLE DUST]		10	Time-weighted average (TWA) OEL-RL:		KE OEL-RL
Limestone 1317-65-3 [MARBLE RESPIRABLE DUST CALCIUM CARBONATE RESPIRABLE DUST LIMESTONE RESPIRABLE DUST]		5	Time-weighted average (TWA) OEL-RL:		KE OEL-RL
Talc (Mg ₃ H ₂ (SiO ₃) ₄) 14807-96-6 [TALC TOTAL INHALABLE DUST]		10	Time-weighted average (TWA) OEL-RL:		KE OEL-RL
Talc (Mg ₃ H ₂ (SiO ₃) ₄) 14807-96-6 [TALC RESPIRABLE DUST]		1	Time-weighted average (TWA) OEL-RL:		KE OEL-RL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE TOTAL INHALABLE DUST]		10	Time-weighted average (TWA) OEL-RL:		KE OEL-RL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE RESPIRABLE DUST]		5	Time-weighted average (TWA) OEL-RL:		KE OEL-RL

Biological Exposure Indices:

None

8.2. Exposure controls:

Respiratory protection:

Suitable breathing mask when there is inadequate ventilation.
Combination filter: ABEKP (EN 14387)
This recommendation should be matched to local conditions.

Hand protection:

Recommended are gloves made from Nitril rubber (Material thickness >0,1 mm, Perforation time < 30s).Gloves should be replaced after each short time contact or contamination. Available at laboratory specialized trade or at pharmacies / chemist's shops.

In the case of longer contact protective gloves made from nitrile rubber are recommended according to EN 374.

material thickness > 0.4 mm

Perforation time > 30 minutes

In the case of longer and repeated contact please note that in practice the penetration times may be considerably shorter than those determined according to EN 374. The protective gloves must always be checked for their suitability for use at the specific workplace (e.g. mechanical and thermal stress, product compatibility, antistatic effects, etc.). The gloves must be replaced immediately at the first signs of wear and tear. The information provided by the manufacturers and given in the relevant trade association regulations for industrial safety must always be observed. We recommend that a hand care plan is drawn up in cooperation with a glove manufacturer and the trade association in accordance with the local operating conditions.

Eye protection:

Goggles which can be tightly sealed.
Protective eye equipment should conform to EN166.

Skin protection:

Suitable protective clothing
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	liquid liquid light grey
Odor	characteristic
Odour threshold	No data available / Not applicable
pH	No data available / Not applicable
Initial boiling point	No data available / Not applicable
Flash point	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Vapour pressure	No data available / Not applicable
Density (20 °C (68 °F))	1,55 - 1,65 g/cm ³
Bulk density	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Solubility (qualitative)	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Melting point	No data available / Not applicable
Flammability	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Explosive limits	No data available / Not applicable
Partition coefficient: n-octanol/water	No data available / Not applicable
Evaporation rate	No data available / Not applicable
Vapor density	No data available / Not applicable
Oxidising properties	No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Reaction with acids: production of heat and carbon dioxide.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

None if used for intended purpose.

10.5. Incompatible materials

None if used properly.

10.6. Hazardous decomposition products

None known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

General toxicological information:

Cross-reactions with other epoxide compounds possible.

Acute oral toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane 25068-38-6	LD50	> 2.000 mg/kg	oral		rat	OECD Guideline 420 (Acute Oral Toxicity)
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	LD50	26.800 mg/kg	oral		rat	not specified

Acute dermal toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane 25068-38-6	LD50	> 2.000 mg/kg	dermal		rat	OECD Guideline 402 (Acute Dermal Toxicity)
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	LD50	> 4.000 mg/kg	dermal		rabbit	not specified

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane 25068-38-6	slightly irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	moderately irritating	24 h	rabbit	EPA OTS 798.4470 (Acute Dermal Irritation)

Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane 25068-38-6	slightly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	not irritating		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane 25068-38-6	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	sensitising	Buehler test	guinea pig	EPA OPPTS 870.2600 (Skin Sensitisation)

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane 25068-38-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 472 (Genetic Toxicology: Escherichia coli, Reverse Mutation Assay)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane 25068-38-6	negative	oral: gavage		mouse	not specified
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
	positive	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	negative	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
	negative	intraperitoneal		rat	equivalent or similar to OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test)
	negative	oral: gavage		rat	OECD Guideline 488 (In Vivo Transgenic Cell Gene Mutation Assays)

Carcinogenicity:

Hazardous components CAS-No.	Result	Species	Sex	Exposure time Frequency of treatment	Route of application	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane 25068-38-6	not carcinogenic	mouse	male	2 y daily	dermal	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane 25068-38-6	not carcinogenic	rat	male/female	2 y daily	oral: gavage	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Reproductive toxicity:

Hazardous substances CAS-No.	Result / Classification	Species	Exposure time	Species	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane 25068-38-6	NOAEL P = >= 50 mg/kg NOAEL F1 = >= 750 mg/kg NOAEL F2 = >= 750 mg/kg	Two generation study oral: gavage	238 d	rat	OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	NOAEL P = 40 mg/kg	one- generation study oral: gavage		rat	OECD Guideline 443 (Extended One-Generation Reproductive Toxicity Study)

Repeated dose toxicity

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane 25068-38-6	NOAEL=50 mg/kg	oral: gavage	14 wdaily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	NOAEL=>= 1 mg/kg	oral: gavage	13 w5 d/w	rat	OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)

SECTION 12: Ecological information**General ecological information:**

Do not empty into drains, soil or bodies of water.

12.1. Toxicity

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 25068-38-6	LC50	1,75 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 25068-38-6	EC50	1,7 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 25068-38-6	EC50	> 11 mg/l	Algae	72 h	Scenedesmus capricornutum	OECD Guideline 201 (Alga, Growth Inhibition Test)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 25068-38-6	NOEC	4,2 mg/l	Algae	72 h	Scenedesmus capricornutum	OECD Guideline 201 (Alga, Growth Inhibition Test)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 25068-38-6	IC50	> 100 mg/l	Bacteria	3 h	activated sludge, industrial	other guideline:
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 25068-38-6	NOEC	0,3 mg/l	chronic Daphnia	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	LL50	> 100 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	EL50	7,2 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	NOELR	56 mg/l	chronic Daphnia	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

12.2. Persistence and degradability

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 25068-38-6	not readily biodegradable.	aerobic	5 %	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	readily biodegradable	aerobic	87 %	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

12.3. Bioaccumulative potential / 12.4. Mobility in soil

Hazardous components CAS-No.	LogPow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 25068-38-6	3,242				25 °C	EU Method A.8 (Partition Coefficient)
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	3,77				20 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

12.5. Results of PBT and vPvB assessment

Hazardous components CAS-No.	PBT/vPvB
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 25068-38-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

Waste code

080119

SECTION 14: Transport information**14.1. UN number or ID number**

ADR	3082
RID	3082
ADN	3082
IMDG	3082
IATA	3082

14.2. UN proper shipping name

ADR	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin)
RID	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin)
ADN	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin)
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin)
IATA	Environmentally hazardous substance, liquid, n.o.s. (Epoxy resin)

14.3. Transport hazard class(es)

ADR	9
RID	9
ADN	9
IMDG	9
IATA	9

14.4. Packing group

ADR	III
RID	III
ADN	III
IMDG	III
IATA	III

14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	Marine pollutant
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable Tunnelcode:
-----	-------------------------------

RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), A197 (IATA), 2.10.2.7 (IMDG), NZ 4.3(10) may be applied, which can result in a deviation from the transport classification for packed goods.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

No information available:

Ozone Depleting Substance (ODS) (Regulation (EC) No 2024/590):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H360F May damage fertility.
- H411 Toxic to aquatic life with long lasting effects.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

This Safety Data Sheet has been generated based on Regulation (EC) No 1907/2006 and it is applicable for Gulf Cooperation Council (GCC) and Africa only. No warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory, including export laws and regulations. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory affairs for additional assistance.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Product is intended for professional use.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.