



Safety Data Sheet

Loctite Super Glue-3 Control Liquid

Page 1 of 8

SDS No. : 281463

V001.1

Date of issue: 17.11.2023

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: Loctite Super Glue-3 Control Liquid

Intended use: Super glue

Supplier:
Henkel Australia Pty Ltd
135-141 Canterbury Road
Kilsyth, Victoria, 3137
Australia

Phone: +61 (3) 9724 6444

Section 2. Hazards identification

Classification of the substance or mixture

Hazardous according to the criteria of Safe Work Australia.

GHS Classification:

| <u>Hazard Class</u> | <u>Hazard Category</u> | <u>Target organ</u> |
|-----------------------------------------------------|------------------------|------------------------------|
| Flammable liquids | Category 4 | |
| Skin irritation | Category 2 | |
| Serious eye irritation | Category 2A | |
| Target Organ Systemic Toxicant - Single exposure | Category 3 | respiratory tract irritation |
| Acute hazards to the aquatic environment | Category 3 | |

Hazard pictogram:



Signal word:

Warning

| | |
|------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Hazard statement(s): | H227 Combustible liquid. H315 Causes skin irritation. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H402 Harmful to aquatic life. |
| Precautionary Statement(s): | |
| Prevention: | P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing mist/vapours. P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment. P280 Wear protective gloves/protective clothing/eye protection/face protection. |
| Response: | P302+P352 IF ON SKIN: Wash with plenty of water. P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. |
| Storage: | P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. |
| Disposal: | P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations. |

Dangerous Goods information:

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

Section 3. Composition / information on ingredients

General chemical description: Mixture

Identity of ingredients:

| Chemical ingredients | CAS-No. | Proportion |
|---------------------------------------------------|-----------|--------------|
| Ethyl 2-cyanoacrylate | 7085-85-0 | 60- <= 100 % |
| Bis(2-hydroxy-3-tert-butyl-5-methylphenyl)methane | 119-47-1 | < 0.3 % |
| non hazardous ingredients~ | | 1- <= 10 % |

Section 4. First aid measures

| | |
|-------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Ingestion: | Ensure that breathing passages are not obstructed. The product will polymerise immediately in the mouth making it almost impossible to swallow. Saliva will slowly separate the solidified product from the mouth (several hours). |
| Skin: | Do not pull bonded skin apart. It may be gently peeled apart using a blunt object such as a spoon, preferably after soaking in warm soapy water. Cyanoacrylates give off heat on solidification. In rare cases a large drop will generate enough heat to cause a burn. Burns should be treated normally after the adhesive has been removed from the skin. If lips are accidentally stuck together apply warm water to the lips and encourage maximum wetting and pressure from saliva inside the mouth. Peel or roll lips apart. Do not try to pull the lips apart with direct opposing action. |
| Eyes: | If the eye is bonded closed, release eyelashes with warm water by covering with wet pad. Cyanoacrylate will bond to eye protein and will cause periods of weeping which will help to debond the adhesive. Keep eye covered until debonding is complete, usually within 1-3 days. Do not force eye open. Medical advice should be sought in case solid particles of cyanoacrylate trapped behind the eyelid cause any abrasive damage. |
| Inhalation: | Move to fresh air, consult doctor if complaint persists. |
| First Aid facilities: | Eye wash and safety shower Normal washroom facilities |
| Medical attention and special treatment: | Treat symptomatically. |

Section 5. Fire fighting measures

| | |
|--------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| Suitable extinguishing media: | Foam, extinguishing powder, carbon dioxide. Fine water spray |
| Improper extinguishing media: | High pressure waterjet |
| Combustion behaviour: | Combustible Liquid Keep away from heat, spark, and open flames. |
| Decomposition products in case of fire: | Thermal decomposition can lead to release of irritating gases and vapors. carbon monoxide Carbon dioxide. Oxides of nitrogen. |
| Special protective equipment for fire-fighters: | Wear full protective clothing. Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA). |

Section 6. Accidental release measures

| | |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Personal precautions: | Ensure adequate ventilation. Avoid skin and eye contact. Wear protective equipment. |
| Environmental precautions: | Do not let product enter drains. |
| Clean-up methods: | Do not use cloths for mopping up. Flood with water to complete polymerization and scrape off the floor. Cured material can be disposed of as non-hazardous waste. Dispose of contaminated material as waste according to Section 13. |

Section 7. Handling and storage

| | |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Precautions for safe handling: | Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Avoid contact with fabric or paper goods. Contact with these materials may cause rapid polymerization which can generate smoke and strong irritating vapors, and cause thermal burns. |
| Conditions for safe storage: | Protect from direct sunlight. Store away from incompatible materials. Store in a cool place in closed original container. For optimum shelf life store in original containers under refrigerated conditions at 2 - 8°C (35.6 - 46.4 °F) |

Section 8. Exposure controls / personal protection

National exposure standards:

None

| | |
|--------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Eye protection: | Wear protective glasses. |
| Skin protection: | Protective clothing that covers arms and legs. The use of chemical resistant gloves such as Nitrile is recommended. Polyethylene or polypropylene gloves are recommended when using large volumes. Do not use PVC, rubber or nylon gloves. Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced. |
| Respiratory protection: | If inhalation risk exists, wear a respirator or air supplied mask complying with the requirements of AS/NZS 1715 and AS/NZS 1716. |

Section 9. Physical and chemical properties

| | |
|-------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| Appearance: | colourless liquidColorless liquid |
| Odor: | characteristicirritating |
| pH: | Not applicable, Product reacts with water. |
| Melting point / freezing point: | Not applicable, Product is a liquid |
| Specific gravity: | 1.05 - 1.1 |
| Boiling point: | > 100 °C (> 212 °F) |
| Flash point: (no method / method unknown) | 80 - 93 °C (176 - 199.4 °F) |
| Vapor pressure: (; 50 °C (122 °F); 20 °C (68 °F)) | 2.5 hPa < 0.2 mm hg |
| Vapor density: | 3 |
| Density: | 1.1 g/cm3 |
| Viscosity (dynamic): | 20 - 120 mPa.s(Cone and plate; Instrument: Physica MC 100 (or equivalent), Cone MK 22; Method: ;; LCT STM 740; cone & plate viscosity) |
| VOC content (2010/75/EC) | 0.0 % (VOCV 814.018 VOC regulation CH) |

Section 10. Stability and reactivity

| | |
|------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| Stability: | Stable under recommended storage conditions. |
| Conditions to avoid: | Keep away from sources of ignition and naked flames. |
| Incompatible materials: | Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and alcohols. |
| Hazardous decomposition products: | Thermal decomposition can lead to release of irritating gases and vapors. carbon monoxide Carbon dioxide. Oxides of nitrogen. |

Section 11. Toxicological information**Acute toxicity:**

| Hazardous components CAS-No. | Value type | Value | Route of application | Exposure time | Species | Method |
|---------------------------------------------------------------|--------------|----------------------------------|----------------------|---------------|---------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Ethyl 2-cyanoacrylate 7085-85-0 | LD50 LD50 | > 5,000 mg/kg > 2,000 mg/kg | oral dermal | | rat rabbit | equivalent or similar to OECD Guideline 423 (Acute Oral toxicity) equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity) |
| Bis(2-hydroxy-3-tert-butyl-5-methylphenyl)methane 119-47-1 | LD50 LD50 | > 10,000 mg/kg > 10,000 mg/kg | oral dermal | | rat rat | not specified not specified |

Skin corrosion/irritation:

| Hazardous components CAS-No. | Result | Exposure time | Species | Method |
|------------------------------------|---------------------|---------------|---------|-----------------------------------------------------------------------------------|
| Ethyl 2-cyanoacrylate 7085-85-0 | slightly irritating | 24 h | rabbit | equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |

Serious eye damage/irritation:

| Hazardous components CAS-No. | Result | Exposure time | Species | Method |
|------------------------------------|------------|---------------|---------|--------------------------------------------------------------------------------|
| Ethyl 2-cyanoacrylate 7085-85-0 | irritating | | rabbit | equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion) |

Respiratory or skin sensitization:

| Hazardous components CAS-No. | Result | Test type | Species | Method |
|------------------------------------|-----------------|--------------------|------------|---------------|
| Ethyl 2-cyanoacrylate 7085-85-0 | not sensitising | Skin sensitisation | guinea pig | not specified |

Germ cell mutagenicity:

| Hazardous components CAS-No. | Result | Type of study / Route of administration | Metabolic activation / Exposure time | Species | Method |
|---------------------------------------------------------------|----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------|---------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Ethyl 2-cyanoacrylate 7085-85-0 | negative negative negative | bacterial reverse mutation assay (e.g Ames test) in vitro mammalian chromosome aberration test mammalian cell gene mutation assay | with and without with and without with and without | | equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay) OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| Bis(2-hydroxy-3-tert-butyl-5-methylphenyl)methane 119-47-1 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |

Section 12. Ecological information

General ecological information: Do not empty into drains / surface water / ground water.

Ecotoxicity: H402 Harmful to aquatic life.

Toxicity:

| Hazardous components CAS-No. | Value type | Value | Acute Toxicity Study | Exposure time | Species | Method |
|---------------------------------------------------------------|------------|-----------------------------|----------------------|---------------|-------------------------------------------------------------------------|--------------------------------------------------------------------|
| Bis(2-hydroxy-3-tert-butyl-5-methylphenyl)methane 119-47-1 | LC50 | Toxicity > Water solubility | Fish | 96 h | Oryzias latipes | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Bis(2-hydroxy-3-tert-butyl-5-methylphenyl)methane 119-47-1 | EC50 | Toxicity > Water solubility | Daphnia | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Bis(2-hydroxy-3-tert-butyl-5-methylphenyl)methane 119-47-1 | EC50 | Toxicity > Water solubility | Algae | 72 h | Pseudokirchneriella subcapitata (reported as Selenastrum capricornutum) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Bis(2-hydroxy-3-tert-butyl-5-methylphenyl)methane 119-47-1 | NOEC | Toxicity > Water solubility | Algae | 72 h | Pseudokirchneriella subcapitata (reported as Selenastrum capricornutum) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Bis(2-hydroxy-3-tert-butyl-5-methylphenyl)methane 119-47-1 | EC50 | Toxicity > Water solubility | Bacteria | 3 h | activated sludge | OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test) |

Persistence and degradability:

| Hazardous components CAS-No. | Result | Route of application | Degradability | Method |
|---------------------------------------------------------------|--------------------------------------------------|----------------------|---------------|-----------------------------------------------------------------------|
| Ethyl 2-cyanoacrylate 7085-85-0 | not readily biodegradable. | aerobic | 57 % | OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test) |
| Bis(2-hydroxy-3-tert-butyl-5-methylphenyl)methane 119-47-1 | under test conditions no biodegradation observed | aerobic | 0 % | OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I)) |

Bioaccumulative potential / Mobility in soil:

| Hazardous components CAS-No. | LogPow | Bioconcentration factor (BCF) | Exposure time | Species | Temperature | Method |
|------------------------------|--------|-------------------------------|---------------|---------|-------------|--------|
|------------------------------|--------|-------------------------------|---------------|---------|-------------|--------|

| | | | | | | |
|---------------------------------------------------------------|-------|-----------|------|-----------------|-------|------------------------------------------------------------------------------------|
| Ethyl 2-cyanoacrylate 7085-85-0 | 0.776 | | | | 22 °C | EU Method A.8 (Partition Coefficient) |
| Bis(2-hydroxy-3-tert-butyl-5-methylphenyl)methane 119-47-1 | | 320 - 780 | 60 d | Cyprinus carpio | | OECD Guideline 305 E (Bioaccumulation: Flow-through Fish Test) |
| Bis(2-hydroxy-3-tert-butyl-5-methylphenyl)methane 119-47-1 | 6.25 | | | | 20 °C | OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method) |

Section 13. Disposal considerations

Waste disposal of product: Cured adhesive: Dispose of as water insoluble non-toxic solid chemical in authorised landfill or incinerate under controlled conditions.
Dispose of in accordance with local and national regulations.
Contribution of this product to waste is very insignificant in comparison to article in which it is used

Disposal for uncleaned package: After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.
Disposal must be made according to official regulations.

Section 14. Transport information

Road and Rail Transport:

Dangerous Goods information: Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

Marine transport IMDG:

Not dangerous goods

Air transport IATA:

UN no.: 3334
Proper shipping name: Aviation regulated liquid, n.o.s. (Cyanoacrylate ester)
Class or division: 9
Packing group: III
Packing instructions (passenger): 964
Packing instructions (cargo): 964
Additional Information IATA: Not more than 500 ml (each inner package) - Unrestricted

Section 15. Regulatory information

AIIC: All components are listed or are exempt from listing on the Australian Inventory of Industrial Chemicals or Introduced under AICIS.

Section 16. Other information

Abbreviations/acronyms: CAS: Chemical Abstracts Service
GHS: Globally Harmonized System
IMDG: International Maritime Dangerous Goods code
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations
ADGC - Australian Dangerous Goods Code
SUSMP - Standard for the Uniform Medicines of Medicines and Poisons
AIIC - Australian Inventory of Industrial Chemicals (AIIC)
AICIS - Australian Industrial Chemicals Introduction Scheme

Reason for issue: Reviewed SDS. Reissued with new date. involved chapters: 3,11

Date of previous issue: 26.06.2022

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material.

The information contained in the Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.