



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 17

Ceresit CL 51 (UA)

SDS No. : 510718
V002.0

Revision: 03.06.2024

printing date: 17.07.2025

Replaces version from: 10.06.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Ceresit CL 51 (UA)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Special product

1.3. Details of the supplier of the safety data sheet

Henkel Bautechnik (Ukraine)

Vyshhorod, Novopromyslova St. 2

07302 Kyiv region

Ukraine

Phone: +380 (800) 308 405

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website www.mysds.henkel.com or www.henkel-adhesives.com.

1.4. Emergency telephone number

0-800-308-405 (24 h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin sensitizer

Category 1

H317 May cause an allergic skin reaction.

Chronic hazards to the aquatic environment

Category 3

H412 Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains

1,2-Бензизотиазолин-3-он

Смесь изотиазолинонов (С(М)ИТ/МІТ (3:1))

Signal word:

Warning

Hazard statement:	H317 May cause an allergic skin reaction. H412 Harmful to aquatic life with long lasting effects.
Supplemental information	EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Precautionary statement:	P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children.
Precautionary statement: Prevention	P273 Avoid release to the environment. P280 Wear protective gloves.
Precautionary statement: Response	P302+P352 IF ON SKIN: Wash with plenty of soap and water.
Precautionary statement: Disposal	P501 Dispose of contents/container in accordance with national regulation.

2.3. Other hazards

None if used properly.

Following substances are present in a concentration \geq the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration \geq the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
Титана двуокись 13463-67-7 236-675-5 01-2119489379-17	1- < 5 %	Carc. 2, Inhalation, H351		
1,2-Бензизотиазолин-3-он 2634-33-5 220-120-9 01-2120761540-60	0,0036- < 0,036 % (36 ppm- < 360 ppm)	Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Acute Tox. 4, Oral, H302 Skin Irrit. 2, H315 Skin Sens. 1A, H317 Eye Dam. 1, H318 Acute Tox. 2, Inhalation, H330	Skin Sens. 1A; H317; C >= 0,036 % ===== M acute = 1 M chronic = 1 ===== oral:ATE = 450 mg/kg inhalation:ATE = 0,21 mg/l;dust/mist	
Смесь изотиазолинонов (С(М)IT/MIT (3:1)) 55965-84-9 01-2120764691-48	0,0025- < 0,025 % (25 ppm- < 250 ppm)	Aquatic Chronic 1, H410 Skin Corr. 1C, H314 Acute Tox. 2, Dermal, H310 Acute Tox. 3, Oral, H301 Eye Dam. 1, H318 Acute Tox. 2, Inhalation, H330 Aquatic Acute 1, H400 Skin Sens. 1A, H317	Skin Irrit. 2; H315; C 0,06 - < 0,6 % Skin Corr. 1C; H314; C >= 0,6 % Eye Irrit. 2; H319; C 0,06 - < 0,6 % Eye Dam. 1; H318; C >= 0,6 % Skin Sens. 1A; H317; C >= 0,0015 % ===== M acute = 100 M chronic = 100	

For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures**4.1. Description of first aid measures**

General information:

In case of adverse health effects seek medical advice.

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing. If necessary, see a dermatologist.

Eye contact:

Immediately flush eyes with soft jet of water or eye rinse solution for at least 5 minutes. If pains remain (intensive smarting, sensitivity to light, visual disturbance) continue flushing and contact/seek doctor or hospital.

Ingestion:

Rinse mouth and throat. Drink 1-2 glasses of water. Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media**Suitable extinguishing media:**

carbon dioxide, foam, powder, water spray jet, fine water spray

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO₂) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Wear protective equipment.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Wear protective equipment.

Avoid contact with skin and eyes.

Ensure adequate ventilation.

Danger of slipping on spilled product.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13.

Remove mechanically.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Ensure that workrooms are adequately ventilated.

Avoid skin and eye contact.

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Store in sealed original container.

Temperatures between + 5 °C and + 30 °C.

Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

7.3. Specific end use(s)

Special product

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Ukraine

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Limestone 1317-65-3 [Carbon dusts: coke from coal, pitch, oil, shale Silicate-containing dust, silicates, aluminosilicates: asbestos cement Carbon dusts: anthracite containing up to 5% free SiO ₂ Silicate-containing dust, silicates, aluminosilicates: concrete, olivine, apatite, fosterite, clay, kaolin fireclay]		6	Time Weighted Average (TWA):		UA OELA
Limestone 1317-65-3 [Silicate-containing dust, silicates, aluminosilicates: asbestos dust with asbestos content from 10% to 20%]		1	Short Term Exposure Limit (STEL):		UA OELA
Limestone 1317-65-3 [Carbon dusts: other mined coals and coal dusts containing up to 5% free SiO ₂ Silicate-containing dust, silicates, aluminosilicates: asbestos groceries, asbestos rubber]		10	Time Weighted Average (TWA):		UA OELA
Limestone 1317-65-3 [Silicate-containing dust, silicates, aluminosilicates: asbestos dust with asbestos content from 10% to 20% Silicate-containing dust, silicates, aluminosilicates: natural asbestos (chrysotile, anthophyllite, actinolite, tremolite, magnesium)]		2	Time Weighted Average (TWA):		UA OELA
Limestone 1317-65-3 [Silicate-containing dust, silicates, aluminosilicates: natural asbestos (chrysotile, anthophyllite, actinolite, tremolite, magnesium)]		0,5	Short Term Exposure Limit (STEL):		UA OELA
Limestone 1317-65-3 [Carbon dusts: carbon fiber materials based on polyacrylonitrile fibers Carbon dusts: carbon fiber materials based on cellulose hydrate fibers]		2	Short Term Exposure Limit (STEL):		UA OELA
Limestone 1317-65-3 [Carbon dusts: carbon fiber materials based on polyacrylonitrile fibers Carbon dusts: carbon fiber materials based on cellulose hydrate fibers]			Skin designation:	Chemical is dangerous when exposed to the skin and the mucous membrane of the eyes	UA OELA
Limestone 1317-65-3 [Silicate-containing dust, silicates, aluminosilicates: asbestos cement Silicate-containing dust, silicates, aluminosilicates: asbestos groceries, asbestos rubber]		4	Short Term Exposure Limit (STEL):		UA OELA
Limestone 1317-65-3 [Carbon dusts: carbon fiber materials based on cellulose hydrate fibers Carbon dusts: carbon fiber materials based on polyacrylonitrile fibers]		4	Time Weighted Average (TWA):		UA OELA
Limestone		8	Time Weighted Average		UA OELA

1317-65-3 [Carbon dusts: natural and synthetic diamonds]			(TWA):		
Limestone 1317-65-3 [Silicate-containing dust, silicates, aluminosilicates: asbestos dust with asbestos content less than 10%]		2	Short Term Exposure Limit (STEL):		UA OELA
Limestone 1317-65-3 [Carbon dusts: other mined coals and coal dusts containing from 5 to 10% free SiO ₂ Carbon dusts: black industrial soot containing <35 mg benz(a)pyrene per kg Silicate-containing dust, silicates, aluminosilicates: vitreous silicates of volcanic origin (tuff, pumice, perlite) Silicate-containing dust, silicates, aluminosilicates: asbestos dust with asbestos content less than 10% Silicate-containing dust, silicates, aluminosilicates: mica (flagopit, muscovite), talc, talc dust (natural mixtures of talc with tr Carbon dust: metallized diamond]		4	Time Weighted Average (TWA):		UA OELA
Titanium dioxide 13463-67-7 [Titanium and its dioxide]		10	Time Weighted Average (TWA):		UA OELA
Propane-1,2-diol 57-55-6 [Propane-1,2-diol]		7	Time Weighted Average (TWA):		UA OELA

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
1,2-Benzisothiazol-3(2H)-one 2634-33-5	aqua (freshwater)		0,00403 mg/l				
1,2-Benzisothiazol-3(2H)-one 2634-33-5	aqua (marine water)		0,000403 mg/l				
1,2-Benzisothiazol-3(2H)-one 2634-33-5	Freshwater - intermittent		0,0011 mg/l				
1,2-Benzisothiazol-3(2H)-one 2634-33-5	sewage treatment plant (STP)		1,03 mg/l				
1,2-Benzisothiazol-3(2H)-one 2634-33-5	sediment (freshwater)				0,0499 mg/kg		
1,2-Benzisothiazol-3(2H)-one 2634-33-5	sediment (marine water)				0,00499 mg/kg		
1,2-Benzisothiazol-3(2H)-one 2634-33-5	Soil				3 mg/kg		
1,2-Benzisothiazol-3(2H)-one 2634-33-5	Marine water - intermittent		0,000110 mg/l				
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone (3:1) 55965-84-9	aqua (freshwater)		0,00339 mg/l				
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone (3:1) 55965-84-9	aqua (marine water)		0,00339 mg/l				
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone (3:1) 55965-84-9	sewage treatment plant (STP)		0,23 mg/l				
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone (3:1) 55965-84-9	sediment (freshwater)				0,027 mg/kg		
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone (3:1) 55965-84-9	sediment (marine water)				0,027 mg/kg		
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone (3:1) 55965-84-9	Soil				0,01 mg/kg		
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone (3:1) 55965-84-9	Freshwater - intermittent		0,00339 mg/l				
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone (3:1) 55965-84-9	Marine water - intermittent		0,00339 mg/l				

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Titanium dioxide 13463-67-7	Workers	inhalation	Long term exposure - local effects		0,17 mg/m ³	
Titanium dioxide 13463-67-7	General population	inhalation	Long term exposure - local effects		0,028 mg/m ³	
1,2-Benzisothiazol-3(2H)-one 2634-33-5	Workers	inhalation	Long term exposure - systemic effects		6,81 mg/m ³	
1,2-Benzisothiazol-3(2H)-one 2634-33-5	Workers	dermal	Long term exposure - systemic effects		0,966 mg/kg	
1,2-Benzisothiazol-3(2H)-one 2634-33-5	General population	inhalation	Long term exposure - systemic effects		1,2 mg/m ³	
1,2-Benzisothiazol-3(2H)-one 2634-33-5	General population	dermal	Long term exposure - systemic effects		0,345 mg/kg	
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone (3:1) 55965-84-9	Workers	inhalation	Long term exposure - local effects		0,02 mg/m ³	
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone (3:1) 55965-84-9	Workers	inhalation	Acute/short term exposure - local effects		0,04 mg/m ³	
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone (3:1) 55965-84-9	General population	inhalation	Long term exposure - local effects		0,02 mg/m ³	
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone (3:1) 55965-84-9	General population	inhalation	Acute/short term exposure - local effects		0,04 mg/m ³	
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone (3:1) 55965-84-9	General population	oral	Long term exposure - systemic effects		0,09 mg/kg	
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone (3:1) 55965-84-9	General population	oral	Acute/short term exposure - systemic effects		0,11 mg/kg	

Biological Exposure Indices:

None

8.2. Exposure controls:**Respiratory protection:**

Suitable breathing mask when there is inadequate ventilation.

Combination filter: ABEKP (EN 14387)

This recommendation should be matched to local conditions.

Hand protection:

In the case of longer contact protective gloves made from nitrile rubber are recommended according to EN 374.

Perforation time > 480 minutes

material thickness > 0.1 mm

In the case of longer and repeated contact please note that in practice the penetration times may be considerably shorter than those determined according to EN 374. The protective gloves must always be checked for their suitability for use at the specific workplace (e.g. mechanical and thermal stress, product compatibility, antistatic effects, etc.). The gloves must be replaced immediately at the first signs of wear and tear. The information provided by the manufacturers and given in the relevant trade association regulations for industrial safety must always be observed. We recommend that a hand care plan is drawn up in cooperation with a glove manufacturer and the trade association in accordance with the local operating conditions.

Eye protection:

Goggles which can be tightly sealed.
Protective eye equipment should conform to EN166.

Skin protection:

Suitable protective clothing
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Delivery form	paste
Colour	white
Odor	characteristic
Physical state	liquid
Melting point	Currently under determination
Initial boiling point	Currently under determination
Flammability	Currently under determination
Explosive limits	Currently under determination
Flash point	Currently under determination
Auto-ignition temperature	Currently under determination
Decomposition temperature	Currently under determination
pH	Currently under determination
Viscosity (kinematic)	Currently under determination
Solubility (qualitative)	Insoluble
(20 °C (68 °F); Solvent: Water)	
Solubility (qualitative)	Miscible
Partition coefficient: n-octanol/water	Currently under determination
Vapour pressure	Currently under determination
Density	1,3 g/cm ³ no method / method unknown
(20 °C (68 °F))	
Relative vapour density:	Currently under determination
Particle characteristics	Currently under determination

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity**10.1. Reactivity**

None if used for intended purpose.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

None if used for intended purpose.

10.5. Incompatible materials

None if used properly.

10.6. Hazardous decomposition products

None known.

SECTION 11: Toxicological information

General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

11.1. Information on toxicological effects

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Titanium dioxide 13463-67-7	LD50	> 5.000 mg/kg	rat	OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	Acute toxicity estimate (ATE)	450 mg/kg		Expert judgement
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	LD50	66 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Titanium dioxide 13463-67-7	LD50	> 10.000 mg/kg	rabbit	not specified
1,2-Benzisothiazol-3(2H)-one 2634-33-5	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	LD50	87,12 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Titanium dioxide 13463-67-7	LC50	> 6,82 mg/l	dust	4 h	rat	not specified
1,2-Benzisothiazol-3(2H)-one 2634-33-5	Acute toxicity estimate (ATE)	0,21 mg/l	dust/mist			Expert judgement
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	LC50	0,171 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Titanium dioxide 13463-67-7	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	moderately irritating	4 h	rabbit	EPA OPP 81-5 (Acute Dermal Irritation)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	corrosive	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Titanium dioxide 13463-67-7	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	corrosive	3 h	rabbit	EPA OPP 81-4 (Acute Eye Irritation)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	Category 1 (irreversible effects on the eye)		rabbit	not specified

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Titanium dioxide 13463-67-7	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Titanium dioxide 13463-67-7	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	sensitising	Mouse local lymphnode assay (LLNA)	mouse	not specified

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Titanium dioxide 13463-67-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Titanium dioxide 13463-67-7	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Titanium dioxide 13463-67-7	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Titanium dioxide 13463-67-7	negative	in vitro mammalian cell micronucleus test	without		equivalent or similar to OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	positive without metabolic activation	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	ambiguous	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	positive	in vitro mammalian chromosome aberration test	with and without		EPA OPP 84-2 (Mutagenicity Testing)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	positive	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	negative	DNA damage and repair assay, unscheduled DNA synthesis in mammalian cells in vitro	not applicable		OECD Guideline 482 (Genetic Toxicology: DNA Damage and Repair, Unscheduled DNA Synthesis in Mammalian Cells In Vitro)
Titanium dioxide 13463-67-7	negative	oral: gavage		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	negative	oral: unspecified		rat	OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	negative	oral: gavage		mouse	OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	negative	oral: feed		Drosophila melanogaster	OECD Guideline 477 (Genetic Toxicology: Sex-linked Recessive Lethal Test in Drosophila melanogaster)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	negative	oral: gavage		rat	OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	negative	oral: gavage		rat	EPA OPP 84-2 (Mutagenicity Testing)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Titanium dioxide 13463-67-7	not carcinogenic	oral: feed	103 w daily	rat	male/female	not specified
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	not carcinogenic	oral: drinking water	2 y daily	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Titanium dioxide 13463-67-7	NOAEL P >= 1.000 mg/kg NOAEL F1 >= 1.000 mg/kg	one- generation study	oral: feed	rat	OECD Guideline 443 (Extended One-Generation Reproductive Toxicity Study)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	NOAEL P 112 mg/kg NOAEL F1 56,6 mg/kg NOAEL F2 56,6 mg/kg	Two generation study	oral: feed	rat	EPA OPPTS 870.3800 (Reproduction and Fertility Effects)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	NOAEL P 30 ppm NOAEL F1 300 ppm NOAEL F2 300 ppm	Two generation study	oral: drinking water	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)

STOT-single exposure:

No data available.

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Titanium dioxide 13463-67-7	NOAEL > 1.000 mg/kg	oral: gavage	92 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	NOAEL 150 mg/kg	oral: gavage	28 days daily	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	NOAEL 69 mg/kg	oral: feed	90 days daily	rat	EPA OPP 82-1 (90-Day Oral Toxicity)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	NOAEL 16,3 mg/kg	oral: drinking water	90 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	NOAEL 0.34 mg/m ³	inhalation: aerosol	90 d 6 h/d, 5 d/w	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	NOAEL 2,625 mg/kg	dermal	90 d 6 h/d	rat	EPA OPP 82-3 (Subchronic Dermal Toxicity 90 Days)

Aspiration hazard:

No data available.

SECTION 12: Ecological information**General ecological information:**

Do not empty into drains, soil or bodies of water.

12.1. Toxicity**Toxicity (Fish):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Titanium dioxide 13463-67-7	LC50	Toxicity > Water solubility	48 h	Leuciscus idus	OECD Guideline 203 (Fish, Acute Toxicity Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	LC50	2,15 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	NOEC	0,21 mg/l	30 d	Oncorhynchus mykiss	OECD Guideline 215 (Fish, Juvenile Growth Test)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	LC50	0,22 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	NOEC	0,098 mg/l	28 d	Oncorhynchus mykiss	OECD Guideline 210 (fish early lite stage toxicity test)

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Titanium dioxide 13463-67-7	EC50	Toxicity > Water solubility	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	EC50	2,9 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	EC50	0,12 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Titanium dioxide 13463-67-7	NOEC	Toxicity > Water solubility	21 d	Daphnia magna	OECD Guideline 202 (Daphnia sp. Chronic Immobilisation Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	NOEC	1,2 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	NOEC	0,0036 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Titanium dioxide 13463-67-7	EC50	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Titanium dioxide 13463-67-7	NOEC	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	EC50	0,1087 mg/l	24 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	EC10	0,0264 mg/l	24 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	EC50	0,0052 mg/l	72 h	Skeletonema costatum	OECD Guideline 201 (Alga, Growth Inhibition Test)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	NOEC	0,00064 mg/l	48 h	Skeletonema costatum	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Titanium dioxide 13463-67-7	EC0	Toxicity > Water solubility	24 h	Pseudomonas fluorescens	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	EC50	23 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	EC20	0,97 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
1,2-Benzisothiazol-3(2H)-one 2634-33-5	not readily biodegradable.	aerobic	42,1 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	inherently biodegradable	aerobic	100 %	28 d	OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	readily biodegradable	aerobic	> 60 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

12.3. Bioaccumulative potential

Hazardous substances CAS-No.	Bioconcentration factor (BCF)	Exposure time	Temperature	Species	Method
1,2-Benzisothiazol-3(2H)-one 2634-33-5	6,62	56 d		not specified	other guideline:
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	3,6			calculation	QSAR (Quantitative Structure Activity Relationship)

12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
1,2-Benzisothiazol-3(2H)-one 2634-33-5	0,7	20 °C	EU Method A.8 (Partition Coefficient)
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	> -0,71 - 0,75	20 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
Titanium dioxide 13463-67-7	According to Annex XIII to Regulation (EC) No 1907/2006, a PBT and vPvB assessment shall not be conducted for inorganic substances.
1,2-Benzisothiazol-3(2H)-one 2634-33-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Isothiazolinone mixture (C(M)IT/MIT (3:1)) 55965-84-9	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

Waste code

080409

SECTION 14: Transport information

14.1. UN number or ID number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

No information available:

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**15.2. Chemical safety assessment**

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H301 Toxic if swallowed.
H302 Harmful if swallowed.
H310 Fatal in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H330 Fatal if inhaled.
H351 Suspected of causing cancer.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.