



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 11

Metylan Aktiv Tapeten Ablöser

SDS No. : 49061
V004.1

Revision: 11.07.2022

printing date: 19.05.2025

Replaces version from: 30.06.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Metylan Aktiv Tapeten Ablöser

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Wall paper remover

1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA

Henkelstr. 67

40589 Düsseldorf

Germany

Phone: +49 211 797 0

ua-productsafety.de@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

Further information is available at Poison Control Centers.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Serious eye irritation

H319 Causes serious eye irritation.

Category 2

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Signal word:

Warning

Hazard statement:	H319 Causes serious eye irritation.
Precautionary statement:	P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children.
Precautionary statement: Prevention	P280 Wear eye protection.
Precautionary statement: Response	P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
None if used properly.

Following substances are present in a concentration $\geq 0,1\%$ and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in concentration \geq the concentration limit that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
Fatty alcohol, C12-14, EO/PO 68439-51-0	5- < 10 %	Aquatic Chronic 3, H412		
Alcohols, C10-16 ethoxylated propoxylated 69227-22-1	1- < 3 %	Acute Tox. 4, Oral, H302 Eye Dam. 1, H318	oral:ATE = 500 mg/kg	
2-n-butyl-benzo[d]isothiazol-3-one 4299-07-4 420-590-7	0,01- < 0,1 %	Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Skin Corr. 1B, H314	M acute = 10 M chronic = 10 ===== oral:ATE = 4.267 mg/kg	

**For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.**

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

In case of adverse health effects seek medical advice.

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap. Skin care. Remove contaminated clothes immediately.

Eye contact:

Immediately flush eyes with soft jet of water or eye rinse solution for at least 5 minutes. If pains remain (intensive smarting, sensitivity to light, visual disturbance) continue flushing and contact/seek doctor or hospital.

Ingestion:

Rinse mouth and throat. Drink 1-2 glasses of water. Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media:**

carbon dioxide, foam, powder, water spray jet, fine water spray

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO₂) can be released.

5.3. Advice for firefighters

Wear protective equipment.

Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Wear protective equipment.

Avoid contact with skin and eyes.

Ensure adequate ventilation.

Danger of slipping on spilled product.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Remove with liquid-absorbing material (sand, peat, sawdust).

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Avoid skin and eye contact.

Ensure that workrooms are adequately ventilated.

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Store in a cool, dry place.

Temperatures between + 5 °C and + 35 °C

Keep away from heat and direct sunlight.

7.3. Specific end use(s)

Wall paper remover

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational Exposure Limits**Valid for
GermanyValid for
Germany

None

None

Biological Exposure Indices:

None

8.2. Exposure controls:Respiratory protection:
Not needed.

Hand protection:

In the case of longer contact protective gloves made from nitrile rubber are recommended according to EN 374.

Perforation time > 480 minutes

material thickness > 0.1 mm

In the case of longer and repeated contact please note that in practice the penetration times may be considerably shorter than those determined according to EN 374. The protective gloves must always be checked for their suitability for use at the specific workplace (e.g. mechanical and thermal stress, product compatibility, antistatic effects, etc.). The gloves must be replaced immediately at the first signs of wear and tear. The information provided by the manufacturers and given in the relevant trade association regulations for industrial safety must always be observed. We recommend that a hand care plan is drawn up in cooperation with a glove manufacturer and the trade association in accordance with the local operating conditions.

Eye protection:

Goggles which can be tightly sealed.

Protective eye equipment should conform to EN166.

Skin protection:

Suitable protective clothing

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state	liquid
Delivery form	liquid
Colour	transparent
Odor	typical
Solidification temperature	0 °C (32 °F)
Initial boiling point	100 °C (212 °F)
Flammability	The product is not flammable.
Explosive limits	Currently under determination

Flash point	Not applicable, No flash point up to 100°C. Aqueous preparation.
Flash point	Not available.
Auto-ignition temperature	> 300 °C (> 572 °F)
Decomposition temperature	Currently under determination
pH (20 °C (68 °F); Conc.: 100,0 % product)	11 - 11,5 pH-value, universal method
pH (20 °C (68 °F); Conc.: 100 % product)	10,5 - 11,4 pH-value, universal method
Viscosity (kinematic) (40 °C (104 °F);)	> 20,5 mm ² /s
Solubility (qualitative) (20 °C (68 °F); Solvent: Water)	Soluble
Partition coefficient: n-octanol/water	Currently under determination
Vapour pressure (20 °C (68 °F))	23 hPa
Density (20 °C (68 °F))	0,99 - 1,01 g/cm ³
Relative vapour density: (20 °C)	< 1
Particle characteristics	Currently under determination

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

Reaction with acids: production of heat and chlorine gas.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

None if used for intended purpose.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

Heating causes decomposition and chlorine evolution.

SECTION 11: Toxicological information

1.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Fatty alcohol, C12-14, EO/PO 68439-51-0	LD50	3.515 mg/kg	rat	EU Method B.1 (Acute Toxicity (Oral))
Alcohols, C10-16 ethoxylated propoxylated 69227-22-1	Acute toxicity estimate (ATE)	500 mg/kg		Expert judgement
2-n-butyl- benzo[d]isothiazol-3-one 4299-07-4	LD50	4.267 - 4.732 mg/kg	rat	not specified
2-n-butyl- benzo[d]isothiazol-3-one 4299-07-4	Acute toxicity estimate (ATE)	4.267 mg/kg		Expert judgement

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Fatty alcohol, C12-14, EO/PO 68439-51-0	LD50	> 5.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
2-n-butyl- benzo[d]isothiazol-3-one 4299-07-4	LD50	> 2.000 mg/kg	rat	not specified

Acute inhalative toxicity:

No data available.

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Fatty alcohol, C12-14, EO/PO 68439-51-0	mildly irritating	4 h	rabbit	EU Method B.4 (Acute Toxicity: Dermal Irritation / Corrosion)
Alcohols, C10-16 ethoxylated propoxylated 69227-22-1	slightly irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
2-n-butyl- benzo[d]isothiazol-3-one 4299-07-4	corrosive	4 h		not specified

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Fatty alcohol, C12-14, EO/PO 68439-51-0	slightly irritating	24 h	rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Alcohols, C10-16 ethoxylated propoxylated 69227-22-1	highly irritating	24 h	rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Alcohols, C10-16 ethoxylated propoxylated 69227-22-1	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
2-n-butyl- benzo[d]isothiazol-3-one 4299-07-4	sensitising			not specified

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method

Carcinogenicity

No data available.

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
2-n-butyl- benzo[d]isothiazol-3-one 4299-07-4	NOAEL P 600 ppm NOAEL F1 1700 ppm	Two generation study	oral: feed	rat	not specified

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
2-n-butyl- benzo[d]isothiazol-3-one 4299-07-4	NOAEL 15 mg/kg		90 d daily	rat	not specified

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains, soil or bodies of water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Fatty alcohol, C12-14, EO/PO 68439-51-0	LC50	1,6 mg/l	48 h	Leuciscus idus	DIN 38412-15
Alcohols, C10-16 ethoxylated propoxylated 69227-22-1	LC50	> 1 - 10 mg/l	96 h	Brachydanio rerio (new name: Danio rerio)	ISO 7346/1-3 (Determination of the Acute Lethal Toxicity of Substances to a Freshwater Fish [Brachydanio rerio Hamilton-Buchanan (Teleostei, Cyprinidae)])
2-n-butyl-benzo[d]isothiazol- 3-one 4299-07-4	LC50	0,15 mg/l	96 h	Salmo gairdneri (new name: Oncorhynchus mykiss)	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Fatty alcohol, C12-14, EO/PO 68439-51-0	EC50	5,4 mg/l	24 h	Daphnia magna	not specified
Alcohols, C10-16 ethoxylated propoxylated 69227-22-1	EC50	> 1 - 10 mg/l	24 h	Daphnia magna	DIN 38412, part 11
2-n-butyl-benzo[d]isothiazol- 3-one 4299-07-4	EC50	0,093 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity to aquatic invertebrates

No data available.

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Fatty alcohol, C12-14, EO/PO 68439-51-0	EC10	0,54 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	DIN 38412-09
Fatty alcohol, C12-14, EO/PO 68439-51-0	EC50	1,3 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	DIN 38412-09
Alcohols, C10-16 ethoxylated propoxylated 69227-22-1	EC50	> 1 - 10 mg/l	72 h	Desmodesmus subspicatus	DIN 38412-09
Alcohols, C10-16 ethoxylated propoxylated 69227-22-1	EC10	> 1 mg/l	72 h	Desmodesmus subspicatus	DIN 38412-09
2-n-butyl-benzo[d]isothiazol- 3-one 4299-07-4	ErC50	0,45 mg/l	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	not specified
2-n-butyl-benzo[d]isothiazol- 3-one 4299-07-4	NOEC	0,099 mg/l	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	not specified

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Fatty alcohol, C12-14, EO/PO 68439-51-0	EC0	1.000 mg/l	30 min		not specified

12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Fatty alcohol, C12-14, EO/PO 68439-51-0	readily biodegradable	aerobic	78 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Alcohols, C10-16 ethoxylated propoxylated 69227-22-1	readily biodegradable	not specified	> 70 %	30 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
2-n-butyl-benzo[d]isothiazol- 3-one 4299-07-4	2,86		not specified

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
Fatty alcohol, C12-14, EO/PO 68439-51-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

Waste code

161001

SECTION 14: Transport information

14.1. UN number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

National regulations/information (Germany):

WGK:	WGK 2: significantly water endangering (Ordinance on facilities for handling substances that are hazardous to water (AwSV)) Classification according to AwSV, Annex 1 (5.2)
------	---

Storage class according to TRGS 510:	10
--------------------------------------	----

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H302 Harmful if swallowed.
 H314 Causes severe skin burns and eye damage.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.