

Safety Data Sheet



Revision Number: 002.1

Issue date: 03/11/2025

1. IDENTIFICATION

Product name: GE Silicone Concrete Advanced
Specialty Projects
Product type/ Recommended use: Joint sealant, silicone

Restriction of Use: None identified

Company address:
Henkel Corporation
One Henkel Way
Rocky Hill, Connecticut 06067

IDH number: 2816709

Region: United States

Contact information:
Telephone: +1 (860) 571-5100
MEDICAL EMERGENCY Phone: Poison Control Center
1-877-671-4608 (toll free) or 1-303-592-1711
TRANSPORT EMERGENCY Phone: CHEMTREC
1-800-424-9300 (toll free) or 1-703-527-3887
Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING: H317 - MAY CAUSE AN ALLERGIC SKIN REACTION.
H361 - SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD.

HAZARD CLASS	HAZARD CATEGORY
SKIN SENSITIZATION	1
REPRODUCTIVE TOXICITY	2

PICTOGRAM(S)



Precautionary Statements

Prevention: P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P261 - Avoid breathing dust or fumes.
P272 - Contaminated work clothing should not be allowed out of the workplace.

Response: P280 - Wear protective gloves, clothing, eye and face protection.
P302+P352 - IF ON SKIN: Wash with plenty of water.
P308+P313 - IF exposed or concerned: Get medical attention.
P333+P313 - If skin irritation or rash occurs: Get medical attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.

Storage: P405 - Store locked up.

Disposal: P501 - Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Other hazards Not available.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*
Silica, amorphous, fumed, crystal-free	112945-52-5	5 - 10
1,1,1,3,3,3-Hexamethyldisilazane	999-97-3	1 - 5
Trimethoxy(methyl)silane	1185-55-3	1 - 5
Titanium dioxide	13463-67-7	1 - 5
octamethylcyclotetrasiloxane	556-67-2	0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

First Aid Measures by likely routes of exposure

Inhalation:	If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Move to fresh air. If symptoms persist, seek medical advice.
Skin contact:	Wipe off with paper towel or cloth. Rinse with running water and soap. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. Thoroughly clean shoes before reuse. Seek medical attention immediately.
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical attention immediately.
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Seek medical attention immediately.
Most important symptoms and effects (acute and delayed):	The most important known symptoms and effects, both acute and delayed, are described in Section 11: Toxicological Information.
Indication of any immediate medical attention / special treatment needed:	Not available.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Foam, dry chemical or carbon dioxide.
Improper extinguishing agents:	Not available.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Unusual fire or explosion hazards:	Closed containers may rupture (due to build up of pressure) when exposed to extreme heat. In case of fire, keep containers cool with water spray.
Hazardous combustion products:	Oxides of carbon. Oxides of silicon. Formaldehyde. Toxic and irritating vapors.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
-----------------------------------	---

Clean-up methods:

Ensure adequate ventilation. Wear appropriate personal protective equipment. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up spilled material and place in a closed container for disposal.

7. HANDLING AND STORAGE

Handling:

Use only with adequate ventilation. Vapours should be extracted to avoid inhalation. Avoid contact with eyes, skin and clothing. Do not wear contact lenses. Do not handle contact lenses until all sealant has been removed from hands. Residual sealant may transfer to lenses and cause eye irritation. Wash thoroughly after handling. See Section 8 of the SDS for Personal Protective Equipment. Keep container closed.

Storage:

Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Silica, amorphous, fumed, crystal-free	10 mg/m ³ TWA Inhalable dust. 3 mg/m ³ TWA Respirable fraction. 3 mg/m ³ TWA Respirable particles. 10 mg/m ³ TWA Inhalable particles.	20 MPPCF TWA 0.8 mg/m ³ TWA 50 MPPCF TWA Total dust. 5 mg/m ³ TWA Respirable fraction. 15 mg/m ³ TWA Total dust. 15 MPPCF TWA Respirable fraction.	None	None
1,1,1,3,3,3-Hexamethyldisilazane	None	None	10 ppm TWA 50 ppm STEL	None
Titanium dioxide	0.2 mg/m ³ TWA Respirable nanoscale particles 2.5 mg/m ³ TWA Respirable finescale particles	15 mg/m ³ PEL Total dust. 15 MPPCF TWA Respirable fraction. 15 mg/m ³ TWA Total dust. 50 MPPCF TWA Total dust. 5 mg/m ³ TWA Respirable fraction.	None	None
octamethylcyclotetrasiloxane	None	None	10 ppm TWA	None

Engineering controls:

Use local ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.

Respiratory protection:

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Eye/face protection:

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

Skin protection:

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:

Solid

Color:

Light gray / grey

Odor:

Alcoholic

Odor threshold:

Not available.

pH:

Not applicable

Vapor pressure:

Not applicable

IDH number: 2816709

Product name: GE Silicone Concrete Advanced Specialty Projects

Boiling point/range:	Not available.
Melting point/ range:	Not available.
Density/Relative density:	1.01 at 20 °C (68°F)
Relative vapor density:	Not available.
Flash point:	Not available.
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	Not available.
Solubility:	Not applicable
Partition coefficient n-octanol/water (logarithmic value):	Not available.
VOC content:	3 %; 31 g/l (by weight, calculated using CARB method; g/L less water, less exempts calculated using SCAQMD method)
Dynamic viscosity:	Not available.
Kinematic viscosity:	Not available.
Particle characteristics:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	None under normal processing.
Hazardous decomposition products:	Oxides of carbon. Oxides of silicon. Formaldehyde. Ammonia. Methanol.
Incompatible materials:	Acids and bases. Oxidizing agents. Amines.
Reactivity:	Not available.
Conditions to avoid:	Keep away from heat, ignition sources and incompatible materials. Protect from direct sunlight. Exposure to moisture.

11. TOXICOLOGICAL INFORMATION

Likely routes of exposure:	Skin, Inhalation, Eyes, Ingestion
-----------------------------------	-----------------------------------

Potential Health Effects/Symptoms

Inhalation: May cause respiratory tract irritation. When heated to temperatures exceeding 300° F (150° C) in the presence of air, silicones may form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Vapors irritate the eyes, nose and throat. Safe handling conditions may be maintained by keeping formaldehyde vapor concentrations below the OSHA permissible limit.

Skin contact: Prolonged or repeated skin contact may cause skin irritation or allergic skin sensitization reaction.

Eye contact: May cause eye irritation.

Ingestion: Not expected under normal conditions of use. May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s
Silica, amorphous, fumed, crystal-free	None
1,1,1,3,3,3-Hexamethyldisilazane	Oral LD50 (Rat) = 847 mg/kg Oral LD50 (Rabbit) = 1,100 mg/kg Oral LD50 (Mouse) = 850 mg/kg Inhalation LC50 (Rat, 4 h) = 8,700 mg/m3 Inhalation LC50 (Rat, 4 h) = 10.3 mg/l
Trimethoxy(methyl)silane	Inhalation LC50 (Rat, 4 h) = > 26000 ppm
Titanium dioxide	Inhalation LC50 (Rat, 4 h) = > 6.82 mg/l Inhalation LC50 (Rat, 4 h) = > 2.28 mg/l Inhalation LC50 (Rat, 4 h) = > 3.56 mg/l
octamethylcyclotetrasiloxane	Oral LD50 (Rat) = > 4,800 mg/kg Dermal LD50 (Rat) = > 2,000 mg/kg Dermal LD50 (Rabbit) = > 4,640 mg/kg Inhalation LC50 (Rat, 4 h) = 36 mg/l

Hazardous Component(s)	Immediate Health Effects	Delayed Health Effects	Chronic Health Effects
Silica, amorphous, fumed, crystal-free	Nuisance dust		
1,1,1,3,3,3-Hexamethyldisilazane	Irritant		
Trimethoxy(methyl)silane	Irritant	Allergen	
Titanium dioxide	Irritant		Respiratory Some evidence of carcinogenicity
octamethylcyclotetrasiloxane	Irritant		

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Silica, amorphous, fumed, crystal-free	No	No	No
1,1,1,3,3,3-Hexamethyldisilazane	No	No	No
Trimethoxy(methyl)silane	No	No	No
Titanium dioxide	No	Group 2B	No
octamethylcyclotetrasiloxane	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Environmentally hazardous substance, solid, n.o.s. (octamethylcyclotetrasiloxane)
Hazard class or division: 9
Identification number: UN 3077
Packing group: III

Water Transportation (IMO/IMDG)

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(octamethylcyclotetrasiloxane)
Hazard class or division: 9
Identification number: UN 3077
Packing group: III
Marine pollutant: octamethylcyclotetrasiloxane

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis.

CERCLA/SARA Section 311/312: Please refer to the GHS classification in Section 2

CERCLA/SARA Section 313: None above reporting de minimis.

California Proposition 65: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: Reviewed SDS. Reissued with new date.

Prepared by: Product Safety and Regulatory Affairs

Issue date: 03/11/2025

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.