



Revision Number: 003.0

Issue date: 06/23/2025

1. IDENTIFICATION

Product name: GE Pro Seal Max Kitchen and Bath
White
Product type/ Recommended use: Joint sealant, polymer silan-modified
Restriction of Use: None identified
Company address: Henkel Corporation
 One Henkel Way
 Rocky Hill, Connecticut 06067

IDH number: 3012017

Region: United States


Contact information:
 Telephone: +1 (860) 571-5100
 MEDICAL EMERGENCY Phone: Poison Control Center
 1-877-671-4608 (toll free) or 1-303-592-1711
 TRANSPORT EMERGENCY Phone: CHEMTREC
 1-800-424-9300 (toll free) or 1-703-527-3887
 MEDICAL EMERGENCY Phone: Poison Control Center
 1-877-671-4608 (toll free) or 1-303-592-1711
 TRANSPORT EMERGENCY Phone: CHEMTREC
 1-800-424-9300 (toll free) or 1-703-527-3887
 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: H315 - CAUSES SKIN IRRITATION.
 H317 - MAY CAUSE AN ALLERGIC SKIN REACTION.
 H319 - CAUSES SERIOUS EYE IRRITATION.
 H360 - MAY DAMAGE FERTILITY OR THE UNBORN CHILD.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1
REPRODUCTIVE TOXICITY	1B



Precautionary Statements

Prevention: P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P261 - Avoid breathing dust or fumes.
 P264 - Wash affected area thoroughly after handling.
 P272 - Contaminated work clothing should not be allowed out of the workplace.
 P280 - Wear protective gloves, clothing, eye and face protection.

Response: P302+P352 - IF ON SKIN: Wash with plenty of water.
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P313 - IF exposed or concerned: Get medical attention.
 P333+P313 - If skin irritation or rash occurs: Get medical attention.
 P337+P313 - If eye irritation persists: Get medical attention.
 P362+P364 - Take off contaminated clothing and wash it before reuse.

Storage: P405 - Store locked up.

Disposal: P501 - Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Other hazards Not available.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*
Limestone	1317-65-3	30 - 60
Phthalic acid, di(C9-11)alkylester, branched, C10-rich	68515-49-1	10 - 30
Benzene, mono-C10-13-alkyl derivs.	129813-58-7	1 - 5
Trimethoxyvinylsilane	2768-02-7	1 - 5
Titanium dioxide	13463-67-7	1 - 5
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	52829-07-9	0.1 - 1
dibutyltin dilaurate	77-58-7	0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

First Aid Measures by likely routes of exposure

Inhalation:	If inhaled, immediately remove the affected person to fresh air. If symptoms develop and persist, get medical attention.
Skin contact:	Immediately wash skin thoroughly with soap and water. If symptoms develop and persist, get medical attention.
Eye contact:	In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention.
Ingestion:	Get immediate medical attention. Do not induce vomiting.
Most important symptoms and effects (acute and delayed):	The most important known symptoms and effects, both acute and delayed, are described in Section 11: Toxicological Information.
Indication of any immediate medical attention / special treatment needed:	Treat symptomatically and supportively.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Improper extinguishing agents:	Not available.
Special firefighting procedures:	Wear protective equipment. Wear self-contained breathing apparatus.
Unusual fire or explosion hazards:	None identified.
Hazardous combustion products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Oxides of nitrogen.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Store in a partly filled, closed container until disposal. Spilled material will solidify. Scrape up as much material as possible. Maintain good ventilation for large spills.

7. HANDLING AND STORAGE

Handling: Do not handle contact lenses until all sealant has been removed from hands. Residual sealant may transfer to lenses and cause eye irritation. Avoid contact with eyes, skin and clothing. Keep out of the reach of children. Protect from moisture. Use only with adequate ventilation.

Storage: Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Limestone	10 mg/m3 TWA Inhalable particles. 3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Total dust.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 5 mg/m3 TWA Respirable fraction. 50 MPPCF TWA Total dust. 15 mg/m3 TWA Total dust. 15 MPPCF TWA Respirable fraction.	None	None
Calcium carbonate	10 mg/m3 TWA Total dust. 3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Inhalable particles.	15 mg/m3 PEL Total dust. 5 mg/m3 PEL Respirable fraction. 15 mg/m3 TWA Total dust. 50 MPPCF TWA Total dust. 15 MPPCF TWA Respirable fraction. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 PEL Total dust. 5 mg/m3 PEL Respirable fraction.	None	None
Titanium dioxide	0.2 mg/m3 TWA Respirable nanoscale particles 2.5 mg/m3 TWA Respirable finescale particles	15 mg/m3 PEL Total dust. 15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction.	None	None
dibutyltin dilaurate	0.1 mg/m3 TWA (as Sn) 0.2 mg/m3 STEL (as Sn) (SKIN) (as Sn)	0.1 mg/m3 PEL (as Sn)	None	None

Engineering controls: Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

Respiratory protection: If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

Eye/face protection: Wear chemical goggles; face shield (if splashing is possible).

Skin protection:

Wear impervious gloves for prolonged contact. Gloves should be tested to determine suitability for prolonged contact. Use of impervious apron and boots are recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Solid
Color:	White
Odor:	Alcohol
Odor threshold:	Not available.
pH:	Not applicable
Vapor pressure:	Not available.
Boiling point/range:	Not available.
Melting point/ range:	Not available.
Density/Relative density:	1.55 - 1.65
Relative vapor density:	Not available.
Flash point:	100 - 110 °C (212°F - 230°F) None
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	Not available.
Solubility:	Not available.
Partition coefficient n-octanol/water (logarithmic value):	Not available.
VOC content:	2.44 %; 36.6 g/l (by weight, calculated using CARB method; g/L less water, less exempts calculated using SCAQMD method)
Dynamic viscosity:	Not available.
Kinematic viscosity:	Not available.
Particle characteristics:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	None under normal processing.
Hazardous decomposition products:	Methanol is liberated slowly upon exposure to moisture.
Incompatible materials:	This product may react with strong acids or oxidizing agents.
Reactivity:	Not available.
Conditions to avoid:	Exposure to moisture.

11. TOXICOLOGICAL INFORMATION

Likely routes of exposure:	Skin, Inhalation, Eyes, Ingestion
-----------------------------------	-----------------------------------

Potential Health Effects/Symptoms

Inhalation:	Inhalation of vapors or mists of the product may be irritating to the respiratory system. May cause respiratory tract irritation.
Skin contact:	Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitisation of susceptible persons.
Eye contact:	This product may cause irritation to the eyes. Causes serious eye irritation.
Ingestion:	Not expected under normal conditions of use. May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s
Limestone	None
Phthalic acid, di(C9-11)alkylester, branched, C10-rich	None
Benzene, mono-C10-13-alkyl derivs.	None
Trimethoxyvinylsilane	Inhalation LC50 (Rat, 4 h) = 2773 ppm
Titanium dioxide	Inhalation LC50 (Rat, 4 h) = > 6.82 mg/l Inhalation LC50 (Rat, 4 h) = > 2.28 mg/l Inhalation LC50 (Rat, 4 h) = > 3.56 mg/l
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	Inhalation LC50 (Rat, 4 h) = 500 mg/m3
dibutyltin dilaurate	Oral LD50 (Rat) = 175 mg/kg

Hazardous Component(s)	Immediate Health Effects	Delayed Health Effects	Chronic Health Effects
Limestone	Nuisance dust		
Phthalic acid, di(C9-11)alkylester, branched, C10-rich	Irritant		
Benzene, mono-C10-13-alkyl derivs.			
Trimethoxyvinylsilane	Irritant	Allergen	
Titanium dioxide	Irritant		Respiratory Some evidence of carcinogenicity
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate			
dibutyltin dilaurate			

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Limestone	No	No	No
Phthalic acid, di(C9-11)alkylester, branched, C10-rich	No	No	No
Benzene, mono-C10-13-alkyl derivs.	No	No	No
Trimethoxyvinylsilane	No	No	No
Titanium dioxide	No	Group 2B	No
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	No	No	No
dibutyltin dilaurate	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

International Air Transportation (ICAO/IATA)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

Water Transportation (IMO/IMDG)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:	All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.
TSCA 12 (b) Export Notification:	None above reporting de minimis
CERCLA/SARA Section 302 EHS:	None above reporting de minimis.
CERCLA/SARA Section 311/312:	Please refer to the GHS classification in Section 2
CERCLA/SARA Section 313:	None above reporting de minimis.
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status:	Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.
------------------------------	---

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: This Safety Data Sheet contains changes from the previous version in Section(s): 2, 3, 8, 9, 11

Prepared by: Product Safety and Regulatory Affairs

Issue date: 06/23/2025

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.