



Revision Number: 002.2

Issue date: 04/09/2025


1. IDENTIFICATION

Product name:	GE Interior Fill Wall Repair	IDH number:	3019891
Product type/	Filler		
Recommended use:		Region:	United States
Restriction of Use:	None identified	Contact information:	
Company address:		Telephone:	+1 (860) 571-5100
Henkel Corporation		MEDICAL EMERGENCY Phone:	Poison Control Center
One Henkel Way		TRANSPORT EMERGENCY Phone:	CHEMTREC
Rocky Hill, Connecticut 06067		1-800-424-9300 (toll free) or 1-703-527-3887	
		MEDICAL EMERGENCY Phone:	Poison Control Center
		TRANSPORT EMERGENCY Phone:	CHEMTREC
		1-800-424-9300 (toll free) or 1-703-527-3887	
		Internet:	www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW	
WARNING:	H226 - FLAMMABLE LIQUID AND VAPOUR. H319 - CAUSES SERIOUS EYE IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	3
EYE IRRITATION	2A



Precautionary Statements

Prevention:	P210 - Keep away from heat, sparks, open flames, hot surfaces - no smoking. P233 - Keep container tightly closed. P241 - Use explosion-proof equipment. P242 - Use non-sparking tools. P243 - Take action to prevent static discharges. P264 - Wash affected area thoroughly after handling.
Response:	P280 - Wear protective gloves, clothing, eye and face protection. P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 - If eye irritation persists: Get medical attention.
Storage:	P370+P378 - In case of fire: Use foam, dry chemical or carbon dioxide to extinguish.
Disposal:	P403+P235 - Store in a well-ventilated place. Keep cool. P501 - Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Other hazards Not available.

The following percentage of the mixture consists of ingredient(s) with unknown acute oral toxicity: 3 %

The following percentage of the mixture consists of ingredient(s) with unknown acute dermal toxicity: 3 %

The following percentage of the mixture consists of ingredient(s) with unknown acute inhalation toxicity: 3 %

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*
Limestone	1317-65-3	30 - 60
2-Propanol	67-63-0	10 - 30
Kaolin	1332-58-7	5 - 10
Talc	14807-96-6	1 - 5
Quartz (SiO ₂), <1% respirable	14808-60-7	0.1 - 1
titanium dioxide	1317-70-0	0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

First Aid Measures by likely routes of exposure

Inhalation:	Move to fresh air. If symptoms persist, seek medical advice.
Skin contact:	Wash with soap and water. If skin irritation persists, call a physician.
Eye contact:	Immediately flush eyes with plenty of water for at least 15 minutes. If symptoms develop and persist, get medical attention.
Ingestion:	Do not induce vomiting. If symptoms develop and persist, get medical attention.
Most important symptoms and effects (acute and delayed):	The most important known symptoms and effects, both acute and delayed, are described in Section 11: Toxicological Information.
Indication of any immediate medical attention / special treatment needed:	Not available.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Improper extinguishing agents:	Not available.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Unusual fire or explosion hazards:	None known.
Hazardous combustion products:	Carbon dioxide. Carbon monoxide. Smoke.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Remove all sources of ignition. Do not allow product to enter sewer or waterways.
-----------------------------------	---

Clean-up methods:

Sweep up spilled material and place in a closed container for disposal. Avoid creating dust. Wash away residue with plenty of water.

7. HANDLING AND STORAGE

Handling:

Avoid breathing vapors or mists of this product. Avoid generating static electricity while handling. Use proper grounding procedures when handling near flammable or explosive materials.

Storage:

Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use. Keep away from heat, spark and flame. Keep from freezing.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Limestone	10 mg/m3 TWA Inhalable particles. 3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Total dust.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 5 mg/m3 TWA Respirable fraction. 50 MPPCF TWA Total dust. 15 mg/m3 TWA Total dust. 15 MPPCF TWA Respirable fraction.	None	None
2-Propanol	200 ppm TWA 400 ppm STEL	400 ppm (980 mg/m3) PEL	None	None
Kaolin	2 mg/m3 TWA Respirable fraction.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 15 MPPCF TWA Respirable fraction. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust.	None	None
Talc	2 mg/m3 TWA Respirable fraction.	0.1 mg/m3 TWA Respirable 20 MPPCF TWA 2.4 MPPCF TWA Respirable	None	50 ppm
Quartz (SiO ₂), <1% respirable	0.025 mg/m3 TWA Respirable fraction.	0.05 mg/m3 TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m3 OSHA_ACT (Respirable dust.) 0.05 mg/m3 PEL Respirable dust. 2.4 MPPCF TWA Respirable 0.1 mg/m3 TWA Respirable	None	None
titanium dioxide	3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Inhalable particles. 2.5 mg/m3 TWA Respirable finescale particles 0.2 mg/m3 TWA Respirable nanoscale particles	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction. 50 MPPCF TWA Total dust. 15 mg/m3 PEL Total dust.	None	None

Engineering controls:

General room ventilation is usually adequate.

Respiratory protection:

Not normally required. When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH for dust which may be generated from this product, underlying paint, or the abrasive.

Eye/face protection:

Safety goggles or safety glasses with side shields.

Skin protection:

None required in normal use. Wear impervious gloves for prolonged contact.
Wear suitable protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Color:	White
Odor:	Characteristic
Odor threshold:	< 400 ppm
pH:	7.0
Vapor pressure:	33 mm hg (20 °C (68°F))
Boiling point/range:	83 °C (181.4 °F)
Melting point/ range:	Not available.
Density/Relative density:	1.6
Relative vapor density:	2.1 (Air = 1)
Flash point:	23.5 °C (74.3 °F) Flash Point, Pensky-Martens
Flammable/Explosive limits - lower:	2 %
Flammable/Explosive limits - upper:	12 %
Autoignition temperature:	460 °C (860°F)
Flammability:	Not applicable
Evaporation rate:	1.4 (Butyl acetate = 1)
Solubility:	Miscible
Partition coefficient n-octanol/water (logarithmic value):	Not available.
VOC content:	< 1 %
Dynamic viscosity:	Not available.
Kinematic viscosity:	Not available.
Particle characteristics:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under recommended storage conditions. Electrostatic charge may build-up during handling. Grounding of equipment is recommended.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Oxides of carbon.
Incompatible materials:	Heat. Strong oxidizing agents.
Reactivity:	Not available.
Conditions to avoid:	See "Handling and Storage" (Section 7) and "Incompatibility" (Section 10).

11. TOXICOLOGICAL INFORMATION

Likely routes of exposure:	Skin, Inhalation, Eyes, Ingestion
-----------------------------------	-----------------------------------

Potential Health Effects/Symptoms

Inhalation: Abrasion of cured material such as by sanding or grinding could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of this product causes no such release. Prolonged and/or repeated skin contact with this product may cause irritation/dermatitis.

Skin contact:

Eye contact: May cause moderate eye irritation.

Ingestion: Ingestion may cause stomach ache and vomiting.

Hazardous Component(s)	LD50s and LC50s
Limestone	None
2-Propanol	Oral LD50 (Rat) = 5,045 mg/kg Oral LD50 (Mouse) = 3,600 mg/kg Oral LD50 (Rabbit) = 6,410 mg/kg Oral LD50 (Rat) = 4.7 g/kg Oral LD50 (Mouse) = 4.5 g/kg Oral LD50 (Rabbit) = 8.0 g/kg Oral LD50 (Rabbit) = 5.03 g/kg Dermal LD50 (Rabbit) = 12,800 mg/kg
Kaolin	Oral LD50 (Rat) = > 5,000 mg/kg Dermal LD50 (Rat) = > 5,000 mg/kg
Talc	None
Quartz (SiO ₂), <1% respirable	None
titanium dioxide	None

Hazardous Component(s)	Immediate Health Effects	Delayed Health Effects	Chronic Health Effects
Limestone	Nuisance dust		
2-Propanol	Irritant	Allergen	Central nervous system
Kaolin	Nuisance dust		
Talc	Irritant		Lung Some evidence of carcinogenicity
Quartz (SiO ₂), <1% respirable			Immune system Lung Some evidence of carcinogenicity
titanium dioxide	Nuisance dust		

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Limestone	No	No	No
2-Propanol	No	Group 1	No
Kaolin	No	No	No
Talc	No	Group 2A	No
Quartz (SiO ₂), <1% respirable	Known To Be Human Carcinogen.	Group 1	Yes
titanium dioxide	No	Group 2B	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Flammable liquids, n.o.s. (Isopropanol)
Hazard class or division: 3
Identification number: UN 1993
Packing group: III

International Air Transportation (ICAO/IATA)

Proper shipping name: Flammable liquid, n.o.s. (Isopropanol)
Hazard class or division: 3
Identification number: UN 1993
Packing group: III

Water Transportation (IMO/IMDG)

Proper shipping name: FLAMMABLE LIQUID, N.O.S. (Isopropanol)
Hazard class or division: 3
Identification number: UN 1993
Packing group: III

15. REGULATORY INFORMATION**United States Regulatory Information**

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis.
CERCLA/SARA Section 311/312: Please refer to the GHS classification in Section 2
CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). 2-Propanol (CAS# 67-63-0).

California Proposition 65: This product contains a chemical known in the State of California to cause cancer.

Canada Regulatory Information

CEPA DSL/NDSL Status: Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: This Safety Data Sheet contains changes from the previous version in Section(s): 2

Prepared by: Product Safety and Regulatory Affairs

Issue date: 04/09/2025

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.